



RHINO
ANTI-FATIGUE MATS

*Comfort ☆ Craft®
Premium Fall Mats*

DATA & SPEC SHEETS

The Comfort Craft Advantage:

Unmatched Safety Features: Molded bevel edges - They will never curl up, eliminating trip hazards.
Highest Quality: Virgin raw materials only - Integral skin - one-piece construction guarantees unbeaten durability - Silicone and Latex-free.

Hospital Safe: Anti-bacterial and Mildew/Mold resistant. Anti-static.

The Comfort Craft Advantage: Chemical and UV exposure will not affect the state of the top surface of the mat - No curling up - No swelling - No expanding.

The closed-cell/non-porous surface allows for wash down and cleaning. In case washing is necessary, wash surface with soap water (pH range 2-9.5).

SPECS

Material		Integral Skin Polyurethane Foam
Size		24" x 36" / 6 lbs. 24" x 72" / 12 lbs. 36" x 60" / 13 lbs.
Thickness		.750"
Density	ISO 2781	400 kg/m ³ +/-10%
Hardness	DIN 53505	37-54 Sh A
Surface Durability	DIN 4649 teset equip. with 2,5N load	30 m
Fire test	DIN 4102 Part 1/ section 6.1	Flame Retardant
Surface		100% PVC
Surface Tear	ASTM D 751-06	36 lbs/in x 36 lbs/in
Flex Resistance	ASTM D 2097-03 (2010)	25,000 Cycles
Cold Crack Resistance	CFFA-6a	-20°F Pass
Mildew Resistance	ASTM G-21	Pass
Anti-Bacterial	AATCC 147-2004	Pass
Surface Abrasion	ASTM D 4157-92	500,000 cycles, #10 cotton duct
UV Stability	ASTM D 4329-05	650 hours
Surface Flammability	Calif. Bulletin 117-2013, Section 1 U.F.A.C. Class I NFPA 260 I.M.O. A.652 (16) Sec. 8.2 & 8.3	Pass Pass Pass Pass

Comfort*Craft mats should be stored or inventoried flat. Mats rolled and boxed should be inventoried this way for short periods of time.

Roll the mat with top surface to the outside - failure to roll the mat correctly may result in damage to the mat and will not be covered under warranty.