



DATA & SPEC SHEETS

The Comfort Craft Advantage:

Unmatched Safety Features: Molded bevel edges - They will never curl up, eliminating trip hazards. **Highest Quality:** Virgin raw materials only - Integral skin - one-piece construction guarantees unbeaten durability - Silicone and Latex-free.

The Comfort Craft Advantage: Chemical and UV exposure will not affect the state of the top surface of the mat - No curling up - no swelling - no expanding.

The closed-cell/non-porous surface allows for wash down and cleaning. In case washing is necessary, wash surface with soap water (pH range 2 - 9.5). Anti-static properties assure no hair clinging.

Limited Warranty:

All Comfort*Craft products are conditionally warranted against normal home usage for a period of 5 years after date of purchase to the original purchaser. It is considered normal usage when a person stands or walks on the Comfort*Craft mat with regular footwear. Comfort*Craft mats are "not" guaranteed against puncture by shoes with stiletto, spike heels or any other similar sharp objects. All warranty claims must be initiated by the end user of the mat and made directly to Ranco Industries, Inc. Please do not take product back to the distributor or retailer. If a claim is made, we need 3 photos: a close up of the damaged area,an image of the entire top surface, and an image of the underside of the mat. We will also need a copy of the original proof of purchase (invoice), your name, street address, phone number, and e-mail address. A representative will contact you once all the above information has been received.

Please forward the information to Ranco Industries, Inc. e-mail or regular mail care of: Ranco Industries, Inc.

3421 Rusk Houston, TX 77003

Attn: Warranties info@rhinomats.com

SPEC DATA			
Material		Integral Skin Polyurethane Foam	
Top Surface		Decorative	
Size		24" x 36" / 6 lbs. 24" x 72" / 12 lbs. 36" x 60" / 13 lbs.	
Thickness		.750"	
Density	ISO 2781	400 kg/m³ +/-10%	
Hardness	DIN 53505	37-54 Sh A	
Surface Durability	DIN 4649 teset equip. with 2,5N load	30 m	
Fire test	DIN 4102 Part 1/ section 6.1	Flame Retardant	
Warranty		5 years	

CHEMICAL RESISTANCE			
TYPE	TOP	BACK	
Weak Acid	Good	Fair	
Strong Acid	Fair	Poor	
Weak Alkalis	Good	Fair	
Strong Alkalis	Fair	Poor	
Organic Solvents	Poor	Fair	
Alcohols	Fair	Fair	
Hydrocarbons	Excellent	Fair	
Water	Excellent	Fair	
UV Radiation	Good	Poor	

STORING AND PACKAGING

Comfort*Craft mats should be stored or inventoried flat. Mats rolled and boxed should be inventoried this way for short periods of time.

Roll the mat with top surface to the outside - failure to roll the mat correctly may result in damage to teh mat and will not be covered under warranty.