

m o o o i

# Plant Chandelier

KRANEN/GILLE



The philosophy behind the Plant Chandelier, designed by Kranen/Gille, is the imitation of nature's structures while indulging in the poetry of their beauty. Inspired by the linear patterns of Karl Blossfeldt's plant photography, and unrestricted by cables or wires, the Plant Chandelier is free to elegantly bloom towards the ceiling. Its silhouette follows the anatomy of sun-kissed tree branches, with a golden glow, which converges into frosted domes of light.

---

## *Detailing*



The Plant Chandelier captivates the architectural uniformity in nature's design, with its branches that grow and spread in definite directions.

---

## *Colours*



Brass


# Plant Chandelier

## Dimensions

90cm | 35.4"



78cm | 30.7"



80cm | 31.5"



105cm | 41.3"

## Product

**WIDTH** 90cm | 35.4"

**HEIGHT** 80cm | 31.5"

**DEPTH** 78cm | 30.7"

**WEIGHT NETTO** 20kg | 44.09lbs

## Packaging

**WIDTH** 92cm | 36.2"

**HEIGHT** 91cm | 35.8"

**CUBAGE** 0.84m<sup>3</sup> | 29.57ft<sup>3</sup>

**LENGTH** 100cm | 39.4"

**WEIGHT** 27.5kg | 60.63lbs

## Technical CE

### MATERIAL

Steel frame, glass diffusers

### ENERGY LABEL

A

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

8

### INPUT VOLTAGE

220-240

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

16W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Transparent with tinned cores

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

2700 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

1318 lm

### EEI

0.17

### EFFICIENCY

82.38 lm/W

## Technical cULus

### MATERIAL

Steel frame, glass diffusers

### ENERGY LABEL

### LIGHTSOURCE INCLUDED

Yes

### INPUT VOLTAGE

110-130

### MAX POWER CONSUMPTION

16W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Transparent with tinned cores

### CANOPY

Matching steel cylinder

### CRI

80

### LIGHT OUTPUT

1318 lm

### EFFICIENCY

82.38 lm/W

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

8

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### COLOUR TEMPERATURE

2700 K

### LIGHT DIRECTION

All directions

### EEI

0.17

---

## Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

### DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

### LOAD TYPE

Capacitive load (C-Type)

---