

m o o o i

Prop Light Floor

BERTJAN POT



"We have round lights, we have straight lights. We have them with lights on one side, we have them with lights on two sides. You can hang them high, low, horizontally, vertically or even hang them in an angle. Put them on the floor, hang them on your wall or down from the ceiling. We find it very hard to imagine an interior where this prop is not in place" - Bertjan Pot

Detailing



A theatrical, extravagant lamp that can be place on the floor. Its bubbly form and pure spirit brightens up any kind of environment.

Colours

2000K
Warm White

2700K
Soft White


Prop Light Floor / Vertical

Dimensions

25cm | 9.8"



107cm | 42.1"



Product

WIDTH 25cm | 9.8"
HEIGHT 107cm | 42.1"
DEPTH 25cm | 9.8"
WEIGHT NETTO 8kg | 17.64lbs

Packaging

WIDTH 30cm | 11.8"
HEIGHT 30cm | 11.8"
CUBAGE 0.12m³ | 4.23ft³
LENGTH 133cm | 52.4"
WEIGHT 10kg | 22.05lbs

Technical CE

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

18

SHAPE

Linear

INPUT VOLTAGE

110-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

10.3W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

Europlug (Type-C)

CABLE LENGTH

250cm | 98.4"

SWITCH

In line on/off switch

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

499 lm

Technical cULus

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

18

SHAPE

Linear

INPUT VOLTAGE

110-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

10.3W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

CABLE LENGTH

250cm | 98.4"

SWITCH

In line on/off switch

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

499 lm



Prop Light Floor / Round

Dimensions

73cm | 28.7"



32cm | 12.6"



82cm | 32.3"

Product

WIDTH 73cm | 28.7"

HEIGHT 82cm | 32.3"

DEPTH 32cm | 12.6"

WEIGHT NETTO 10kg |

22.05lbs

Packaging

WIDTH 88cm | 34.6"

HEIGHT 34cm | 13.4"

CUBAGE 0.27m³ | 9.4ft³

LENGTH 89cm | 35"

WEIGHT 15kg | 33.07lbs

Technical cULus

ADDITIONAL

The Proplight is available in two colour temperatures: 2000K or 2700K.

MATERIAL

HIPS housing, PMMA light guide, glass bulbs

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

48

SHAPE

Disc

INPUT VOLTAGE

110-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

21W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

PLUG TYPE

US plug (Type A)

CABLE LENGTH

250cm | 98.4"

SWITCH

In line on/off switch

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1079 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

DIMMER TYPE

Integrated dimmer

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.
