SE-G5.1 Pro





◆ Safer

Cobalt Free Lithium Iron Phosphate (LFP) Battery: Safety and long Lifespan, high efficiency and high-Power density. Intelligent BMS, providing complete protection.

♦ Reliable

♦ Flexible

Modular design, easy to expand, Max. 64 units in parallel, Max. capacity of 327kWh.

Suited to residential and commercial applications for increasing the self-consumption ratio.

♦ Convenient

Battery module auto networking, Automatic IP addressing, Easy maintenance, remotely monitoring and upgrade, Support USB drive upgrade the firmware.

♦ Eco-Friendly

Use environmental protection materials, the whole module non -toxic, pollution-free.

Technical Data

| Model | | SE-G5.1 Pro |
|--|--------------------------|---|
| Main Parameter | | |
| Battery Chemistry | | LiFePO4 |
| Capacity (Ah) | | 100 |
| Scalability(Max. in 1 battery group) | | Max. 64 pcs pack (327kWh) in parallel (Max. 32 pcs no external setup) |
| Nominal Voltage (V) | | 51.2 |
| Operating Voltage (V) | | 43.2~57.6 |
| Energy (kWh) | | 5.12 |
| Usable Energy (kWh) ^[1] | | 4.61 |
| Charge/Discharging Current(A) | Recommend ^[2] | 50 |
| | Max ^[2] | 100 |
| | Peak (2 mins,25°C) | 150 |
| Other Parameter | | |
| Depth of Discharge | | 90% |
| Dimension (W/H/D,mm) | | 445*133*430 |
| Weight Approximate (kg) | | 45 |
| Master LED indicator | | 5LED(SOC:20%~100%), 3LED(working,alarming,protecting) |
| IP Rating of Enclosure | | IP20 |
| Altitude | | ≤2000m |
| Working Temperature (°C) | | Charge: 0~55/Discharge: -20~55 |
| Storage Temperature | | 0°C ~ 35°C |
| Humidity | | 5%~95% |
| Cycle Life | | 25±2°C ,0.5C/0.5C,70%EOL≥6000 |
| Installation Location | | 19-inch standard cabinet, cabinet depth ≥600mm / with rack |
| Communication Port | | CAN2.0, RS485 |
| Warranty | | 10 years |
| Life Cycle Power During Warranty Period ^[3] | | 16MWh@70%EOL |
| Certification | | UL1973, IEC62619, IEC61000, CE, UN38.3 |

- [1] DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.
- [2] The current is affected by temperature and SOC.
- $\label{eq:continuous} \ensuremath{\text{[3]}} \ensuremath{\text{The warranty is due whichever reached first of warranty period or life cycle power.}}$

Introduction

This series lithium iron phosphate battery is one of new energystorage products developed and produced by Deye, it can be used to support reliable power for various types of equipment and systems.

This series is especially suitable for application scene of high power, limited installation space, restricted load-bearing and long cycle life.

This series has built-in BMS battery management system, which can manage and monitor cells information including voltage, current and temperature. What's more, BMS can balance cells charging and discharging to extend cycle life.

Multiple batteries can connect in parallel to expand capacity and power in parallel for larger capacity and longer power supporting duration requirements.