

WARNING!

- Installation is the end user's responsibility and beyond THORNY DEVIL's control. Therefore, THORNY DEVIL exclusively limits its warranty to the repair or replacement of a defective product. Damage to your vehicle, your cargo or any person or property is excluded.
- DO NOT lift or take down the carrier bag full of luggage by pulling the rack straps attached to the bag.
- Place more luggage to AVOID the zipper lying flat, so as to reduce the water accumulation on the zipper.
- INSPECT for signs of wear and damage BEFORE each use. DO NOT use if worn or damaged.
- DO NOT EXCEED your vehicle's rated roof capacity.
- DO NOT attempt to modify your rainproof cargo bag or any of the system components. Sharp objects must be properly wrapped and secured so as not to puncture the cargo bag.
- DO NOT use your rainproof cargo bag to transport people, animals, flammable liquids, or for purpose other than those for which it was designed.
- Remove your cargo bag when not in use and before entering automatic car washes.
- Check local and state laws governing projection of objects beyond the perimeter of a vehicle. Be aware of the width and height of your cargo since low clearance branches, bridges, and parking garages can affect the load.
- Your rainproof cargo bag will not prevent property damage that may result from improper loading, securing, or driving.
- It is the responsibility of the driver of the vehicle to ensure the cargo bag is correctly secured before driving the vehicle.

INSTALLATION ON CARGO CARRIER

1. Inspect cargo bag for any missing straps or damage. Make sure the straps and buckles are intact.
2. Place the empty cargo bag on the cargo carrier. Ensure the cargo bag is facing forwards - with the handle facing towards the FRONT of the car.
3. Open the bag and load cargo into the bag. Place heavy, large objects in first. This may require a second person help you. Continue loading lighter items on the top creating a compact load.
4. Close the zipper completely, and fold the yellow flap down so that the zipper is completely covered. Use the hook & loop tabs to hold this flap in place.
5. Pass the straps through the cargo carrier and the bag as pictured and buckle the straps. Ensure all straps are tightened as much as they can be.
6. Before driving vehicle, ensure the cargo bag is properly secured.

