

#### THE EMERALD CITY FOLD EBIKE



### Scan to learn more!

# **Highlights**

Fully assembled Magnesium alloy frame Top speed 20 mph Up to 30 mile range Ultra compact, folding and rolling design Integrated wheel for easy moving when folded Removable 36V battery Waterproof grade IPX5 16" x 2.13" tires Mechanical disc brake Thumb throttle Magnetic buckle (when folded) 5-Year Limited Warranty

#### **Colors**





Matte Black

### Recommendations

Rider Height	4'11" - 6'0"
Rider Weight	Max 240 lbs
Handlebar Torque	Bolt for Handlebar Bolt: 19M.N Standard Torque / N.M: 20
Maintenance	Routine, see user manual

#### **Bike Parts**

Weight	43 lbs without battery, 48 lbs with battery
Frame & Fork	Magnesium Alloy / Internal Battery
Motor	300W
Display	LED
Battery	36V 7.5AH (7.8AH)
Throttle	Thumb Throttle
Pedal Assist	CLASS 1-5 levels
Range	30 miles
Max Speed	16-20 MPH*
Brakes	Mechanical Disc Brake
Brake Lever	Electric Cut-Off While Braking
Handlebar	Alloy
Headset	Alloy
Grips	Rubber
Stem	Alloy, Folding
Saddle	PU
Seatpost	Alu 31.6*300
Tires	16*2.125 inch WANDA
Tubes	16*2.125 inch WANDA
Wheel	Intergrated Wheel
Cassette	Single Speed 16T
Chain	КМС
Crankset	46T
Pedals	Foldable
Front Light	LED
Rear Light	LED
Lock	None

\*On throttle only, flat surface, and no wind: If rider is under 150 lbs on a flat surface and there is no wind, top speed is 20 MPH. If rider is over 225 lbs, top speed is 16 MPH.



#### THE EMERALD CITY FOLD EBIKE





#### **Measurements When Folded**

Length	39 inches
Width	17.70 inches
Height	20.90 inches

## **Frame Size Measurements**

Top Tube Length	24.01 inches
Reach	22.83 inches
Head Tube Length	17.31 inches
Standover Height	17.70 inches
Wheelbase	39.40 inches
Min Saddle Height	30.70 inches
Max Saddle Height	36.20 inches

## **Electric Specs**

=icoti io opeos	
Battery	Nominal Voltage: 36V Nominal: 7.5AH (7.8AH) Weight (Approx.): 5 lb
Motor	Motor Parameters: 300W hub-motor Speed: 20 MPH Top Speed: 20 MPH Maximum Torque: 35N.m Noise Level: <=55 Weight: 4lbs (with alu mag wheel)
Display	LED
PAS	Model: BZ-4 Rated Voltage: 5V Installation Direction: Right Color: Black
Charger	Input: 120V~50V 60HZ 2.0A Model: DPLC048V42Y Output: 42.0V-2.0A
Throttle	Size: L 68mm W 40mm H 30mm Waterproof: IPX5 Materials: PC/ABS Wiring: Non integrated wire with SM connector Power: 5V