

SAFETY DATA SHEET.



Issuing date 03/01/2022

Revision Date 03/01/2022

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name PAINTABLE RUBBERIZED UNDERCOAT

Recommended use of the chemical and restrictions on use

Product code HT 18023

Product Type Extremely flammable aerosol
Synonyms None

Supplier's details

Recommended Use Undercoating.
Uses advised against No information available

Manufactured For:
Hi-Tech Industries
33106 W. 8 Mile
Farmington, MI 48336
Company Telephone: 248-358-2626

Chemical Emergency Phone Number INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

| | |
|--|----------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2A |
| Carcinogenicity | Category 2 |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity | Category 1 |
| Flammable aerosols | Category 1 |
| Gases under pressure | Compressed Gas |

GHS Label elements, including
precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
 Causes serious eye irritation
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs (central nervous system, eyes, kidney, liver, respiratory system, and skin) through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated



Appearance opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 Specific treatment (see first aid on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

- Toxic to aquatic life with long lasting effects

0.60675508% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No | Weight %* |
|-------------------|------------|-----------|
| CALCIUM CARBONATE | 1317-65-3 | 30-40 |
| TOLUENE | 108-88-3 | 10-20 |
| METHYL ACETATE | 79-20-9 | 1-10 |
| ACETONE | 67-64-1 | 1-10 |
| SOLVENT NAPHTHA | 64742-94-5 | 0.1-1 |
| XYLENE | 1330-20-7 | 0.1-1 |
| CARBON BLACK | 1333-86-4 | 0.1-1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

| | |
|---------------------|---|
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. |
| Inhalation | Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately. |
| Ingestion | Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately. |

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. Irritating to respiratory system. May cause drowsiness or dizziness. May damage to fertility or the unborn child. May cause cancer. Harmful or fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling. Ensure adequate ventilation.

Environmental precautions

Environmental precautions Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods and materials for containment and cleaning up

Methods for Containment Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents.

Aerosol Level 1

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------------------|---|---|---|
| CALCIUM CARBONATE 1317-65-3 | - | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| TOLUENE 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| METHYL ACETATE 79-20-9 | STEL: 250 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 610 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m ³ | IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³ |
| ACETONE 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| XYLENE 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³ | - |
| CARBON BLACK 1333-86-4 | TWA: 3 mg/m ³ inhalable fraction | TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³ | IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

| | | | |
|-----------------------|---------|-----------------------|--------------------------|
| Physical state | Aerosol | Odor | Solvent |
| Appearance | opaque | Odor Threshold | No information available |
| Color | black | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Methods</u> |
|---|--------------------------|--------------------------|
| pH | No information available | |
| Melting/freezing point | No information available | |
| Boiling point/boiling range | No information available | |
| Flash Point | -104 °C / -155 °F | Based on propellant |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limits in Air | | |
| upper flammability limit | No information available | |
| lower flammability limit | No information available | |
| Vapor pressure | No information available | |
| Vapor density | No information available | |
| Specific Gravity | 1.2 | |
| Water solubility | Practically insoluble | |
| Partition coefficient: n-octanol/water | No information available | |
| Autoignition temperature | No information available | Not applicable |
| Decomposition temperature | No information available | |
| Viscosity | No information available | |
| Explosive properties | No information available | |

Other information

VOC Content(%) 39.77

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

| | |
|---------------------|--|
| Inhalation | Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists. |
| Eye contact | Irritating to eyes. Avoid contact with eyes. |
| Skin contact | Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin. |
| Ingestion | May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal. |

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------------------|----------------------|--------------------------|---------------------------------------|
| TOLUENE 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| METHYL ACETATE 79-20-9 | > 5000 mg/kg (Rat) | > 5 g/kg (Rabbit) | = 16000 ppm (Rat) 4 h |
| ACETONE 67-64-1 | = 5800 mg/kg | 20,000 mg/kg (Rabbit) | = 50100 mg/m ³ (Rat) 8 h |
| SOLVENT NAPHTHA 64742-94-5 | > 5000 mg/kg (Rat) | > 2 mL/kg (Rabbit) | > 590 mg/m ³ (Rat) 4 h |
| XYLENE 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms Inhalation may cause nose, throat, and respiratory tract irritation. Irritation to skin and eyes. May be harmful if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|----------------------------------|--|
| Skin corrosion/irritation | Irritating to skin. |
| Eye damage/irritation | Irritating to eyes. |
| Irritation | Irritating to eyes, respiratory system and skin. |
| Sensitization | None known. |
| Germ Cell Mutagenicity | None known. |
| Carcinogenicity | The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen. |

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------|-------|------|-----|------|
| | | | | |

| | | | | |
|---------------------------|----|----------|---|---|
| TOLUENE 108-88-3 | - | Group 3 | - | - |
| XYLENE 1330-20-7 | - | Group 3 | - | - |
| CARBON BLACK 1333-86-4 | A3 | Group 2B | - | - |

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2B - Possibly Carcinogenic to Humans

| | |
|--|---|
| Reproductive toxicity | Product is or contains a chemical which is a known or suspected reproductive hazard. |
| Specific target organ systemic toxicity (single exposure) | May cause respiratory irritation. May cause drowsiness and dizziness. |
| Specific target organ systemic toxicity (repeated exposure) | May cause damage to organs through prolonged or repeated exposure. |
| Chronic toxicity | May cause adverse liver effects. |
| Target Organ Effects | Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin. |
| Neurological effects | Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. |
| Aspiration hazard | May be fatal if swallowed and enters airways. |

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.60675508% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 12549 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to microorganisms | Toxicity to daphnia and other aquatic invertebrates |
|---------------------------|--|---|----------------------------|--|
| TOLUENE 108-88-3 | 433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static | 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static 12.6 mg/L LC50 Pimephales promelas 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 54 mg/L LC50 Oryzias latipes 96h static | - | 5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h |
| METHYL ACETATE 79-20-9 | 120 mg/L EC50 Desmodesmus subspicatus 72h | 250 - 350 mg/L LC50 Brachydanio rerio 96h static 295 - 348 mg/L LC50 Pimephales promelas 96h flow-through | - | 1026.7 mg/L EC50 Daphnia magna 48h |
| ACETONE 67-64-1 | - | 4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h | - | 10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h |

| | | | | |
|-------------------------------|---|---|---|--|
| SOLVENT NAPHTHA 64742-94-5 | - | 1740 mg/L LC50 Lepomis macrochirus 96h static 19 mg/L LC50 Pimephales promelas 96h static 2.34 mg/L LC50 Oncorhynchus mykiss 96h 41 mg/L LC50 Pimephales promelas 96h 45 mg/L LC50 Pimephales promelas 96h flow-through | - | 0.95 mg/L EC50 Daphnia magna 48h |
| XYLENE 1330-20-7 | - | 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 13.4 mg/L LC50 Pimephales promelas 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h | - | 0.6 mg/L LC50 Gammarus lacustris 48h 3.82 mg/L EC50 water flea 48h |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical Name | log Pow |
|-------------------------------|---------|
| TOLUENE 108-88-3 | 2.65 |
| METHYL ACETATE 79-20-9 | 0.18 |
| ACETONE 67-64-1 | -0.24 |
| SOLVENT NAPHTHA 64742-94-5 | 6.1 |
| XYLENE 1330-20-7 | 3.15 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

| Chemical Name | TSCA | DSL/NDSL | EINECS/ELI NCS | ENCS | IECSC | KECL | PICCS | AICS |
|-------------------|------|----------|-------------------|------|-------|------|-------|------|
| CALCIUM CARBONATE | X | X | X | X | X | X | X | X |
| TOLUENE | X | X | X | X | X | X | X | X |
| METHYL ACETATE | X | X | X | X | X | X | X | X |
| ACETONE | X | X | X | X | X | X | X | X |
| SOLVENT NAPHTHA | X | X | X | X | X | X | X | X |
| XYLENE | X | X | X | X | X | X | X | X |
| CARBON BLACK | X | X | X | X | X | X | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name | CAS-No | Weight %* | SARA 313 - Threshold Values % |
|--------------------|-----------|-----------|-------------------------------|
| TOLUENE - 108-88-3 | 108-88-3 | 10-20 | 1.0 |
| XYLENE - 1330-20-7 | 1330-20-7 | 0.1-1 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | Yes |
| Reactive Hazard | no |

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| TOLUENE 108-88-3 | 1000 lb | X | X | X |
| XYLENE 1330-20-7 | 100 lb | | | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|---------------------|--------------------------|------------------------------------|--|
| TOLUENE 108-88-3 | 1000 lb 1 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| ACETONE 67-64-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| XYLENE 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|--------------------------|--------------------------------------|
| TOLUENE - 108-88-3 | Developmental Female Reproductive |
| CARBON BLACK - 1333-86-4 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--------------------------------|------------|---------------|--------------|
| CALCIUM CARBONATE 1317-65-3 | X | X | X |
| TOLUENE 108-88-3 | X | X | X |
| METHYL ACETATE 79-20-9 | X | X | X |
| ACETONE 67-64-1 | X | X | X |
| XYLENE 1330-20-7 | X | X | X |
| CARBON BLACK 1333-86-4 | X | X | X |

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

| | | | | |
|-------------|------------------|----------------|-------------------|---------------------------------|
| NFPA | Health Hazard 2 | Flammability 4 | Instability 0 | Physical and chemical hazards - |
| HMIS | Health Hazard 2* | Flammability 4 | Physical Hazard 2 | Personal protection B |

Prepared By Regulatory Affairs
Issuing date 03/01/2022
Revision Date 03/01/2022
Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet