

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 STINGER® DURATION

SDS DATE: 02/19/2018 ORIGINAL: 10/01/2013

# SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

#### SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: 595 STINGER® DURATION PRODUCT USES: Cleaning compound

COMPANY IDENTITY: Stinger Chemical LLC COMPANY ADDRESS: 905 Live Oak Street COMPANY CITY: Houston, TX 77003 COMPANY PHONE: 1-713-227-1340

EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA)

CANUTEC: 1-613-996-6666 (CANÁDA)

# **SECTION 2. HAZARDS IDENTIFICATION**

# WARNING!

2.1 HAZARD STATEMENTS: (CAT = Hazard Category)
 (H300s) HEALTH: Skin Corrosion/Irritation(CAT:2)
H315 CAUSES SKIN IRRITATION.
 (H300s) HEALTH: Serious Eye Damage/Eye Irritation(CAT:2)
H320 CAUSES EYE IRRITATION.



#### 2.2 PRECAUTIONARY STATEMENTS:

EXPOSURE PREVENTION: PREVENT DISPERSION OF MISTS OR DUST!

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present & easy to do - Continue rinsing.
P337+313 If eye irritation persists, get medical advice/attention.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Water	7732-18-5	231-791-2	55-65
Dimethylsiloxane	63148-62-9	_	15-30
C9-11 Álcohol Ethoxylate	68081-81-2	_	2- 7
Dipropylene Glycol	25265-71-8	246-770-3	2- 6
Glycerol	56-81-5	_	2- 5
Triethanolamine	102-71-6	203-049-8	1- 3
Methyl Chloro Isothiazolinone	26172-55-4	_	0- 1

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets. This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (I)(1).

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 STINGER® DURATION

#### SECTION 4. FIRST AID MEASURES

4.1 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC: See Section 11 for Symptoms/Effects (acute & chronic).

#### 4.2 EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

#### 4.3 SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

#### 4.4 INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

#### 4.5 SWALLOWING:

Rinse mouth. Give plenty of water to drink. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

# **SECTION 5. FIRE FIGHTING MEASURES**

- 5.1 FIRE & EXPLOSION PREVENTIVE MEASURES: NO open flames.
- 5.2 SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:
  Use dry powder, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.
- 5.3 SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS:
  Water spray may be ineffective on fire but can protect fire-fighters
  & cool closed containers. Use fog nozzles if water is used.
  Do not enter confined fire-space without full bunker gear.
  (Helmet with face shield, bunker coats, gloves & rubber boots).
- 5.4 SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS: SLIGHTLY COMBUSTIBLE!

Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Continue all label precautions!

# SECTION 6. ACCIDENTAL RELEASE MEASURES

- 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES: Keep unprotected personnel away.
  Wear appropriate personal protective equipment given in Section 8.
- 6.2 ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

6.3 METHODS & MATERIAL FOR CONTAINMENT & CLEAN-UP:

Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Remove to safe place.

# SECTION 7. HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING:

Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Continue all label precautions!

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Keep separated from strong oxidants, strong acids. Keep dry. Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage.

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 STINGER® DURATION

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **8.1 EXPOSURE LIMITS:**

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Water	7732-18-5	231-791-2	None Known	None Known
Dimethylsiloxane	63148-62-9	-	None Known	None Known
Glycerol	56-81-5	-	None Known	None Known
C9-11 Alcohol Ethoxylate	68081-81-2	-	None Known	None Known
Dipropylene Glycol	25265-71-8	246-770-3	None Known	25 ppm
Triethanolamine	102-71-6	203-049-8	1 ppm	5 mg/m3
Methyl Chloro Isothiazolinone	26172-55-4	-	None Known	None Known

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

#### 8.2 APPROPRIATE ENGINEERING CONTROLS:

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

**VENTILATION** 

LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Acceptable SPECIAL: None OTHER: None Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

# 8.3 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

# WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

#### SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

```
APPEARANCE:
                                                                                Liquid, Blue
ODOR:
                                                                                Amine
ODOR THRESHOLD:
                                                                                Not Available
pH (Neutrality):
MELTING POINT/FREEZING POINT:
                                                                                5.5
                                                                                Not Available
BOILING RANGE (IBP,50%, Dry Point):
                                                                                > 102 C / > 216 F
> 100 C / > 212 F (PM)
FLASH POINT (TEST METHOD):
EVAPORATION RATE (n-Butyl Acetate=1):
FLAMMABILITY CLASSIFICATION:
                                                                                Not Applicable
                                                                                Class III-B
LOWER FLAMMABLE LIMIT IN AIR (% by vol): UPPER FLAMMABLE LIMIT IN AIR (% by vol): VAPOR PRESSURE (mm of Hg)@20 C VAPOR DENSITY (air=1):
                                                                                1.0 (Lowest Component)
                                                                                Not Available
                                                                                17.3
0.724
GRAVITY @ 68/68 F / 20/20 C:
DENSITY:
                                                                                0.989
     SPECIFIC GRAVITY (Water=1):
                                                                                0.990
     POUNDS/GALLON:
                                                                                8.247
WATER SOLUBILITY:
                                                                                Appreciable
PARTITION COEFFICIENT (n-Octane/Water):
AUTO IGNITION TEMPERATURE:
DECOMPOSITION TEMPERATURE:
TOTAL VOC'S (TVOC)*:
NONEXEMPT VOC'S (CVOC)*:
                                                                                Not Available
                                                                                371 C /
                                                                                              700 F
                                                                                Not Available
                                                                                0.0 Vol% /0.0 g/L / 0.000 Lbs/Gal 0.0 Vol% /0.0 g/L / 0.000 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)
VISCOSITY @ 20 C (ASTM D445):
                                                                                0.0 Wt% /0.0 g/L / 0.000 Lbs/Gal
                                                                                0.0
                                                                                Not Available
* Using CARB (California Air Resources Board Rules).
```

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 STINGER® DURATION

#### SECTION 10. STABILITY & REACTIVITY

### 10.1 REACTIVITY & CHEMICAL STABILITY:

Stable under normal conditions, no hazardous reactions when kept from incompatibles.

10.2 POSSIBILITY OF HAZARDOUS REACTIONS & CONDITIONS TO AVOID:

Isolate from oxidizers, heat, & open flame.

#### 10.3 INCOMPATIBLE MATERIALS:

The substance is a weak base, reacts with acids. On combustion forms irritating and toxic gases including nitrogen oxides, The substance decomposes on heating producing fumes of arolein. The substance can readily Reacts with strong oxidants, causing fire & explosion hazard.

# 10.4 HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Carbon Dioxide, Nitrogen Oxide vapors, Silicon Dioxide from burning.

# 10.5 HAZARDOUS POLYMERIZATION:

Will not occur.

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1 ACUTE HAZARDS

#### 11.11 EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis. Absorption thru skin increases exposure. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye burns & skin irritation. Wash thoroughly after handling.

#### 11.12 INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

#### 11.13 SWALLOWING:

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

### 11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

# MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this Document can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

### 11.3 CHRONIC HAZARDS

- 11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:
- This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.
- 11.32 TARGET ORGANS: May cause damage to target organs, based on animal data.
- 11.33 IRRITANCY: Irritating to contaminated tissue.
- 11.34 SENSITIZATION: No component is known as a sensitizer.
- 11.35 MUTAGENICITY: No known reports of mutagenic effects in humans.
- 11.36 EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.
- 11.37 TERATOGENICITY: No known reports of teratogenic effects in humans.
- 11.38 REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 ŠTINGER® DURATION

### SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

#### 11.4 MAMMALIAN TOXICITY INFORMATION

LOWEST KNOWN LETHAL DOSE DATA **MATERIAL EINECS#** CAS# LOWEST KNOWN LD50 (ORAL) Triethanolamine 102-71-6 800.0 mg/kg(Guinea Pigs)

#### SECTION 12. ECOLOGICAL INFORMATION

#### 12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

# 12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

#### 12.3 EFFECT OF MATERIAL ON AQUATIC LIFE:

No aquatic environmental information is available on this product.

### 12.4 MOBILITY IN SOIL

Mobility of this material has not been determined.

#### 12.5 DEGRADABILITY

This product is completely biodegradable.

# 12.6 ACCUMULATION

Bioaccumulation of this product has not been determined.

### SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.
ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.

#### SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: No

DOT/TDG SHIP NAME: Not Regulated

DRUM LABEL: None

IATA / ICAO: IMO / IMDG: Not Regulated IMO / IMDG: Not Regulated
EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

# **SECTION 15. REGULATORY INFORMATION**



#### 15.1 EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health

All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title III, Section 313 in amounts greater or equal to 1%.

COMPANY IDENTITY: Stinger Chemical LLC PRODUCT IDENTITY: 595 STINGER® DURATION

# SECTION 15. REGULATORY INFORMATION (CONTINUED)

#### 15.2 STATE REGULATIONS:

US. California Proposition 65
This product may contain chemical(s) known to the state of California to cause cancer and/or birth defects.

#### 15.3 INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

# 15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

D2B: Irritating to skin / eyes.

This product was classified using the hazard criteria of the Controlled Products Regulations (CPR). This Document contains all information required by the CPR.

#### SECTION 16. OTHER INFORMATION

# 16.1 HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 0, PHYSICAL HAZARD: 0 (Personal Protection Rating to be supplied by user based on use conditions.) This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

#### 16.2 EMPLOYEE TRAINING

See Section 2 (Hazards Identification). Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

#### 16.3 SDS DATE Revised: 02/19/2018

#### NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 02/19/2021.