



Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

1 Identification

- **Product identifier**
- **Trade name:** **STINGER BRAKE WASH**
- **Article number:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Paint additive
- **Restrictions on use:** Contact manufacturer.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Stinger Chemical, LLC
905 Live Oak Street
Houston, Texas 77003
P: 713-227-1340
F: 713-225-1767
- **Emergency telephone number:**
CHEMTREC
1-800-424-9300 (US/Canada)
+01 703-527-3887 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371-H336 May cause damage to organs. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalative.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 1)

• **Additional information:**

Repeated exposure may cause skin dryness or cracking.
May cause drowsiness or dizziness.
There are no other hazards not otherwise classified that have been identified.
0 percent of the mixture consists of ingredient(s) of unknown toxicity.

• **Label elements**

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS07 GHS08

• **Signal word** Danger

• **Hazard-determining components of labeling:**

n-hexane
methanol
propan-2-ol

• **Hazard statements**

H225 Highly flammable liquid and vapor. H302+H312+H332
Harmful if swallowed, in contact with skin or if inhaled. H315
Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H371-H336 May cause damage to organs. May cause drowsiness or dizziness.
H373 May cause damage to the nervous system through prolonged or repeated exposure.
Route of exposure: Inhalative.
H304 May be fatal if swallowed and enters airways.

• **Precautionary statements**

P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P240 Ground/bond container and receiving equipment.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 2)

- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P330 Rinse mouth.
- P331 Do NOT induce vomiting.
- P391 Collect spillage.
- P308+P311 IF exposed or concerned: Call a poison center/doctor.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Hazard description:**

· **WHMIS-symbols:**

As of 11 February 2015, the current WHMIS system is being replaced by the GHS system. This is the classification under the older system.

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects



· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 3

REACTIVITY 0 Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 4)

Safety Data Sheet
 acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 3)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

110-54-3	n-hexane	>75%
	⚠ Flam. Liq. 2, H225	
	⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304	
	⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
67-63-0	propan-2-ol	10-25%
	⚠ Flam. Liq. 2, H225	
	⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
67-56-1	methanol	1-5%
	⚠ Flam. Liq. 2, H225	
	⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
	⚠ STOT SE 1, H370	

- **Additional information:**
 For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 Take affected persons out into the fresh air.
- **After inhalation:**
 Supply fresh air; consult doctor in case of complaints.
 Provide oxygen treatment if affected person has difficulty breathing.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.
- **After eye contact:**
 Remove contact lenses if worn.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
 Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; immediately call for medical help.
 A person vomiting while lying on their back should be turned onto their side.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 4)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 - Coughing
 - Dizziness
 - Nausea
 - Gastric or intestinal disorders when ingested.
 - Irritant to skin and mucous membranes.
 - Irritant to eyes.
 - Disorientation
- **Danger**
 - May be fatal if swallowed and enters airways.
 - Irritating to eyes, respiratory system and skin.
 - Vapours may cause drowsiness and dizziness.
 - May be harmful if swallowed, in contact with skin or if inhaled.
 - Danger of pulmonary edema.
 - Danger of impaired breathing.
 - Causes damage to organs.
 - Causes damage to organs through prolonged or repeated exposure.
 - Suspected of damaging fertility or the unborn child.
- **Indication of any immediate medical attention and special treatment needed**
 - Contains methanol. Consult literature for specific antidotes.
 - If swallowed, gastric irrigation with added, activated carbon.
 - If swallowed or in case of vomiting, danger of entering the lungs.
 - If necessary oxygen respiration treatment.
 - Medical supervision for at least 48 hours.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
 - Formation of toxic gases is possible during heating or in case of fire.
 - Highly flammable liquid and vapor.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information** Eliminate all ignition sources if safe to do so.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 5)

6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

• **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

• **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

• **Handling:**

• **Precautions for safe handling**

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

• **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Highly flammable liquid and vapor.

Flammable gas-air mixtures may be formed in empty receptacles.

Fumes can combine with air to form an explosive mixture.

• **Conditions for safe storage, including any incompatibilities**

• **Storage:**

• **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

• **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

• **Further information about storage conditions:**

Keep receptacle tightly sealed.

Keep away from heat.

(Contd. on page 7)

Safety Data Sheet
 acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 6)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-54-3 n-hexane

PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m ³ , 50 ppm
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE

67-63-0 propan-2-ol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

67-56-1 methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin

(Contd. on page 8)

Safety Data Sheet
 acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 7)

TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm Skin
EV (Canada)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
LMPE (Mexico)	Short-term value: 250 ppm Long-term value: 200 ppm PIEL, IBE

· Ingredients with biological limit values:

110-54-3 n-hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis
-----------	---

67-63-0 propan-2-ol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

67-56-1 methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

· Engineering controls: No further relevant information available.

· Breathing equipment:

- Suitable respiratory protective device recommended.
- Use suitable respiratory protective device when aerosol or mist is formed.
- Use suitable respiratory protective device when high concentrations are present.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 8)

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Colorless

· **Odor:** Alcohol-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 63 - 83 °C (145 - 181 °F)

· **Flash point:** - 26 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** > 260 °C (> 500 °F)

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 9)

- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
 - Lower: 1.2 Vol %
 - Upper: 11.5 Vol %
- **Vapor pressure at 20 °C (68 °F):** 105 hPa (79 mm Hg)
- **Density at 20 °C (68 °F):** 0.70 g/cm³ (5.842 lbs/gal)
- **Relative density:** Not determined.
- **Vapour density at 20 °C (68 °F)** 2.7 (Air = 1.0)
- **Evaporation rate at 20 °C (68 °F)** 4.3 (Butyl Acetate = 1.0)
- **Solubility in / Miscibility with Water:** Partly soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic: Not determined.
 - Kinematic: Not determined.
- **Solvent content:**
 - Organic solvents: 100.0 %
 - VOC content: 100.0 %
 - VOC (California) 100.0 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 10)

- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-56-1 methanol

Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4h	130.7 mg/l (RAT)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Toxic and/or corrosive effects may be delayed up to 24 hours.
Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- **Carcinogenic categories**

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Probable Routes of Exposure**

Inhalation.
Ingestion.
Eye contact.
Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):**

May be fatal if swallowed and enters airways. Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation.
Causes damage to organs.
Vapors have narcotic effect.
Irritating to respiratory system.

- **Repeated Dose Toxicity:**

Repeated exposure may cause skin dryness or cracking.
May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalative.

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

Suspected of damaging fertility or the unborn child.

(Contd. of page 11)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Waste disposal key:** EPA RCRA Code (USA): D001.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1993
- **UN proper shipping name**
- **DOT** Flammable liquids, n.o.s.(hexane, isopropanol)
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES, propan-2-ol), ENVIRONMENTALLY HAZARDOUS
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (HEXANES, propan-2-ol)

(Contd. on page 13)

Safety Data Sheet
 acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 12)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
 · **Label** 3
 · **Packing group**
 · **DOT, ADR, IMDG, IATA** II
 · **Environmental hazards:**
 · **Marine pollutant:** No
 · **Special marking (ADR):** Symbol (fish and tree)
 · **Special precautions for user** Warning: Flammable liquids
 · **Danger code (Kemler):** 33
 · **EMS Number:** E-E,S-E
 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
 · **Transport/Additional information:**
 · **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

(Contd. on page 14)

Safety Data Sheet
 acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 13)

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN1993, Flammable liquids, n.o.s. (Hexanes, propan-2-ol), ENVIRONMENTALLY HAZARDOUS, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

All ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1 | methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

110-54-3 | n-hexane | II

· **IARC (International Agency for Research on Cancer)**

67-63-0 | propan-2-ol | 3

· **TLV (Threshold Limit Value established by ACGIH)**

67-63-0 | propan-2-ol | A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 14)

· **State Right to Know Listings**

None of the ingredients is listed.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

All ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/20/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

(Contd. on page 16)

Safety Data Sheet
acc. to OSHA HCS (29 CFR 1910.1200)

Trade name: BRAKE WASH

(Contd. of page 15)

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com