



# Safety Data Sheet

Issue Date: 12-Mar-2014

Revision Date: 16-Sep-2018

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** 809 Stinger® Poly Paint Sealant

### Other means of identification

**SDS #** SDS-809

**Product Code** 809

### Recommended use of the chemical and restrictions on use

**Recommended Use** Polishing Compound.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Stinger Chemical, LLC  
905 Live Oak  
Houston, TX 77003

### Emergency Telephone Number

**Company Phone Number** 713-227-1340

**Emergency Telephone (24 hr)** Chemtrec 1-800-424-9300 (North America) 1-703-527-3887 (International)

## 2. HAZARDS IDENTIFICATION

**Appearance** Creme white

**Physical State** Lotion

**Odor** Hydrocarbon

### Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1
Flammable Liquids	Category 4

### Signal Word

**Danger**

### Hazard Statements

Harmful if inhaled  
May cause an allergic skin reaction  
May cause genetic defects  
May be fatal if swallowed and enters airways  
Combustible liquid



**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Keep away from flames and hot surfaces. - No smoking.

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 Wash contaminated clothing before reuse  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a poison center or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do not induce vomiting  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Aluminum Oxide	1344-28-1	5-50
Petroleum Distillates, Hydrotreated light	64742-47-8	9-20
Petroleum Distillate	64741-65-7	5-18
Glycerol	56-81-5	2-9
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	55965-84-9	0.01-0.2
Poly Dimethyl Siloxane	63148-62-9	2.1 - 5.3

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

**First Aid Measures**

<b>General Advice</b>	If exposed or concerned: Get medical advice/attention.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
<b>Skin Contact</b>	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>Ingestion</b>	IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting.

**Most important symptoms and effects**

<b>Symptoms</b>	May cause an allergic skin reaction. May be irritating to the eyes. May be harmful or fatal if swallowed and enters airways.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Water. Foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Combustible liquid. Can form explosive mixture at temperature at or above the flash point.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Personal Precautions</b>	Use personal protection recommended in Section 8.
-----------------------------	---

<b>Environmental Precautions</b>	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.
----------------------------------	--

**Methods and material for containment and cleaning up**

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
--------------------------------	---

<b>Methods for Clean-Up</b>	Contain and collect with an inert absorbent and place into an appropriate container for disposal.
-----------------------------	---

**7. HANDLING AND STORAGE****Precautions for safe handling**

<b>Advice on Safe Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Contaminated work clothing should not be allowed out of the workplace. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
--------------------------------	--

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not allow to freeze. Store between 4°C (40°F) and 35°C (95°F). Shelf life: one year.
---------------------------	--

<b>Incompatible Materials</b>	None known based on information supplied.
-------------------------------	---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum Oxide 1344-28-1	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	-
Glycerol 56-81-5	-	TWA: 15 mg/m <sup>3</sup> mist, total particulate TWA: 5 mg/m <sup>3</sup> mist, respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> mist, total particulate (vacated) TWA: 5 mg/m <sup>3</sup> mist, respirable fraction	-

**Appropriate engineering controls**

**Engineering Controls**                      Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**                      Safety goggles or safety glasses with side shields.  
**Skin and Body Protection**                Wear nitrile or vinyl gloves. Wear suitable protective clothing.  
**Respiratory Protection**                    NIOSH-approved respirator or mask in the absence of adequate ventilation.  
**General Hygiene Considerations**        Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Lotion	<b>Odor</b>	Hydrocarbon
<b>Appearance</b>	Lotion	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Light Beige		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	~8.8 - 9.6	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	>65.5 C / 150° F	
Flash Point	>66 °C / 151 °F	Tag Closed Cup
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	
Lower Flammability Limit	Not available	
Vapor Pressure	Not applicable	
Vapor Density	Not applicable	
Specific Gravity	1.10 - 1.2	
Water Solubility	Negligible	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not available	
Decomposition Temperature	Not determined	
Dynamic Viscosity	Not determined	
Hazardous Air Pollutants	.0028 lbs HAPS/ lb solids	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content	<12% by weight	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**            Hazardous polymerization does not occur.

### Conditions to Avoid

Avoid high temperatures. Keep out of reach of children.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

**Eye Contact**                                    Avoid contact with eyes.

**Skin Contact**                                   May cause an allergic skin reaction.

**Inhalation**                                      Harmful if inhaled.

**Ingestion**                                        May be fatal if swallowed and enters airways.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aluminum Oxide 1344-28-1	> 5000 mg/kg ( Rat )	-	-
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Petroleum Distillate 64741-65-7	> 7000 mg/kg ( Rat )	> 3000 mg/kg ( Rat ) > 2000 mg/kg ( Rabbit )	> 5.04 mg/L ( Rat ) 4 h
Glycerol 56-81-5	= 12600 mg/kg ( Rat )	> 10 g/kg ( Rabbit )	> 570 mg/m <sup>3</sup> ( Rat ) 1 h
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone 55965-84-9	= 53 mg/kg ( Rat )	-	-

### Information on physical, chemical and toxicological effects

**Symptoms**                                      Please see section 4 of this SDS for symptoms.

## 809 Stinger® Poly Paint Sealant

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	May cause genetic defects.
<b>Carcinogenicity</b>	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum Distillates, Hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Petroleum Distillate 64741-65-7	30000: 72 h Pseudokirchneriella subcapitata mg/L EC50			2: 48 h Mysidopsis bahia mg/L LC50
Glycerol 56-81-5		51 - 57: 96 h Oncorhynchus mykiss mL/L LC50 static		

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Glycerol 56-81-5	-1.76

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods**

<b>Disposal of Wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated Packaging</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.

**14. TRANSPORT INFORMATION**

**Note** According to 49 CFR §173.150(f)(1), this material should be reclassified as "NA1993, Combustible Liquid, N.O.S." if it is shipped in bulk.

**DOT** Not regulated

**IATA** Not regulated

**IMDG**  
**Marine Pollutant** This material may meet the definition of a marine pollutant

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** All ingredients are listed or exempt from listing on Chemical Substance Inventory

**Legend:**  
*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

**US Federal Regulations**

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Aluminum Oxide - 1344-28-1	1344-28-1	5-50	1.0

**US State Regulations**

**California Proposition 65**

This product may contain chemical(s) known to the state of California to cause cancer and/or birth defects. Additional information can be received upon request. **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Aluminum Oxide 1344-28-1	X	X	X
Glycerol 56-81-5	X	X	X

<b>16. OTHER INFORMATION</b>
------------------------------

<b><u>NFPA</u></b>	<b>Health Hazards</b> 1	<b>Flammability</b> 1	<b>Instability</b> 0	<b>Special Hazards</b> Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b> Not determined	<b>Flammability</b> Not determined	<b>Physical Hazards</b> Not determined	<b>Personal Protection</b> Not determined

Issue Date: 12-Mar-2014  
Revision Date: 16-Sep-2014  
Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**