

1. Identification

Product identifier **BLACK G021 US**

Other means of identification

Product Code 10889 722102 604

Recommended use Not available.

Manufacturer/Importer/Supplier/Distributor information

Company name Barwald Industries

Address 1100 Pleasantville Dr.,
Houston, TX 77029
United States

Telephone General Assistance (713) 227-1340

Website www.barwaldindustries.com

Emergency phone number Chemtrec Phone 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 2
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	82.58% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 82.58% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	40 to <50
N-BUTANE		106-97-8	10 to <20
PROPANE		74-98-6	10 to <20
TOLUENE		108-88-3	10 to <20
AMORPHOUS PRECIPITATED SILICA		112926-00-8	1 to <5
METHYL ETHYL KETONE		78-93-3	1 to <5
PROPYLENE GLYCOL METHYL ETHER ACETATE		108-65-6	1 to <5
XYLENE		1330-20-7	1 to <5
1-METHYL-2-PYRROLIDONE		872-50-4	0.1 to <1
Butyl benzyl phthalate		85-68-7	0.1 to <1
CARBON BLACK		1333-86-4	0.1 to <1
ETHYLBENZENE		100-41-4	0.1 to <1
Other components below reportable levels			5 to <10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
ACETONE (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
CARBON BLACK (CAS 1333-86-4)	PEL	3.5 mg/m3
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3 100 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	PEL	590 mg/m3
PROPANE (CAS 74-98-6)	PEL	200 ppm 1800 mg/m3
XYLENE (CAS 1330-20-7)	PEL	1000 ppm 435 mg/m3 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)	TWA	0.8 mg/m3 20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm	
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
METHYL ETHYL KETONE (CAS 78-93-3)	STEL TWA	300 ppm 200 ppm	
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
XYLENE (CAS 1330-20-7)	STEL TWA	150 ppm 100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ACETONE (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)	TWA	6 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m3
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm 435 mg/m3
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	100 ppm 885 mg/m3
	TWA	300 ppm 590 mg/m3
N-BUTANE (CAS 106-97-8)	TWA	200 ppm 1900 mg/m3
PROPANE (CAS 74-98-6)	TWA	800 ppm 1800 mg/m3
TOLUENE (CAS 108-88-3)	STEL	1000 ppm 560 mg/m3
	TWA	150 ppm 375 mg/m3 100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	TWA	40 mg/m3
PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6)	TWA	10 ppm 50 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	100 mg/l	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	*
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
METHYL ETHYL KETONE (CAS 78-93-3)	2 mg/l	MEK	Urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
XYLENE (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines
US - California OELs: Skin designation

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	Can be absorbed through the skin.
PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6)	Can be absorbed through the skin.
TOLUENE (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (CAS 108-88-3)	Skin designation applies.
------------------------	---------------------------

US WEEL Guides: Skin designation

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol. Liquefied gas.

Color

Not available.

Odor

Not available.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-305.68 °F (-187.6 °C) estimated

Initial boiling point and boiling range

-43.78 °F (-42.1 °C) estimated

Flash point

-156.0 °F (-104.4 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1.3 % estimated

Flammability limit - upper (%)

12.8 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

2291.96 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

550 °F (287.78 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density

6.05 lbs/gal

Explosive properties	Not explosive.
Flammability class	Flammable IA estimated
Heat of combustion (NFPA 30B)	30.38 kJ/g estimated
Oxidizing properties	Not oxidizing.
Percent volatile	91.7
Specific gravity	0.73
VOC	4.88 lbs/gal Regulatory 585.04 g/l Regulatory 2.96 lbs/gal Material 355.24 g/l Material

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
---	--

Information on toxicological effects

Acute toxicity	Narcotic effects.
-----------------------	-------------------

Components	Species	Test Results
1-METHYL-2-PYRROLIDONE (CAS 872-50-4)		
Acute		
Dermal		
LD50	Rabbit	8000 mg/kg
Oral		
LD50	Mouse	5130 mg/kg
	Rat	3914 mg/kg
		4.2 ml/kg
ACETONE (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	> 15800 mg/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rat	5800 mg/kg

Components	Species	Test Results
AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Butyl benzyl phthalate (CAS 85-68-7)		
<u>Acute</u>		
Dermal		
LD50	Mouse	6700 mg/kg
	Rat	6700 mg/kg
Oral		
LD50	Rat	13500 mg/kg
CARBON BLACK (CAS 1333-86-4)		
<u>Acute</u>		
Oral		
LD50	Rat	> 8000 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
METHYL ETHYL KETONE (CAS 78-93-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 8000 mg/kg
Inhalation		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
Oral		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
N-BUTANE (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
PROPANE (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
TOLUENE (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg
		14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours
		400 ppm, 24 Hours

Components	Species	Test Results
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
XYLENE (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)	3 Not classifiable as to carcinogenicity to humans.
Butyl benzyl phthalate (CAS 85-68-7)	3 Not classifiable as to carcinogenicity to humans.
CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
TOLUENE (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
XYLENE (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. May damage fertility or the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species		Test Results
ACETONE (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Butyl benzyl phthalate (CAS 85-68-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 0.96 mg/l, 48 hours
Fish	LC50	Shiner perch (Cymatogaster aggregata)	0.47 - 0.56 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
METHYL ETHYL KETONE (CAS 78-93-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
TOLUENE (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
XYLENE (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1-METHYL-2-PYRROLIDONE	-0.54
ACETONE	-0.24
Butyl benzyl phthalate	4.91
ETHYLBENZENE	3.15
METHYL ETHYL KETONE	0.29
N-BUTANE	2.89
PROPANE	2.36
TOLUENE	2.73
XYLENE	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	UN1950, Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



**General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

Butyl benzyl phthalate (CAS 85-68-7)

Phthalates Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

ACETONE (CAS 67-64-1)

Listed.

Butyl benzyl phthalate (CAS 85-68-7)

Listed.

ETHYLBENZENE (CAS 100-41-4)

Listed.

METHYL ETHYL KETONE (CAS 78-93-3)

Listed.

N-BUTANE (CAS 106-97-8)

Listed.

PROPANE (CAS 74-98-6)

Listed.

TOLUENE (CAS 108-88-3)

Listed.

XYLENE (CAS 1330-20-7)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
TOLUENE	108-88-3	10 to <20
XYLENE	1330-20-7	1 to <5
1-METHYL-2-PYRROLIDONE	872-50-4	0.1 to <1
ETHYLBENZENE	100-41-4	0.1 to <1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ETHYLBENZENE (CAS 100-41-4)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8)

PROPANE (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6532

METHYL ETHYL KETONE (CAS 78-93-3) 6714

TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %WV

METHYL ETHYL KETONE (CAS 78-93-3) 35 %WV

TOLUENE (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

ACETONE (CAS 67-64-1) 6532

METHYL ETHYL KETONE (CAS 78-93-3) 6714

TOLUENE (CAS 108-88-3) 594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ACETONE (CAS 67-64-1) Low priority

METHYL ETHYL KETONE (CAS 78-93-3) Low priority

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

ACETONE (CAS 67-64-1)

Butyl benzyl phthalate (CAS 85-68-7)

CARBON BLACK (CAS 1333-86-4)

ETHYLBENZENE (CAS 100-41-4)

METHYL ETHYL KETONE (CAS 78-93-3)

N-BUTANE (CAS 106-97-8)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

ACETONE (CAS 67-64-1)

AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)

Butyl benzyl phthalate (CAS 85-68-7)

CARBON BLACK (CAS 1333-86-4)

ETHYLBENZENE (CAS 100-41-4)

METHYL ETHYL KETONE (CAS 78-93-3)

N-BUTANE (CAS 106-97-8)

PROPANE (CAS 74-98-6)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

ACETONE (CAS 67-64-1)

AMORPHOUS PRECIPITATED SILICA (CAS 112926-00-8)

Butyl benzyl phthalate (CAS 85-68-7)

CARBON BLACK (CAS 1333-86-4)

ETHYLBENZENE (CAS 100-41-4)

METHYL ETHYL KETONE (CAS 78-93-3)

N-BUTANE (CAS 106-97-8)

PROPANE (CAS 74-98-6)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)

ACETONE (CAS 67-64-1)

Butyl benzyl phthalate (CAS 85-68-7)
 CARBON BLACK (CAS 1333-86-4)
 ETHYLBENZENE (CAS 100-41-4)
 METHYL ETHYL KETONE (CAS 78-93-3)
 N-BUTANE (CAS 106-97-8)
 PROPANE (CAS 74-98-6)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. Rhode Island RTK

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)
 ACETONE (CAS 67-64-1)
 Butyl benzyl phthalate (CAS 85-68-7)
 ETHYLBENZENE (CAS 100-41-4)
 METHYL ETHYL KETONE (CAS 78-93-3)
 N-BUTANE (CAS 106-97-8)
 PROPANE (CAS 74-98-6)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4)	Listed: February 21, 2003
ETHYL ALCOHOL (CAS 64-17-5)	Listed: April 29, 2011
	Listed: July 1, 1988
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

1-METHYL-2-PYRROLIDONE (CAS 872-50-4)	Listed: June 15, 2001
Butyl benzyl phthalate (CAS 85-68-7)	Listed: December 2, 2005
DIBUTYL PHTHALATE (CAS 84-74-2)	Listed: December 2, 2005
ETHYL ALCOHOL (CAS 64-17-5)	Listed: October 1, 1987
TOLUENE (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

DIBUTYL PHTHALATE (CAS 84-74-2)	Listed: December 2, 2005
TOLUENE (CAS 108-88-3)	Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

DIBUTYL PHTHALATE (CAS 84-74-2)	Listed: December 2, 2005
---------------------------------	--------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-01-2019

Revision date 06-17-2021
Version # 03
HMIS® ratings Health: 2*
Flammability: 3
Physical hazard: 0
NFPA ratings Health: 2
Flammability: 3
Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.