



INSTALLATION INSTRUCTIONS

Allora USA top mount stainless steel sinks

Applicable Models: All TOP models including their ADA counterparts

ATTENTION, REVIEW BEFORE INSTALLATION:

- **ALLORA USA RECOMMENDS THAT UNDERMOUNT SINKS SHOULD BE INSTALLED BY A PROFESSIONAL EXPERIENCED INSTALLER.**
- **ALLORA USA IS NOT RESPONSIBLE FOR SINK OR COUNTERTOP IF DAMAGED DURING INSTALLATION.**
- **ALLORA USA IS NOT RESPONSIBLE FOR ANY DAMAGES DUE TO IMPROPER INSTALLATION.**
- **INSPECT SINK FOR DAMAGE PRIOR TO BEGINNING INSTALLATION.**
- **METAL EDGES MAY BE SHARP - USE CAUTION WHEN HANDLING.**
- **FOLLOW ALL LOCAL PLUMBING AND BUILDING CODES.**

Allora USA top mount sinks are designed to be mounted over the countertop. It is recommended that you discuss this with your customer and agree that this finished appearance is the desired effect. Allora USA is not responsible for improper sink or countertop installations.





INSTALLATION INSTRUCTIONS

Allora USA undermount sinks

Applicable Models: All TOP models including their ADA counterparts

1. Determine the locations for the clip brackets around the perimeter of the sink.
2. Pre-drill holes for the clips using appropriate methods for the countertop material.
3. Clean the surfaces of the sink and countertop which will meet, with denatured alcohol.
4. Evenly apply a bead of silicone along perimeter edge of the opening on the top of the countertop.
5. Carefully align the sink over the countertop opening. Evenly apply pressure to the sink securing a seal of the silicone against the countertop.
6. Re-check that the sink is evenly aligned with the countertop.
7. Attach and tighten the clip brackets against the edge of the sink. Do not tighten one screw completely before others.
8. Partially tighten one clip then the one across from it, and so on until all clips are fully tightened. This will safeguard against an uneven or insecure installation.
9. Use a cloth with denatured alcohol along the perimeter of the sink and countertop to remove any excess sealant.