



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

1 Identification

- · Product Identifier
- · Trade name: Craft Meister Oxygen Brewery Wash
- Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description Brewery Wash
- · Application of the substance / the mixture: Industry Specific Application
- Details of the Supplier of the Safety Data Sheet:
 Manufacturer/Supplier: National Chemicals, Inc.
 PO Box 506, Lewiston, MN 55952
 Ph: 800-533- 0027 / 507-454- 5640
- info@NationalChemicals.com
- · Emergency telephone number: CHEMTREC 1-800- 424-9300

2 Hazard(s) Identification

• Classification of the substance or mixture:

GHS03 Flame over circle

Ox. Sol. 3 H272 May intensify fire; oxidizer.

GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements:
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Sodium percarbonate Disodium Metasilicate

· Hazard statements:

H272 May intensify fire; oxidizer.

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

· Precautionary statements:

Trecautionary statements.			
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.		
P264	Wash thoroughly after handling.		
P280	Wear protective gloves / eye protection / face protection.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if		
	present and easy to do. Continue rinsing.		
P310	Immediately call a POISON CENTER/doctor.		
P312	Call a POISON CENTER/doctor if you feel unwell.		
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.		
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.		

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 0 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH2Health = 2FIRE1Fire = 1REACTIVITY1Reactivity = 1

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

 Dangerous 	Components:	
15630-89-4	Sodium percarbonate	40-60%
	🚸 Ox. Sol. 2, H272; 🚸 Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302; STOT SE 3, H335	
497-19-8	Sodium carbonate	25-50%
	🚸 Eye Irrit. 2A, H319	
6834-92-0	Disodium Metasilicate	≤ 2.5%
	Skin Corr. 1B, H314; () Acute Tox. 4, H302; STOT SE 3, H335	
Additional	information:	

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

(Contd. on page 3)

Reviewed on 05/10/2017



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

4 First-Aid Measures

- · Description of first aid measures:
- General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

• After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor. If easy to do so, remove contact lenses if worn.

• After swallowing:

Do not induce vomiting without medical advice.

If swallowed and symptoms occur, consult a doctor.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media:
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture:
- Oxidizing substance. Non combustible, but will support combustion of other materials.

Advice for firefighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. Keep containers cool with water spray. Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire.

Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- Environmental precautions: Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

· Protective Action Criteria for Chemicals

• PAC-1:		
497-19-8	Sodium carbonate	7.6 mg/m3
6834-92-0	Disodium Metasilicate	3.8 mg/m3
· PAC-2:		
497-19-8	Sodium carbonate	83 mg/m3
6834-92-0	Disodium Metasilicate	42 mg/m3
· PAC-3:		
497-19-8	Sodium carbonate	500 mg/m3
6834-92-0	Disodium Metasilicate	250 mg/m3

7 Handling and Storage

- · Handling
- · Precautions for safe handling: Prevent formation of dust.
- · Information about protection against explosions and fires:
- Protect from heat. Store below 40 °C
- Conditions for safe storage, including any incompatibilities:
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
 Protect from heat and direct sunlight.
 Store below 40 °C
- Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters:

Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

- Exposure controls:
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:



Suitable respiratory protective device recommended.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

• Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:



Tightly sealed goggles

• Body protection:



Protective work clothing

9 Physical and Chemical Properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:	Powder
Color:	White
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. Not determined.
· Flash point:	None
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	Not applicable
 Decomposition temperature: 	Not determined.
· Auto igniting:	Product is not self-igniting.

Dowdor

• *Danger of explosion:* Product does not present an explosion hazard.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

Page 6/11

Reviewed on 05/10/2017

• Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density:	
Relative density:	Not determined.
Vapor density:	Not applicable.
Evaporation rate:	Not applicable.
 Solubility in / Miscibility with: 	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water): Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
• Other information:	No further relevant information available.
40 Oto hilliter and Decentioniter	

10 Stability and Reactivity

· Reactivity: No further relevant information available.

· Chemical stability: Stable under normal conditions.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

· Conditions to avoid: No further relevant information available.

 Incompatible materials: Incompatible with acids, bases, combustible material, organic materials, reducing agents, moisture, flammable materials, permanganates.

· Hazardous decomposition products: Keep away from oxygen.

1 Toxicological Information

Information on toxicological effects: Acute toxicity:

-	4 Sodium perc		
Oral	LD50	2200 mg/kg (Mouse)	
		2400 mg/kg (Rat)	
497-19-8 Sodium carbonate			
Oral	LD50	4090 mg/kg (Rat)	
Inhalative	LC50/96 hours	300 mg/l (Fathead Minnow)	
6834-92-0	Disodium Meta	asilicate	
Oral	LD50	1280 mg/kg (Rat)	

• On the eye:

Irritating effect.



Reviewed on 05/10/2017



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories:

• *IARC (International Agency for Research on Cancer):* None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

· Toxicity:

· Aquatic toxicity:

497-19-8 Sodium carbonate

EC50 227 mg/l (Daphnia)

6834-92-0 Disodium Metasilicate

EC50 247 mg/l (Water flea)

• Persistence and degradability: No further relevant information available.

- · Behavior in environmental systems:
- *Bioaccumulative potential:* No further relevant information available.
- *Mobility in soil:* No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

· Waste treatment methods:

· Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

14 Transport Information

UN-Number:
 DOT, ADR/ADN, IMDG, IATA
 UN proper shipping name:
 DOT
 ADR/ADN
 UN1479
 Oxidizing solid, n.o.s. (Sodium percarbonate)
 UN1479 Oxidizing solid, n.o.s. (Sodium percarbonate)
 IMDG, IATA
 OXIDIZING SOLID, N.O.S. (Sodium percarbonate)

(Contd. on page 8)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash		
 Transport hazard class(es): 		
DOT		
CONSIDER GRANT		
· Class: · Label:	5.1 Oxidizing substances 5.1	
· ADR/ADN		
51		
· Class: · Label:	5.1 (O2) Oxidizing substances 5.1	
· IMDG, IATA		
51		
 Class: Label: Packing group: DOT, ADR/ADN, IMDG, IATA Environmental hazards: 	5.1 Oxidizing substances5.1IIINot applicable.	
 Special precautions for user: 	Warning: Oxidizing substances	
· Danger code (Kemler): · EMS Number:	50 F-A,S-Q	
Stowage Category	Р <i>-7</i> ,3-Q В	
· Segregation Code	SG38 Stow "separated from" ammonium compo SG49 Stow "separated from" cyanides SG60 Stow "separated from" peroxides SG61 Stow "separated from" powdered metals	unds.
 Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code: 		
• Transport/Additional information:		
· DOT · Quantity limitations:	On passenger aircraft/rail: 25 kg On cargo aircraft only: 100 kg	
· ADR/ADN · Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 g	
	Maximum net quantity per outer packaging: 100	
 IMDG Limited quantities (LQ): 	5 kg	(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

 Excepted quantities (EQ): 	Code: E1
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
• UN "Model Regulation":	UN 1479 OXIDIZING SOLID, N.O.S. (SODIUM
	PERCARBONATE), 5.1, III

5 Regulatory Information

• Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):

· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
• TSCA (Toxic Substances Control Act):	
All ingredients are listed or exempt from listing.	
· California Proposition 65:	
· Chemicals known to cause cancer:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· New Jersey Right-to-Know List:	
None of the ingredients are listed.	
· New Jersey Special Hazardous Substance List:	
None of the ingredients are listed.	
· Pennsylvania Right-to-Know List:	
10124-56-8 Sodium Hexametaphosphate	
Pennsylvania Special Hazardous Substance List:	
10124-56-8 Sodium Hexametaphosphate	E
Carcinogenic categories:	
· EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
• TLV (Threshold Limit Value established by ACGIH):	

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Reviewed on 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

· Hazard pictograms:



· Signal word: Danger

· Hazard-determi	ning components of labeling:			
Sodium percarbonate				
Disodium Metasilicate				
	· Hazard statements:			
H272 May intens	H272 May intensify fire; oxidizer.			
H315 Causes skin irritation.				
H318 Causes serious eye damage.				
	respiratory irritation.			
· Precautionary s	tatements:			
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.			
P264	Wash thoroughly after handling.			
P280	Wear protective gloves / eye protection / face protection.			
P302+P352	IF ON SKIN: Wash with plenty of water.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P305+P351+P33	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if			
	present and easy to do. Continue rinsing.			
P310	Immediately call a POISON CENTER/doctor.			
P312	Call a POISON CENTER/doctor if you feel unwell.			
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).			
P332+P313	If skin irritation occurs: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.			
P403+P233	Store in a well-ventilated place. Keep container tightly closed.			
P501	Dispose of contents/container in accordance with local/regional/national/international			
	regulations.			
National regulation	tions:			

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 05/10/2017 / 7

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances



Reviewed on 05/10/2017



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/10/2017

Trade name: Craft Meister Oxygen Brewery Wash

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Ox. Sol. 2: Oxidizing solids – Category 2 Ox. Sol. 3: Oxidizing solids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 * * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106