

2.6 gallon dual-power foam unit



F100



the good stuff

- **compressed air attachment**
connect to an air source to quickly pressurize the unit, then disconnect and move the unit to the area to be cleaned
- **maximizing portability**
manual pump for when air isn't available. Dual operation with manual pump and connection for air supply allows for flexibility in applications
- **natural tank**
see chemical volume levels at a glance

features

- integrated attachment for compressed air
- manual pump for when air isn't available
- 2.6 gallon (10 liter) capacity
- Viton seals for chemical compatibility
- pressure regulator to not exceed set psi
- built in pressure relief valve
- 6 foot discharge
- natural color tank for easy visibility of products levels

industries

- agriculture
- institutional
- industrial
- food and beverage

specs

- power typecompressed air or manual
- chemical pickup type.....draws from pre-mixed solution
- number of products unit can draw fromone product
- capacity.....2.6 gallons (10 liters)
- discharge line length/diameter 6.5 ft. (2 m) hose, with 1/4 in. (6.4 mm) inside diameter
- discharge wand/tip type polypropylene trigger handle with 65 degree fan tip
- output distance.....5-6 ft. (1.5-1.8 m)
- output volume3 gal/min (11.4 l/min)
- flow rate 0.5 gal/min (1.9 l/min)
- pump sealsViton

requirements

- compressed air requirements..... 40 psi (2.8 bar) with 2-5 cfm (56.6-141.6 l/min)
- liquid temperature range..... 40-100 ° F (4.4-37.8 ° C)
- chemical compatibility..... chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department.



how to buy



800 567 5420 | sales@foamit.com