

US Weight 4594 E. Radio Tower Lane Olney, IL 62450 PH # 1-877-201-9748 usw.sales@escaladesports.com

Additional product information and installation videos can be found at www.usweight.com

Thank you for your business. We value our customers.

DO NOT RETURN

Contact manufacturer for any product issues. usw.sales@escaladesports.com - toll free at 1-877-201-9748.

NOTE - FOR BASES REQUIRING FILLING

Molded Stanchion (ChainBoss)

*Plug for base located inside bottom of post.



To dislodge the plug from the post it may be necessary to turn post upside down and tap the end of post against the floor.


* Recommended material for filling bases is pea gravel. Water and sand will likely leak!

Parts List:

Note: Located inside post.
Only for unfilled base models.

Cap Plug (2)







Cap (2)



*Chain & Hook not included with model #'s ending with NC (No Chain)



No Tools Required

Assembly Instructions per Stanchion

- Insert bottom of post into opening of base by pushing post down to snap in place. See Figure A.
- Taking cap and (1) piece of chain, place ends of chain through cap window and insert hook to each end of chain. See Figure B.
- 3. Place chain inside post and align slot in cap to rivet in post. See Figure C.
- For instructions on using cap, See Figure D. Note: Chain not shown for better clarity on how cap functions.
- With cap in open and locked position, pull chain out to desired length. Once desired length is set, return cap to closed position. See Figure E.
- 6. To store chain inside post, open and lock cap in place. Return chain to post through cap window. Close cap.

