

# DR40RB-WH/BK/SN

4 inch 5CCT LED Baffle Recessed downlight(Air tight)

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/ Name		
Notes		

## Body

- Durable airtight aluminum
- Adjustable Baffle

## LED Characteristics

- 12-Watt LED Module
- Minimal heat emission
- Up to 830Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

## Dimming

- 10%-100% dimming capability
- Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

## Environment

- Suitable for wet locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

## Mounting

- Included two springs loaded clips to attach to any ceiling material

## Description

• DR40RB, a 12watt 4-inch All CCT round baffle LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Adjustable baffle is beneficial to the adjustment of angle. Suitable for wet location and use in soffits.

## Beam Spread

- 38 degree beam spread

## LED Driver

- Extruded aluminum junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input;
- includes an 12" cable from driver to fixture

## Quick Connect Push-in Terminals

- Three "Quick Connect" Push-in terminals for fast and easy wiring

## Operating Temperature

- -20°C - 40°C (-4°F - 104°F)



## SPECIFICATION

Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Wet	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	38	LM 79	YES
CCT	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	Up to 830
Class II	YES	Lumens per Watt	69.17
Color	White/Black/Brushed Nickel	Power Factor	>0.95
CRI	95+	Projected Life	5 Years
Dimming	YES	Wattage	12 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	4"

