

****Stock Clearance**

Melody 5

CARPET TILES

VIEW ON WEBSITE



SCAN HERE



5971 HASHTAG BROWN

Ashlar



5976 FORUM BLUE

Brick

Please note: There may be slight color difference between the picture and actual carpet. Slight color variation may occur from dye lot to dye lot.




5975 MUFFIN BEIGE




Brick



5971 HASHTAG BROWN



5973 PRIVIO GREY



5976 FORUM BLUE

MELODY 5 Specifications

Construction	1/10" Level Loop Pile
Yarn Composition	100% Solution Dyed Polypropylene
Tufted Pile Weight	Ca. 542 g/m ² (16 oz/yd ²) (+/- 10%)
Total Weight	Ca. 3600 g/m ² (105 oz/yd ²) (+/- 10%)
Pile Height	Ca. 3 mm (+/- 0.5 mm)
Total Height	Ca. 5.5 mm (+/- 0.5 mm)
Density (APYD)	4,872 ozs/yd ³
Tuft Density	100,076 stitches/m ²
Stitch Rate	39.4 per 10 cm
Backing	eBac+
Tile Size	50 cm x 50 cm
Packing	20 pcs per box (5 m ²)

Performance

(as tested by ITTS Inc. USA)

Stain Resistance	10 (AATCC-175-2003)
Static Control	Pass - Max. 4 kV (AATCC-134-1996)
Tuft Bind	Pass - 8.8 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 0.1% change (AACHEN)
Indoor Air Quality (V.O.C.)	Pass - No VOC Detected (ASTM-D5116-10)
Impact Noise Rating	ΔL: 26 dB (ISO 10140)
Sound Absorption	qw 0.20 (ISO 354) Hz 125 250 500 1000 2000 4000 αs 0.01 0.03 0.08 0.28 0.35 0.43
Flammability	
- Radiant Panel	Pass - Class I (ASTM-E-648-06)
- Pill Test	Pass - 8 (ASTM-D-2859-06)
- Smoke Density	Pass - Max. 450 (ASTM-E-662-06)
Colourfastness	
- to light	Excellent - 5 (AATCC-16E)
- to wet & dry crocking	Excellent - 5 (AATCC-165)
- to ozone	Excellent - 5 (AATCC-129)

Warranties

10 Year Carpet Wear Warranty
Lifetime Anti-shock Carpet Warranty

Ideal for Medium Contract Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual color may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Environment

The design and production of Melody 5 Tile conforms to the ISO 14001:2004 Environmental Management System and complies with environmental regulations.

As a responsible manufacturer and to minimize our carbon footprint, a majority of our excess production materials are recycled in-house resulting in a minimum of 10% recycled content in our tile backing. Melody 5 Tile does not contain any PVC in its manufactured materials and packaging.

Melody 5 Tile is an environmentally friendly "green" carpet.

Installation Method



Brick



Ashlar