

ULTRA TURF GRASS CARPET





8388 OLIVE GREEN



ULTRATURF GRASS CARPET Specifications

Construction	5/32" Tufted Cut Pile
Yarn Composition	100% Synthetic (Blend of Polypropylene and Polyethylene) with U/V Stabilizer
Yarn Density	7500
Pile Weight	Ca. 1000 g/m ² (29.5 oz/yd ²)
Total Weight	Ca. 2000 g/m ² (59 oz/yd ²)
Pile Height	Ca. 10 mm (+/- 10%)
Total Height	Ca. 12 mm (+/- 10%)
Stitch Rate	30 per 10 cm
Cohesion Base	Synthetic Draining Latex
Secondary Backing	Marine Back
Standard Roll Size	2 m x 25 m

Performance (as tested by ITTS Inc. USA)

Tuft Bind	Pass - 6 lbs (ASTM-D-1335)
Flammability - Pill Test	Pass - 8 (ASTM-D-2859-16) (FF 1-70)
Colorfastness to light	Good - 3 (AATCC-16E)
100% Solution Dyed	Extremely Hardwearing, Waterproof and Abrasion Resistant Fibre.
Synthetic Draining Latex	Mildew Proof, Rot Proof, Excellent Dimensional Stability, Most Suitable for Outdoor Use and for all Types of Weather.
U/V Stabilized	Chemically Treated to provide maximum protection against fading from ultra violet sunlight.
Solution Dyed	For Excellent Colourfastness

Warranties

- 5 Year Carpet Residential Wear Warranty
- 3 Year Colourfastness Warranty
- Lifetime Antishock Carpet Warranty

Ideal for Swimming Pool Borders, Landscape Decoration, Exhibitions, Displays, Outdoor uses, Nautical uses.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.



ULTRATURF