


KOOL-IT

Signature

LX-24RS

SINGLE GLASS DOOR MERCHANDISER REFRIGERATOR

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.



Signature 40/80 Warranty
 40 months parts and labor
 80 months on compressor (part only)

KEY FEATURES



• Eco-Friendly Refrigerant
 Environmentally friendly R290 hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA, California & Canada refrigerant & energy standards.



• Intelligent Electronic Control
 Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



• High Power Reliable Refrigeration System
 Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining cooler temperatures for food preservation.



• Standard LED Lighting System
 Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.



• Newly Designed Condenser
 New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



• Spark-Free Refrigeration Components
 All Reach-In models have spark free refrigeration components for optimal safety, per UL requirements.



3560 NW 56th Street
 Fort Lauderdale, FL, United States
 Telephone: 786.600.4687 / Toll Free: 844.218.8477
 Fax: 786.661.4100


5659 Royalmount Ave.
 Montreal, QC, Canada H4P 2P9
 Telephone: 514.737.9701 / Toll Free: 888.275.4538
 Fax: 514.342.3854 / Toll Free: 877.453.8832
sales@mvpgroupcorp.com / mvpgroupcorp.com



LX-24RS

SINGLE GLASS DOOR MERCHANDISER REFRIGERATOR

PRODUCT VIEWS



ADDITIONAL FEATURES



Manual Lock - External lock available



Gravity kit - Visi-Slide product display technology



Price Kit - Available for shelf display



Casters or legs are available options

TECHNICAL SPECIFICATIONS

Exterior Dimensions		Interior Dimensions	
W:	29 1/2" (75 cm)	W:	25 1/2" (65 cm)
D:	27 7/8" (71 cm)	D:	27 5/8" (55 cm)
H:	78 7/8" (201 cm)	H:	60 3/8" (154 cm)
Usable Interior Capacity		Usable Volume	
W:	24 3/8" (62 cm)	19.2 Cu Ft 543.7 L	
D:	19 1/8" (48 cm)		
H:	52 7/8" (134 cm)		
Doors	Material	Shelves	Shelf Size
1	Plastic Frame	5	W: 24 3/4" (63 cm) D: 19 5/8" (50 cm)
Exterior Material		430 Stainless Steel	
Interior Material		201 Stainless Steel	

REFRIGERATION PERFORMANCE

Refrigerant	Energy Consumption
R290a / 2.3 oz (0.065 kg)	1.820 kWh/24h
Compressor Power	Condenser
1/5 HP	Finless (low maintenance)
Thermostat default setting	32°F (0°C) to 44.6°F (7°C)

ELECTRICAL

Power Supply	Amps	Lighting
115V/60Hz	7.0A	257.6 Lux Output 9 modules, 8 LED per
Plug Type	Controller	Cord Length
NEMA 5-15P	ETC1H	118" (300 cm)

LOGISTICS

Trailer Loads	Unit Weight	Shipping Dimensions	
53': 80	223.7 lb (101.5 kg)	W:	32 1/8" (82 cm)
	Shipping Weight	D:	32 5/8" (83 cm)
	240.5 lb (109.1 kg)	H:	82 1/4" (209 cm)