

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

## Standard Features

- Kettle System-Seamless deep-drawn 316 kettle liner with an integrally formed radius lip
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 260°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, field replaceable heating elements, tilting cut-off switch
- Full body insulation between kettle jacket and outer casing
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded to control console
- 304 stainless, reinforced gear box
- Self locking worm gear tilt mechanism
- 304 stainless, 2" tubular support frame
- Etched gallon markings
- Faucet bracket
- Adjustable flanged feet

## Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle\*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet\*
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALACWS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package\*

\* Call AccuTemp for additional information

## Electrical Options

208V, 240V, 380V, 415V, 440V, 480V

## Short Spec

AccuTemp Edge Series tilting floor-mounted kettle, model ALTWE-40, seamless deep-drawn 316 kettle liner with integrally formed radius lip and 304 stainless kettle jacket. Full body insulation between the kettle jacket and outer casing. 2/3 jacketed with pressure relief valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light and field replaceable heating elements. Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 140°C). Etched gallon markings and faucet bracket. Adjustable flanged feet.

## Other Approvals



## Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Pour lip pan holder assembly (ALPHKTL)
- Measuring strip (ALMS)
- Lift-off or two piece hinged\*
- 1 piece actuator-assisted lid, 20-60 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)
- 2" or 3" draw off valve, compression or ball type fitting\*

\* Call AccuTemp for additional information



**MODEL ALTWE ELECTRICAL SPECIFICATIONS (AMPERES PER LEG)**

GAL	KW	208 Volt		240 Volt		380 Volt		415 Volt		440 Volt		480 Volt	
		1 $\emptyset$	3 $\emptyset$	1 $\emptyset$	3 $\emptyset$	1 $\emptyset$	3 $\emptyset$	1 $\emptyset$	3 $\emptyset$	1 $\emptyset$	3 $\emptyset$	1 $\emptyset$	3 $\emptyset$
40	24	115.4	66.6	100.0	57.7	63.2	36.5	57.8	33.4	54.5	31.5	50.0	28.9

Revision 113

**MODEL ALTWE DIMENSIONS**

GAL	A	B	C	D	F	G	H*	K	L	S*	W	Y
40	25.5	22.3	47.5	7.0	46.6	43.5	21.7	31.0	38.5	37.3	19.9	41.4

\*Dimensions H & S apply only if an optional 2" draw-off is ordered. If a 3" draw-off is required, contact AccuTemp for applicable dimensions.

DRAWING REPRESENTS 60 GALLON MODEL WITH OPTIONAL 1 1/2" DRAW-OFF

