



S-SERIES



Feature-rich and uncompromising with advanced technology in a compact footprint.

The S-Series continues the legacy of what defines a Synesso. Its a low-profile, auto volumetric machine designed for cafes and multi-concept restaurants that need Synesso's build quality, premium components, and long service intervals.

Our auto volumetric controls allow the barista to set their espresso parameters, and then rely on the machine to deliver consistent results in the cup. This allows the baristas of all skill levels room to engage with their guests and provide a more enjoyable coffee experience. Furthermore, the low-profile design of the S-Series fosters an approachable atmosphere wherever it's installed.

With a rainbow of RAL custom color options available, an accessible price point, super easy to use interface, and stability delivered by our industry leading design and build quality, the S-Series is a great investment for any business looking to grow or start their own coffee program.

CUSTOM RAL POWDER COAT OPTIONS AVAILABLE



KEY BENEFITS

Connect with your customers over a low-profile design that can be sunk further into bar tops.

Prepare premium-quality espresso without a premium price via independent brew-boilers and other high-end internal components found in our leading products.

Easily extract delicious espresso with volumetric recipes and one-tap controls that make use fast and fun.

PERFECT FOR

Small to medium specialty coffee shops with traditional menus.

Multi-concept retailers: bakeries, restaurants, or hotels.

Roasters expanding into brick-and mortar coffee retail.

	Voltage, Single Phase	Amps, Max Draw	Cord Plug Rating, Amps (UL)	Watts per Element	Total Wattage	Tank Capacity, Liters	Watts per Element	Total Wattage	Tank Capacity, Liters
2 Group	220	28	30	2000 x 2	4000	7.7	700x2	1400	1.9x2
3 Group	220	36	50	2500 x 2	5000	12.3	700x3	2100	1.9x3

Electrical

Steam

Brew

	Height	Width	Depth	Machine Weight	Shipping Weight	Shipping Dimension (LxWxH)
2 Group	16.9in/428mm	27.6in/702mm	24in/610mm	152lb/69kg	247lb/112kg	33in x 36in x 30in, 838mm x 914mm x 762mm
3 Group	16.9in/534mm	37in/940mm	24in/610mm	225lb/102kg	320lb/145kg	33in x 46in x 30in, 838mm x 1168mm x 762mm

Machine Dimensions

Direct Connection (Compression)

2 Group	3/8" OD
3 Group	3/8" OD

Plumbing



Certified by Intertek (ETL) for Sanitation to NSF / ANSI 4

Certified by Intertek (ETL) for Electrical Safety to ANSI / UL 197

Certified by Intertek (ETL) for Electrical Safety to CSA C22.2 No. 109



Certified by KTR for Korean KC Mark

Certified to IECEE CB Scheme

CE Compliant (By request)



C-Tick Compliant (By request)

Sabre Compliant (By request)