TOTO®

CWT994CEMFG

NEOREST® EW™ Wall-Hung Toilet, 1.28GPF & 0.9GPF

FEATURES

NEOREST EW

- 3D Tornado Flush™ system, high efficiency
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Dual Flush function (1.28 GPF/4.8 LPF and 0.9 GPF/3.4 LPF)
- Universal Height
- WASHLET® with three wash modes (front, rear, soft)
- Oscillating and pulsing comfort washing
- Auto lid open/close, auto flush
- Automatic air purifying system
- Adjustable heated seat
- Adjustable spray position
- Programmable energy saver system
- Back-up manual flush
- EWATER+® mists the bowl with electrolyzed water, reducing the need for harsh cleaning chemicals.
- Multifunctional remote control
- ADA compliant

NEOREST In-Wall Tank Unit

- Dual-Max® flushing system, high-efficiency (1.28 GPF/4.8 LPF & 0.9 GPF/3.4 LPF)
- Adjustable 15"-19" mounting height
- Supports up to 880lbs
- Commercial 2" x 6" or optional residential installation with 2" x 4" wall studs with waste outlet kit
- Copper pipe supply line

KIT COMPONENTS

- CT994CEFG#01 Bowl Unit
- SN994M#01 Top Unit
- WT174M
 - NEOREST In-Wall Tank Unit (Copper Pipe)
- YT994#WH
 White Glass Push Plate

COLORS/FINISHES

Standard #01 Cotton











CODES/STANDARDS

- Meets and exceeds:
 - Bowl: ASME A112.4.2, ASME A112.19.2/CSA B45.1, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 # 68
 - Carrier System: ASME A112.6.2
 - Tank Trim: IAPMO PS50, CSA B125.3, ASSE1002
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, and others
- ADA compliant
- Complies with CA Prop 65 warning requirements







NEOREST EW Wall-Hung Toilet, 1.28GPF & 0.9GPF

PRODUCT SPECIFICATIONS

CT994CEFG

The NEOREST EW with the 3D Tornado Flush system toilet shall be 1.28 GPF/4.8 LPF and 0.9 GPF/3.4 LPF. Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall be of skirted design with auto open and close seat. Toilet shall be TOTO Model CT994CEFG.

Water Use: 1.28 GPF & 0.9 GPF

(4.8 LPF & 3.4 LPF)

Flush System: 3D Tornado Flush

Water Pressure: Flowing:

Min 7.25 PSI (0.05MPa)

Static:

Max 108.75 PSI (0.75 MPa)

Water Surface: 5-3/4" x 4"
Trap Diameter: 2" (53 mm)
Trap Seal: 2-1/16" (53 mm)

Warranty: Three Year Limited (Residential)

One Year Limited (Commercial)

Material: Bowl: Vitreous china Seat + Cover: Urea-Resin

Shipping Weight: 81.6 lbs

Shipping Dimensions: 29-5/16" L x 18-1/16" W x 17-1/2" H

SN994M

Power Rating: AC 120 V, 60 Hz, 1300 W

Power Cord: 1.2 m (3.94 ft)

Water Feature: Adjustable Water Flow Rate
Rear Washing: Approx. 0.07 - 0.11 gal/min
Soft Washing: Approx. 0.08 - 0.11 gal/min
Front Washing: Approx. 0.08 - 0.11 gal/min
Wide Front Washing: Approx. 0.09 - 0.11 gal/min
Washing Spray Temperature: Approx: 86°F - 104°F (30°C - 40°C)

Safety Feature: Temperature Fuse
Drying Feature: Air Temperature:

Approx: 95°F - 140°F (35°C - 60°C)

Airflow Volume: 10.2 ft³/min
Safety Feature: Temperature Fuse
Seat Warming Feature: Surface Temperature

Surface Temperature: Approx: 82°F - 97°F (28°C - 36°C)

Seat Heater Capacity: 59 W Safety Feature: Thermal Fuse Air Purifying Feature: O_2 Deodorizer Air Volume: 5.7 ft 3 /min

Ambient Temperature Range: 32°F/0°C to 104°F/40°C

Product Size: 16-7/10" W x 26-3/5" D x 20-9/10" L

Weight: Net: 97 lbs.

Floor to Seat Height: 17 1/4" (438mm) Recommended

Shipping Weight: 26.5 lbs

Shipping Dimensions: 31-1/4" L x 19-9/16" W x 8-7/8" H

WT174M

This universal height, high-efficiency, dual flushing, inwall tank unit toilet shall be 1.28GPF & 0.9GPF. Requires TOTO toilet model CT994CEFG. In-Wall tank system shall be TOTO Model WT174M.

Water Use: 1.28 GPF & 0.9 GPF

(4.8 LPF & 3.4 LPF)

Flush System: Dual-Max®

Min Water Pressure: 7.25 PSI (Flowing)

Installation Height: 15" - 19"

Warranty: One Year Limited


Material: Various Shipping Weight: 43 lbs

Shipping Dimensions: 47-1/2"L x 26"W x 6"H

Installation Note

- For use with potable water only. Do not use with recycled water.
- Adequate structural bracing is required


INCORRECT INSTALLATION





NEOREST EW Wall-Hung Toilet, 1.28GPF & 0.9GPF

PRODUCT DIMENSIONS

CT994CEFG/SN994M







WT174M

