



Walkable flat roof skylight  
Triple pane with non-slip coating

## BENEFITS & PRODUCT PROPERTIES

With a tempered and triple laminated outer pane this walkable flatroof skylight provides day light while maintaining a completely flat, walkable surface when installed on terraces or green roofs. Can be used from 0° - 15° (0:12 to 3:12)

- Frame material multi-chamber PVC profiles partially manufactured from recycled raw material.
- Load capacity of 1,100 lbs/sqft
- Acoustic insulation Rw: 36dB

## TECHNICAL SPECS

<b>U-value window</b>	<b>NFRC 100</b>	0.22 Btu/h ft <sup>2</sup> F
<b>U-value IGU</b>		0.18 Btu/h ft <sup>2</sup> F
<b>SHGC (Solar heat gain)</b>	<b>NFRC 200</b>	0.24
<b>Gas fill</b>		Argon
<b>Ufr</b>	<b>EN 14351</b>	0.67W/m <sup>2</sup> K
<b>Uglass</b>	<b>EN 1279</b>	0.5W/m <sup>2</sup> k
<b>G-value</b>	<b>EN1279</b>	35%
<b>PSIspacer</b>	<b>EN 14351</b>	0.055W/mK
<b>Insulated glazing unit</b>	<b>IGU</b>	1xESG, 2xTVG)-Tg16Ar-4HT-Tg18Ar-66.2T

SIZES	30 x 30	30 x 36	36 x 36	36 x 48	48 x 48
<b>Rough Opening WxH</b>	29.9" x 29.9"	29.9" x 34.8"	34.8" x 34.8"	34.8" x 46.6"	46.6" x 46.6"
<b>Outside Frame</b>	39.3" x 39.3"	39.3" x 44.1"	44.1" x 44.1"	44.1" x 55.9"	55.9" x 55.9"
<b>Daylight area (SF glass)</b>	4.52	5.43	6.46	8.93	12.49

