AT-937



ATTEN 安泰信

ESD Safe Constant Temperature Controllable Soldering Station





Package list	Standard Packing:	
Main unit: 1Unit	Inner box: 26.5x23x16 (CM)	
Handle set: 1 PCS	N.W.: 1.6KG	
Iron stand: 1 PCS	G.W.: 1.78KG	
AC cord: 1 PCS		
Manual: 1 PCS		
Cleaning sponge: 1 PCS		

Specification:

Voltage:	230VAC/50Hz	110VAC/60Hz
Power:	50W	
Temperature range:	200-480°C/392-896°F	
Temperature stability:	±2°C(in still air, no load)	
	Four core stainless steel heater	
Heater:	Four core stair	nless steel heater
Heater: Tip-to-ground impedance:		nless steel heater
		nless steel heater



Silver alloy heater

Features:

- MCU controlled temperature calibration with PID system equipped.
- Imported heat-resistant materials heater with long life.
- The heater using low voltage AC source to ensure the antistatic and no leakage, no interference.
- Steady temperature setting with 200 \sim 480 $^{\circ}$ C.
- Rapid heating-up.
- Legerity handle suitable for long time operation.
- Unique temperature locks setting to avoid adjusting temperature.
- Using split design, easy to place.

