



# Operation

#### Description






#### Suggested Panel Cutout







Max. Panel Thickness: 0.394 (10.0)



## Illuminated Options



#### Actuator Options



## Vandal Resistant Switch Φ16mm

## Anti-Vandal IK09/ Sealed IP65

## Illuminated And Non-Illuminated

## Flat/Concave

## Momentary/ Latching

#### Variety Of Colors

Momentary: Means that when you push Switch and then move your finger, the actuator will back to the original position.

Latching: Means that when you push Switch once it will change state and stay in this pushed-down position and will not come back to original position unless you push it again.


#### Order Code

Seriees	Actuator Options	Terminal	Function	Material Finish	Illuminated Options	Color	Color Voltage	Protection
								· 🗌
L16	F- Flat	Pin(2,8x0,5) blank	M- Momentary	A- Anodized aluminum	D- Dot	W- White	6V	Blank IP40
L16S Short body	H- Raised flat		1 1N01NC	N- Nickel plated brass	R - Ring	Y- Yellow	12V	IP65
	C · Concave		2 2NO2NC	S- Stainless steel	Non-illuminated blank	B. Blue	24V	
	G- Guarded con	cave	Z- Latching			G- Green	36V	
			1 1N01NC			R- Red	110V	
Remark: L16S	will be non-il	lluminated	2 2NO2NC			O- Orange	230V	


#### Technical Data

Туре	L16-F/L16s-F	L16-F/R	L16-F/D			
Illuminated Type	Non-Illuminated		Dot			
Terminal	Non-Illuminated Ring Dot Pin (1.8X0.4)					
	Ith: 3A Ui: 250VAC					
Max.Switch Rating Contact Resistance	101. 3A 01. 230VAC <50mQ					
Insulation Resistance	>100mQ					
Dielectric Strengh	2000VAC					
Operation Temp.	-20°C ~ +55°C					
Mechanical Life	200,000 Cycles					
Electrical Life	>50,000 Cycles					
Contact Material	Silver Alloy					
Torque	5 ~ 14Nm					
Operation Pressure	approx. 3 ~ 5N					
Protection	IP40,IP65/ IK09					
Material						
Button	Stainless steel/ Nickel plated brass/ Anodized aluminum					
Bodey	Stainless steel/ Nickel plated brass/ Anodized aluminum					
Base	PBT					
Color	R G Y O B W					
Туре	LED					
Voltage	6V/ 12V/ 24V/ 36V/ 110V/ 230V					
Life	Approx: 40,000 hours					

### Dimension



## Short Body Version



© Copyright Yueqing LANGIR Electric Co.,Ltd. All Right Reserved.

Disclaimer: The appearance of the products listed on this catalogue, color, parameters are for reference only, issued a kind of LANGIR Electric Company shall prevail.

LANGIR Electric Company reserves the right to modify or cancel the relevant parameters of this catalogue does not advance notice. If in doubt, please contact your sales representative.



ADD: 4th, No. 188 Liuqing North Rd, Liushi, Yueqing, Zhejiang China 325604

FAX: 86 (577) 62737671

TEL: 86 (577) 62737672 62737670 E-mail: sunshine@sunshinele.com

Http://www.anti-vandal-switch.com www.piezo-switch.com