

# TV Connector

## Technical data

Dimensions (L x W x H)	63 x 63 x 12 mm (2.5" x 2.5" x 0.46")
Weight	30 g
Color	Black
Operating conditions	0°C to 40°C (+32°F to +104°F). Relative humidity of <90% (non-condensing)
Transport and storage conditions	-20°C to 60°C (-4°F to +140°F). Relative humidity of <90% for a long period of time

## Power supply

Type	DC, stabilized
Secondary voltage	5 VDC
Max. current	500 mA
Plug	micro-USB
Important notice	Only use the original Phonak power supply or an USB power supply (5 VDC, > 500 mA) compliant with IEC 60065, IEC 60950-1 or IEC 62368-1

## Audio information

Audio inputs	Digital optical (Toslink) Analog (3.5 mm plug)
Audio quality	Stereo, 120 Hz – 7.3 kHz

## Radio information

Streaming technology	AirStream Technology
Frequency range	2.4 GHz ISM band
RF power	20 mW max. (conducted)
Transmission range	Up to 15 m (50 ft)
Max. paired devices	Unlimited

## Standards

Europe	EN 300 328; EN 301 489 ; IEC/EN 60601-1-2 ; EN 60950-1 ; IEC/EN 62479
Canada	RSS-247; RSS-102
Japan	ARIB-T66
USA	CFR 47, part 15.247; FCC OET Bulletin No.65

## Compatibility note

The TV Connector is only compatible with Phonak direct streaming hearing aids.  
For further information please visit our website:  
[www.phonakpro.com/TVconnector](http://www.phonakpro.com/TVconnector)

