Midi Message Types

Midi CC Messages

Parameter	СС	Range	Description	
Bypass	0	0-3	0: Bypass effect pedal with current tails mode 1: Engage effect pedal 2: Bypass with tails 3: Bypass without tails 4: Toggle	
Dry Mix	1	0-127	Dry Level	
Wet Mix	2	0-127	Delay level	
Dose	3	0-127	Wet/Dry Mix	
Regen	4	0-127	Feedback	
Pulse	5	0-127	Time	
Mutation	6	0-127	Modulation	
Algorithm	7	0-127	 0-15: Eq delay: Low pass filter in feedback loop Mutation controls cutoff frequency 16-31: Eq delay Alt: High pass filter in feedback loop Mutation controls cutoff frequency 32- 47: Modulated Delay: Mutation controls the depth of the chorus 48- 63: Modulated Delay Alt: Mutation controls the speed of the chorus 64-79: Filter Delay: Auto filter post delay Mutation controls the depth of the auto filter 80-95: Filter Delay: Auto filter post delay Mutation controls the speed of the auto filter 96-111: Dual Delay Mutation controls the time of the second delay synced to the PULSE time 112-127: Dual Delay Mutation controls the time of the second delay not 	

			synced to the PULSE time	
DIV	8	0-4	0-24: ½ note 25-49: dotted ¼ note 50-74:¼ note 74-99: dotted 1/8th note 100-127: 1/8th note	
Ramp	9	0-1	0:Ramp Reset 1:Ramp Trigger 2:Ramp Trigger/Reset Sending a value of 2 will trigger ramp then reset once Sending a value of 1 will trigger ramp Sending a value of 0 will reset ramp to original knob positions	
Tails Mode	10	0-1	0: Tails OFF 1: Tails ON	
Expression Assign Mode	11	any	Sending any value will enter Expression Assign Mode	
Ramp Assign Mode	12	any	Sending any value will enter Ramp Assign Mode	
Тар	13	any	Sending any value will trigger tap	
Expression	14	0-127	Control Expression assigned parameters	
Previous Preset	15	1-10	Decrements through presets by given value	
Next Preset	16	1-10	Increments through presets by given value	
Midi Clock	17	0-1	0: Midi Clock Off 1: Midi Clock On	
Clear all presets	18	0-127	Any value clears all presets.	

MIDI PC Messages

Parameter	РС	Description
Bypass Toggle	0	Toggles the bypass using the current tails state
Change Preset	1-127	PC1 = Preset 1, PC2 = Preset 2, etc