

LCD Display



Hydraulic Brake



ZOOM Suspension Fork



Cikada

Touring e-Bike

Ride with a Smile

The Cikada Touring e-Bike offers a new and exciting way to venture beyond the familiar. Equipped with a powerful 350W/80Nm mid-drive motor, it is known for its efficient power distribution. The Touring empowers riders to embrace longer trips with ease while enhancing handling and provides a natural riding feel, making it ideal for diverse terrains. Ascending hills becomes effortless with its five pedal-assist modes that makes any climb feel conquerable. Extending boundaries is a snap with the long-lasting LG 720Wh battery, allowing every journey to be more exciting and attainable than ever before!

LG 21700 720 Wh Estimated Range 125 km



Low Step-Through



SPECIFICATIONS



Optional accessory (links to Cikada app)

Frameset

Frame 6061 Aluminum, 27.5"

Fork Alloy suspension fork, Travel 80mm, Threadless, Steerer 28.6mm, 10x100mm

with quick release

Component

Handlebar 31.8mm barbore, 680mm

Stem Adjustable, 31.8mm barbore/ EXT105mm

Headset 1-1/8"*44/50*55/61*30

Black anatomic polyurethane cover, Black Saddle

steel rail

ZOOM, 30.9mm (1.2") x S/M 250mm (9.8"), M/L 300mm (11.8") aluminium Seatpost

Grips Velo Gel

Pedals 9/16" steel axle, size: 112mm x 108mm (4.4" x 4.3")

Bottom Bracket BB73

Braking System

Brakes Hydraulic disc brake, Rotor 160mm

Wheels

Front Hub Alloy, 13Gx3/8x36Hx100mm

Rear Hub Alloy, 13G spokes 3/8x36Hx135mm O.L.D.

Rims Alloy 27.5", Double wall

Tire KENDA Kwick Seven.5 Sport, Anti-puncture

with reflector strip, 27.5x2.8

e-Bike Related

Motor BaFang M410HD 350W/80Nm Mid-drive

Throttle Twist style (right handlebar)

Battery LG 21700, 48V, 15AH, 720Wh UL Certified 2271, 2849

Estimated Range 125km per charge (200 lbs/PAS level 1)

Pedal Assist Torque sensor, 5 PAS levels

Display LCD with Bluetooth

Gears

Crankset Chainring 1/2x3/32x44T, Crank length:170mm

Shift Lever Microshift TS-39, Thumb-tap shifter

Rear Derailleur Microshift RD-M26

Chain KMC, e8S

Cassette Microshift, 8 speed, 11T/34T

Accessories

Tire Pressure Monitor Sensor (TPMS)

Headlight LED (on/off operated via console)

Taillight Reflector Illuminates, Reflector


Shipping

Carton Size 81.0x10.0x51.2" / 2,057x254x1,300mm

NW/GW 30/44 KGS, 66/97 LBS

Assembly Bike is shipped 98% assembled







Battery complies with current safety testing standards.





Alabaster White