

GH16000E-LRT 16kVA HONDA

**16kVA
HONDA
GH16000E-LRT**



ENGINE

MANUFACTURER	Honda
ENGINE MODEL	GX690E
TYPE & CYLINDER	O.H.V.
STARTING	Electric Start
RUN TIME	7hrs @ 60% load
FUEL	Unleaded Petrol
CUBIC CAPACITY	688 cm3
HP 3000 RPM CONT	14.1HP
OIL CAPACITY	1.9L

TECHNICAL

MODEL	GH16000E-LRT
TYPE	Portable
FREQUENCY	50Hz
PHASE/VOLTAGE	1/240

SPEED	POWER		NOISE LEVEL	FUEL CAPACITY	CONTINUOUS OUTPUT
	Max Power		dBa @7m see *1		
	kW	kVA	dBa		
3000RPM	13	16	74	25L	16kVA

ADDITIONAL INFO

OUTLETS	2 x 15 amp 240V outlets switched with thermal overload
FRAME	Extra large roll frame

DIMENSIONS

LENGTH	87cm
WIDTH	70cm
HEIGHT	60cm
WEIGHT	140kg

ALTERNATOR

ALTERNATOR BRAND	Mecc Alte
TYPE	Brushless
HARMONIC DISTORTION	Less than 5%
INSULATION CLASS	Class H

OPTIONS

- Weather protected IP66 outlets
- RCD/ELCB protection
- 4 wheel kit
- Fuel Tank Base with Roll Over Frame