

SAFETY DATA SHEET

Page 1

PRODUCT NUMBER: VGG-9015C
PRODUCT NAME: Wipe-On Clear Coat Gloss Finish

SECTION I - IDENTIFICATION

PRODUCT NUMBER: VGG-9015C
PRODUCT NAME: Wipe-On Clear Coat Gloss Finish
DATE PREPARED: 2/22/2023
REVISION DATE: 3/9/2023

COMPANY: Vice Grip Garage
ADDRESS: 621 West Commerce St
CITY: Lewis burg TN, 37091
PHONE: (405) 805-6084
EMERGENCY PHONE: CHEMTREC: 1-800-424-9300

SECTION II - HAZARDOUS IDENTIFICATION

| | |
|--|-----------------|
| CLASSIFICATION: | |
| Flammable Liquids | Category 3 |
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2B |
| Acute Toxicity, Inhalation | Category 4 |
| Specific target organ toxicity, single exposure, R | Category 3 |
| Germ Cell Mutagenicity | Category 2 |
| Carcinogenicity | Category 1A, 1B |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity, repeated exposure | Category 2 |

SIGNAL WORD: DANGER!

PICTOGRAMS:



HAZARD STATEMENTS:

H226 Flammable liquid and vapor
H315 Causes skin irritation
H320 Causes eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H341 Suspected of causing genetic defects
H350 May cause cancer
H361 Suspected of damaging fertility or the unborn child
H373 Causes damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENTS:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surface - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/light/equipment, etc.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated are.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P302+352 IF ON SKIN: Wash with soap and water.
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9015C
PRODUCT NAME: Wipe-On Clear Coat Gloss Finish

Page 2

breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.

P308+313 IF exposed or concerned: get medical advice/attention.

P312 Call a POISON CENTER or a doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P332+313 If skin irritation occurs: get medical advice/attention.

P337+313 If eye irritation persists get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| MATERIAL: | CAS #: | WEIGHT %: |
|-------------------------------|-----------|-----------|
| 2-Propanone | 67-64-1 | 10-15 |
| Carbonic Acid, Dimethyl Ester | 616-38-6 | 10-15 |
| 2-Butoxyethanol | 111-76-2 | <1 |
| Methyl Amyl Ketone | 110-43-0 | 1-5 |
| Butyl Acetate | 123-86-4 | 1-5 |
| p-Chlorobenzotrifluoride | 98-56-6 | 45-50 |
| Dimethylbenzene | 1330-20-7 | 1-5 |

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES: Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

SKIN CONTACT: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical, or carbon dioxide extinguisher.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

UNUSUAL FIRE FIGHTING HAZARDS: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep all sources of ignition and hot metal surfaces away from spill or release.

ENVIRONMENTAL PRECAUTIONS: Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

METHODS FOR CLEANING UP: Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851)

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9015C
PRODUCT NAME: Wipe-On Clear Coat Gloss Finish

Page 3

for additional information.

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

| MATERIAL: | CAS #: | OSHA PEL: | ACGIH TLV: |
|-------------------------------|-----------|-----------------|-----------------|
| 2-Propanone | 67-64-1 | 750ppm | 500ppm |
| Carbonic Acid, Dimethyl Ester | 616-38-6 | Not Established | Not Established |
| 2-Butoxyethanol | 111-76-2 | 50 ppm | 20 ppm |
| Methyl Amyl Ketone | 110-43-0 | 100 ppm | 50 ppm |
| Butyl Acetate | 123-86-4 | 150 ppm | 150 ppm |
| p-Chlorobenzotrifluoride | 98-56-6 | Not Established | Not Established |
| Dimethylbenzene | 1330-20-7 | 100ppm | 100ppm |

ENGINEERING CONTROLS: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

MONITORING: Follow accepted work practices for handling a flammable material.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistant gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|-------------------|
| APPEARANCE: | Clear |
| ODOR: | Mild |
| ODOR THRESHOLD: | Not Available |
| pH@25°C: | Not Applicable |
| MELTING/FREEZING POINT: | Not Available |
| FLASHPOINT: | Not Available |
| SPECIFIC GRAVITY (water=1): | 1.1 |
| WATER SOLUBILITY: | Negligible |
| AUTO-IGNITION TEMPERATURE: | Not Available |
| DECOMPOSITION TEMPERATURE: | Not Available |
| BOILING RANGE: | 134-662°F |
| EVAPORATION RATE: | Slower than Ether |
| LOWER FLAMMABLE LIMIT: | 1% |
| UPPER FLAMMABLE LIMIT: | 7% |
| VAPOR PRESSURE: | 32.38mm Hg@68°F |
| VAPOR DENSITY (air=1): | >1.0 |
| VISCOSITY: | Not Available |
| VOC AS PACKAGED: | 0.74 |
| VOC REGULATORY: | 2.10 |

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9015C

PRODUCT NAME: Wipe-On Clear Coat Gloss Finish

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO2 and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

TOXICITY:

| | | |
|-------------------------------|--|--|
| MATERIAL: | LD50: | LC50: |
| 2-Propanone | Dermal: 20,000 mg/kg (rabbit) Oral: 5,340 mg/kg (rabbit) | Inhalation: 2,100 ppm (cat) |
| Carbonic Acid, Dimethyl Ester | Dermal: >5,000mg/kg (rabbit) Oral: 13,000mg/kg (rat) | Inhalation: 4 h > 140 mg/l (rat) Irritating to respiratory system |
| 2-Butoxyethanol | Dermal: 440 mg/kg (rabbit) Oral: 1,414 mg/kg (guinea pig) | Inhalation: 700 ppm (mouse) |
| Methyl Amyl Ketone | Dermal: >2,000 mg/kg (rat) Oral: 1,600 mg/kg (rat) | Inhalation: 4 h >16.7 mg/l (rat) |
| Butyl Acetate | Oral: 7,100 mg/kg (mouse) | Inhalation: 2,000 ppm (rat) |
| p-Chlorobenzotrifluoride | Dermal: >2.7 g/kg (rabbit) Oral: >6.8 g/kg (rat) | Inhalation: 4,479 ppm (rat) |
| Dimethylbenzene | Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat) | Inhalation: 4 h 6,350 mg/l (rat) |

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Tocicological Information) for further data on the effects of this product's components on test animals.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is completely biodegradable.

BIOACCUMULATION: This product does not accumulate or biomagnify in the environment.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cuase it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION XIV - TRANSPORT INFORMATION

US GROUND (DOT) SHIPPING INFORMATION:

| | |
|--------------------------------|--------|
| UN NUMBER: | UN1263 |
| PROPER SHIPPING NAME: | PAINT |
| TRANSPORT HAZARD CLASS: | 3 |
| PACKAGING GROUP: | II |

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9015C
PRODUCT NAME: Wipe-On Clear Coat Gloss Finish

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG II.

SECTION XV - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

UNITED STATES INVENTORY (TSCA 8b): All components are listed or exempted.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| | | | | |
|--------|----------|-------|-----------|-----------|
| ACUTE: | CHRONIC: | FIRE: | PRESSURE: | REACTIVE: |
| Yes | Yes | Yes | No | No |

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

| | | |
|-----------------|-----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. |
| Butyl Acetate | 123-86-4 | 1-5 |
| Dimethylbenzene | 1330-20-7 | 1-5 |

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

| | | | |
|-----------------|-----------|----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. | RQ(LBS.) |
| 2- Propanone | 67-64-1 | 10-15 | 5000 |
| 2-Butoxyethanol | 111-76-2 | <1 | 5000 |
| Butyl Acetate | 123-86-4 | 1-5 | 5000 |
| Dimethylbenzene | 1330-20-7 | 1-5 | 100 |

CALIFORNIA PROPOSITION 65:

WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

CANADA:

All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

SECTION XVI - OTHER INFORMATION

HMIS Health: 2
HMIS Flammability: 3
HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

SAFETY DATA SHEET

Page 1

PRODUCT NUMBER: VGG-9025C
PRODUCT NAME: Wipe-On Clear Coat Matte Finish

SECTION I - IDENTIFICATION

PRODUCT NUMBER: VGG-9025C
PRODUCT NAME: Wipe-On Clear Coat Matte
DATE PREPARED: Finish 2/22/2023
REVISION DATE: 3/9/2023

COMPANY: Vice Grip Garage
ADDRESS: 621 West Commerce St
CITY: Lewis burg TN, 37091
PHONE: (405) 805-6084
EMERGENCY PHONE: CHEMTREC: 1-800-424-9300

SECTION II - HAZARDOUS IDENTIFICATION

| | |
|--|-----------------|
| CLASSIFICATION: | |
| Flammable Liquids | Category 3 |
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2B |
| Acute Toxicity, Inhalation | Category 4 |
| Specific target organ toxicity, single exposure, R | Category 3 |
| Germ Cell Mutagenicity | Category 2 |
| Carcinogenicity | Category 1A, 1B |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity, repeated exposure | Category 2 |

SIGNAL WORD: DANGER!

PICTOGRAMS:



HAZARD STATEMENTS:

H226 Flammable liquid and vapor
H315 Causes skin irritation
H320 Causes eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H341 Suspected of causing genetic defects
H350 May cause cancer
H361 Suspected of damaging fertility or the unborn child
H373 Causes damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENTS:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surface - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/light/equipment, etc.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated are.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P302+352 IF ON SKIN: Wash with soap and water.
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9025C
PRODUCT NAME: Wipe-On Clear Coat Matte Finish

Page 2

breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.

P308+313 IF exposed or concerned: get medical advice/attention.

P312 Call a POISON CENTER or a doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P332+313 If skin irritation occurs: get medical advice/attention.

P337+313 If eye irritation persists get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| MATERIAL: | CAS #: | WEIGHT %: |
|-------------------------------|-----------|-----------|
| 2-Propanone | 67-64-1 | 10-15 |
| Carbonic Acid, Dimethyl Ester | 616-38-6 | 10-15 |
| 2-Butoxyethanol | 111-76-2 | <1 |
| Methyl Amyl Ketone | 110-43-0 | 1-5 |
| Butyl Acetate | 123-86-4 | 1-5 |
| p-Chlorobenzotrifluoride | 98-56-6 | 45-50 |
| Dimethylbenzene | 1330-20-7 | 1-5 |

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES: Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

SKIN CONTACT: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical, or carbon dioxide extinguisher.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

UNUSUAL FIRE FIGHTING HAZARDS: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep all sources of ignition and hot metal surfaces away from spill or release.

ENVIRONMENTAL PRECAUTIONS: Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

METHODS FOR CLEANING UP: Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851)

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-9025C
PRODUCT NAME: Wipe-On Clear Coat Matte Finish

Page 3

for additional information.

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

| MATERIAL: | CAS #: | OSHA PEL: | ACGIH TLV: |
|-------------------------------|-----------|-----------------|-----------------|
| 2-Propanone | 67-64-1 | 750ppm | 500ppm |
| Carbonic Acid, Dimethyl Ester | 616-38-6 | Not Established | Not Established |
| 2-Butoxyethanol | 111-76-2 | 50 ppm | 20 ppm |
| Methyl Amyl Ketone | 110-43-0 | 100 ppm | 50 ppm |
| Butyl Acetate | 123-86-4 | 150 ppm | 150 ppm |
| p-Chlorobenzotrifluoride | 98-56-6 | Not Established | Not Established |
| Dimethylbenzene | 1330-20-7 | 100ppm | 100ppm |

ENGINEERING CONTROLS: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

MONITORING: Follow accepted work practices for handling a flammable material.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistant gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|-------------------|
| APPEARANCE: | Clear |
| ODOR: | Mild |
| ODOR THRESHOLD: | Not Available |
| pH@25°C: | Not Applicable |
| MELTING/FREEZING POINT: | Not Available |
| FLASHPOINT: | Not Available |
| SPECIFIC GRAVITY (water=1): | 1.1 |
| WATER SOLUBILITY: | Negligible |
| AUTO-IGNITION TEMPERATURE: | Not Available |
| DECOMPOSITION TEMPERATURE: | Not Available |
| BOILING RANGE: | 134-662°F |
| EVAPORATION RATE: | Slower than Ether |
| LOWER FLAMMABLE LIMIT: | 1% |
| UPPER FLAMMABLE LIMIT: | 7% |
| VAPOR PRESSURE: | 32.38mm Hg@68°F |
| VAPOR DENSITY (air=1): | >1.0 |
| VISCOSITY: | Not Available |
| VOC AS PACKAGED: | 0.74 |
| VOC REGULATORY: | 2.10 |

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

SAFETY DATA SHEET

Page 4

PRODUCT NUMBER: VGG-9025C
PRODUCT NAME: Wipe-On Clear Coat Matte Finish

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO₂ and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

TOXICITY:

| MATERIAL: | LD50: | LC50: |
|-------------------------------|--|--|
| 2-Propanone | Dermal: 20,000 mg/kg (rabbit) Oral: 5,340 mg/kg (rabbit) | Inhalation: 2,100 ppm (cat) |
| Carbonic Acid, Dimethyl Ester | Dermal: >5,000mg/kg (rabbit) Oral: 13,000mg/kg (rat) | Inhalation: 4 h > 140 mg/l (rat) Irritating to respiratory system |
| 2-Butoxyethanol | Dermal: 440 mg/kg (rabbit) Oral: 1,414 mg/kg (guinea pig) | Inhalation: 700 ppm (mouse) |
| Methyl Amyl Ketone | Dermal: >2,000 mg/kg (rat) Oral: 1,600 mg/kg (rat) | Inhalation: 4 h >16.7 mg/l (rat) |
| Butyl Acetate | Oral: 7,100 mg/kg (mouse) | Inhalation: 2,000 ppm (rat) |
| p-Chlorobenzotrifluoride | Dermal: >2.7 g/kg (rabbit) Oral: >6.8 g/kg (rat) | Inhalation: 4,479 ppm (rat) |
| Dimethylbenzene | Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat) | Inhalation: 4 h 6,350 mg/l (rat) |

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Toxicological Information) for further data on the effects of this product's components on test animals.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is completely biodegradable.

BIOACCUMULATION: This product does not accumulate or biomagnify in the environment.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION XIV - TRANSPORT INFORMATION

US GROUND (DOT) SHIPPING INFORMATION:

UN NUMBER: UN1263
PROPER SHIPPING NAME: PAINT
TRANSPORT HAZARD CLASS: 3
PACKAGING GROUP: II

SAFETY

DATA SHEET PRODUCT NUMBER: VGG-9025C

Page 5

PRODUCT NAME: Wipe-On Clear Coat Matte Finish

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG II.

SECTION XV - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

UNITED STATES INVENTORY (TSCA 8b): All components are listed or exempted.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| | | | | |
|--------|----------|-------|-----------|-----------|
| ACUTE: | CHRONIC: | FIRE: | PRESSURE: | REACTIVE: |
| Yes | Yes | Yes | No | No |

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

| | | |
|-----------------|-----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. |
| Butyl Acetate | 123-86-4 | 1-5 |
| Dimethylbenzene | 1330-20-7 | 1-5 |

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

| | | | |
|-----------------|-----------|----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. | RQ(LBS.) |
| 2- Propanone | 67-64-1 | 10-15 | 5000 |
| 2-Butoxyethanol | 111-76-2 | <1 | 5000 |
| Butyl Acetate | 123-86-4 | 1-5 | 5000 |
| Dimethylbenzene | 1330-20-7 | 1-5 | 100 |

CALIFORNIA PROPOSITION 65:

WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

CANADA:

All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

SECTION XVI - OTHER INFORMATION

HMIS Health: 2
HMIS Flammability: 3
HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

SAFETY DATA SHEET

Page 1

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst

SECTION I - IDENTIFICATION

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst
DATE PREPARED: 2/22/2023
REVISION DATE: 3/9/2023

COMPANY: Vice Grip Garage 621
ADDRESS: West Commerce St
CITY: Lewis burg TN, 37091
PHONE: (405) 805-6084
EMERGENCY PHONE: CHEMTREC:1-800-424-9300

SECTION II - HAZARDOUS IDENTIFICATION

| | |
|--|-----------------|
| CLASSIFICATION: | |
| Flammable Liquids | Category 3 |
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2B |
| Acute Toxicity, Inhalation | Category 4 |
| Specific target organ toxicity, single exposure, R | Category 3 |
| Germ Cell Mutagenicity | Category 2 |
| Carcinogenicity | Category 1A, 1B |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity, repeated exposure | Category 2 |

SIGNAL WORD: DANGER!

PICTOGRAMS:



HAZARD STATEMENTS:

H226 Flammable liquid and vapor
H315 Causes skin irritation
H320 Causes eye irritation
H332 Harmful if inhaled
H335 May cause respiratory irritation
H341 Suspected of causing genetic defects
H350 May cause cancer
H361 Suspected of damaging fertility or the unborn child
H373 Causes damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENTS:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surface - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/light/equipment, etc.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P302+352 IF ON SKIN: Wash with soap and water.
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst

Page 2

breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.

P308+313 IF exposed or concerned: get medical advice/attention.

P312 Call a POISON CENTER or a doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P332+313 If skin irritation occurs: get medical advice/attention.

P337+313 If eye irritation persists get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| MATERIAL: | CAS #: | WEIGHT %: |
|-----------------------------------|-----------|-----------|
| Carbonic Acid, Dimethyl Ester | 616-38-6 | 10-15 |
| Methyl Acetate | 79-20-9 | 5-10 |
| Hexamethylene Diisocyanate Trimer | 3779-63-3 | 35-40 |
| Hexamethylene-1, 6-Diisocyanate | 822-06-0 | <1 |
| p-Chlorobenzotrifluoride | 98-56-6 | 40-45 |

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES: Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

SKIN CONTACT: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical, or carbon dioxide extinguisher.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

UNUSUAL FIRE FIGHTING HAZARDS: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep all sources of ignition and hot metal surfaces away from spill or release.

ENVIRONMENTAL PRECAUTIONS: Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

METHODS FOR CLEANING UP: Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

SAFETY DATA SHEET

Page 3

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

| | | | |
|-----------------------------------|-----------|-----------------|-----------------------|
| MATERIAL: | CAS #: | OSHA PEL: | ACGIH TLV: |
| Carbonic Acid, Dimethyl Ester | 616-38-6 | Not Established | Not Established |
| Methyl Acetate | 79-20-9 | 200 ppm | 200 ppm |
| Hexamethylene Diisocyanate Trimer | 3779-63-3 | Not established | 0.5 mg/m ³ |
| Hexamethylene-1, 6-Diisocyanate | 822-06-0 | Not established | 0.005 ppm |
| p-Chlorobenzotrifluoride | 98-56-6 | Not Established | Not Established |

ENGINEERING CONTROLS: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

MONITORING: Follow accepted work practices for handling a flammable material.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistant gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|-------------------|
| APPEARANCE: | Clear |
| ODOR: | Mild |
| ODOR THRESHOLD: | Not Available |
| pH@25°C: | Not Applicable |
| MELTING/FREEZING POINT: | Not Available |
| FLASHPOINT: | Not Available |
| SPECIFIC GRAVITY (water=1): | 1.19 |
| WATER SOLUBILITY: | Negligible |
| AUTO-IGNITION TEMPERATURE: | Not Available |
| DECOMPOSITION TEMPERATURE: | Not Available |
| BOILING RANGE: | 136-530°F |
| EVAPORATION RATE: | Slower than Ether |
| LOWER FLAMMABLE LIMIT: | 1% |
| UPPER FLAMMABLE LIMIT: | 7% |
| VAPOR PRESSURE: | 23.75mm Hg@68°F |
| VAPOR DENSITY (air=1): | >1.0 |
| VISCOSITY: | Not Available |
| VOC AS PACKAGED: | 0.00 |
| VOC REGULATORY: | 0.11 |

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO₂ and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst

Page 4

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

TOXICITY:

| MATERIAL: | LD50: | LC50: |
|-----------------------------------|---|--|
| Carbonic Acid, Dimethyl Ester | Dermal: >5,000mg/kg (rabbit) Oral: 13,000mg/kg (rat) | Inhalation: 4 h > 140 mg/l (rat) Irritating to respiratory system |
| Methyl Acetate | Oral: 6,970 mg/kg (rat) | Inhalation: 4hr 6,350 mg/l (rat) |
| Hexamethylene Diisocyanate Trimer | Dermal: >2,000 mg/kg (rat) Oral: >2,500 mg/kg (rat female) | Inhalation: 4 hr 0.39-0.543 mg/l (rat) |
| Hexamethylene-1, 6-Diisocyanate | Dermal: >7,000 mg/kg (rat) Oral: 959 mg/kg (rat male) | Inhalation: 4 hr 124 mg/m3 (rat) |
| p-Chlorobenzotrifluoride | Dermal: >2.7 g/kg (rabbit) Oral: >6.8 g/kg (rat) | Inhalation: 4,479 ppm (rat) |

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Toxicological Information) for further data on the effects of this product's components on test animals.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is completely biodegradable.

BIOACCUMULATION: This product does not accumulate or biomagnify in the environment.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION XIV - TRANSPORT INFORMATION

US GROUND (DOT) SHIPPING INFORMATION:

UN NUMBER: UN1263
PROPER SHIPPING NAME: PAINT
TRANSPORT HAZARD CLASS: 3
PACKAGING GROUP: II

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG II.

SECTION XV - REGULATORY INFORMATION

SAFETY DATA SHEET

PRODUCT NUMBER: VGG-899C
PRODUCT NAME: Clear Catalyst

U.S. FEDERAL REGULATIONS:
UNITED STATES INVENTORY (TSCA 8b): All components are listed or exempted.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| | | | | |
|--------|----------|-------|-----------|-----------|
| ACUTE: | CHRONIC: | FIRE: | PRESSURE: | REACTIVE: |
| Yes | No | Yes | No | No |

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

| | | |
|---------------------------------|----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. |
| Hexamethylene-1, 6-Diisocyanate | 822-06-0 | <1 |

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

| | | | |
|---------------------------------|----------|----------|----------|
| COMPONENT NAME: | CAS #: | % BY WT. | RQ(LBS.) |
| Hexamethylene-1, 6-Diisocyanate | 822-06-0 | <1 | 100 |

CALIFORNIA PROPOSITION 65:

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

CANADA:

All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

SECTION XVI - OTHER INFORMATION

HMIS Health: 2
HMIS Flammability: 3
HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.