





MIURA

AUTOMATIC XY CUTTER OF FLEXIBLE MATERIALS

High performing cutting machine with rotating blades for X and Y trimming of flexible materials from roll to sheets.

- HIGH PRODUCTIVITY
 - Combined horizontal and vertical cutting for the fastest finish of your rolls
- **MAXIMUM CUTTING PRECISION**

Precise cutting: trimmed images perfectly square every time

- **HIGH PERFORMING**
 - It cuts one roll of 50 meters in less than 5 minutes
- **LOW MAITENANCE COSTS**

Miura ensures low costs maintenance. Blade replacement is simple and needs just a few minutes

✓ LONG-TERM RELIABILITY AND SAFETY

The lengthwise rotary crush cutters last for **100's of thousands of cuts** and are safe for the operator

TOUCH SCREEN DISPLAY

Intuitive set up of the cut parameters

CUTTING FLEXIBILITY

3 cutting modes: 1. automatic by crop marks; 2. sheeting; 3. manual: Miura can trim different lenghts from the same printed roll

✓ SMART REMOTE SYSTEM ▮


Miura can be connected to the internet network for remote assistance, for fast and efficient diagnostics

NEW

SUITABLE FOR:

- > Paper (also laminated or encapsulated)
- > Vinyl & self adhesive vinyl / Backlit & frontlit displa
- > Canvas & polyester (with liner)
- > PVC banner (up to 900 gr/m² 27 oz./ya²)
- Magnetic rubber / Polycarbonate (film)
- > Reflective material
- > Many more..





Fine positioning of the cutting blades (optional)



Advanced cutting mark reader



User-friendly software design



Unwinding shaft brake for adjusting the tension of the material




Aluminium 3"shaft with flanges for the right alignment of the roll



Heavy duty unwinding shaft for rolls Ø 400 mm up to 90 kg weight (optional)





Fine pressure adjustment

(according to the types of

material)



Can be fitted with: (optional):

1. **Motorized Stacker** in line with the cutter: height and inclination electronically adjustable; extensible length up to 3,2 meters

2. Folding collecting table

3. **NEW Tiltable** collecting table with wheels



Adjustable unwinding shaft (optional)

| | MIURA 160 | MIURA 210 | MIURA 265 |
|--------------------------------|---|---|--|
| Working width | 1650 mm (65 in) | 2150 mm (84 in) | 2650 mm (104 in) |
| Maximum cutting thickness | 1,2 mm (0,04 in) | 1,2 mm (0,04 in) | 1,2 mm (0,04 in) |
| Feeding speed | 1 - 30 m/min. (3 - 98 ft/min) | 1 - 30 m/min. (3 - 98 ft/min) | 1 - 30 m/min. (3 - 98 ft/min) |
| Usable cutting units | max. 8 | max. 8 | max. 8 |
| Cross cutting speed | 5-120 m/min. (16-393 ft./in) | 5-120 m/min. (16-393 ft./in) | 5-120 m/min. (16-393 ft./in) |
| Max. roll diameter | 300 mm (12 in) | 300 mm (12 in) | 300 mm (12 in) |
| Max. roll weight | 60 kg (132 lbs) | 60 kg (132 lbs) | 60 kg (132 lbs) |
| Power supply | 110 V - 60 Hz - 650 W | 110 V - 60 Hz - 650 W | 110 V - 60 Hz - 650 W |
| Dimensions (W x D x H) | 2460 x 97 x 1330 mm (96 x 39 x 52 in) | 2960 x 97 x 1330 mm (116 x 39 x 52 in) | 3460 x 97 x 1330 mm (136 x 39 x 52 in) |
| Weight | 330 kg (727 lbs) | 370 kg (815 lbs) | 430 kg (947 lbs) |
| Packing Dimensions (W x D x H) | 2650 x 1150 x 1650 mm (104 x 45 x 65 in) | 3250 × 1250 × 1700 mm (128 × 49 × 67 in) | 3750 x 1250 x 1700 mm (147 x 49x 67 in) |
| Packing Weight | 415 kg (914 lbs) | 540 kg (1190 lbs) | 628 kg (1384 lbs) |

Manufactured in compliance with CE regulations



100% Made by FLEXA
100% Made in Italy







MIURA PLUS

AUTOMATIC XY CUTTER WITH AUTOMATIC VERTICAL ALIGNMENT

High performing cutting machine for X and Y trimming of flexible materials with automatic vertical cutting correction.

HIGH PRODUCTIVITY

Combined horizontal and vertical cutting for the fastest finish for your printed and unprinted rolls

MAXIMUM CUTTING PRECISION

The **edge control** guarantees a perfect straight cutting of the media roll

HIGH PERFORMING

It cuts one roll of 50 meters (164 ft) in less than 5 minutes

LOW MAITENANCE COSTS

Miura ensures low costs maintenance. Blade replacement is simple and needs just a few minutes

✓ LONG-TERM RELIABILITY AND SAFETY

The lengthwise rotary crush cutters last for 100's of thousands of cuts and are safe for the operator

TOUCH SCREEN DISPLAY

Intuitive set up of the cut parameters

CUTTING FLEXIBILITY

3 cutting modes: 1. automatic by crop marks; 2. sheeting; 3. manual: Miura can trim different lenghts from the same printed roll

✓ SMART REMOTE SYSTEM **▲**

Miura can be connected to the internet network for remote assistance, for fast and efficient diagnostics

SUITABLE MATERIALS:

- > Paper (also laminated or encapsulated) / Wallpaper
- > Vinyl & self adhesive vinyl / Backlit & frontlit display
- > Canvas & poliestere (with liner)
- > PVC banner (up to 900 gr/m² 27 oz./ya²)
- Magnetic rubber / Polycarbonate (film)
- > Reflective material / Many more...





Automatic vertical alignment control panel



Optical sensor for vertical alignment



Advanced cutting mark reader



User-friendly software design



Fine positioning of the cutting blades (optional)



Single lengthwise rotary crush cutter (twin cutters optional)



Can be fitted with: (optional):

1. **Motorized Stacker** in line with the cutter: height and inclination electronically adjustable; extensible length up to 3,2 meters

2. **Folding** collecting table

3. **NEW Tiltable** collecting table with wheels





Fine pressure adjustment (according to the types of material)



Slimline lengthwise rotary crush cutter, single or twin, (optional)



Clean working area thanks to the big waste basket

| | MIURA 160 PLUS | MIURA 210 PLUS | MIURA 265 PLUS |
|--------------------------------|---|---|---|
| Working width | 1650 mm (65 in) | 2150 mm (84 in) | 2650 mm (104 in) |
| Maximum cutting thickness | 1,2 mm (0,04 in) | 1,2 mm (0,04 in) | 1,2 mm (0,04 in) |
| Feeding speed | 1 - 30 m/min. (3 - 98 ft/min) | 1 - 30 m/min. (3 - 98 ft/min) | 1 - 30 m/min. (3 - 98 ft/min) |
| Usable cutting units | max. 8 | max. 8 | max. 8 |
| Cross cutting speed | 5-120 m/min (16-393 ft/min) | 5-120 m/min (16-393 ft/min) | 5-120 m/min (16-393 ft/min) |
| Max. roll diameter | 300 mm (12 in) | 300 mm (12 in) | 300 mm (12 in) |
| Max. roll weight | 60 kg (132 lbs) | 60 kg (132 lbs) | 60 kg (132 lbs) |
| Power supply | 110 V - 60z - 650 W | 110 V - 60 Hz - 650 W | 110 V - 60 Hz - 650 W |
| Dimensions (W x D x H) | 2460 x 1000 x 1330 mm (96 x 39 x 52 in) | 2960 x 1000 x 1330 mm (116 x 39 x 52 in) | 3460 × 1000 × 1330 mm (136 × 39 × 52 in) |
| Weight | 415 kg (881 lbs) | 460 kg (1014 lbs) | 530 kg (1168 lbs) |
| Packing dimensions (W x D x H) | 2650 × 1150 × 1650 mm (104 × 45 × 65 in) | 3250 × 1250 × 1700 mm (128 × 49 × 67 in) | 3750 x 1250 x 1700 mm (147 x 49 x 67 in) |
| Packing weight | 500 kg (1102 lbs) | 630 kg (1388 lbs) | 728 kg (1604 lbs) |

Manufactured in compliance with CE regulations



100% Made by FLEXA

100% Made in Italy





NEW CONFIGURATION



MIURA WALLPAPER

AUTOMATIC XY CUTTER FOR WALLPAPER

Highly precise cutting machine for X and Y trimming with automatic vertical cutting correction.

Suitable for wallpaper and many other flexible supports.

- HIGH PRODUCTIVITY
 - Combined horizontal and vertical cutting for the fastest finish of your rolls
- **MAXIMUM CUTTING PRECISION**

The edge control guarantees perfect joints of pattern and designs on the wall.

The sensor has a reading accuracy of 0,05 mm

NO WASTE OF MATERIAL

Each lengthwise rotary crush cutter includes a fine positioning of the cutting blades for micro-adjustments. The result is a perfectly cut wallpaper

MAITENANCE COSTS

Miura ensures low costs maintenance. Blade replacement is simple and needs just a few minutes

LONG-TERM RELIABILITY AND SAFETY

The lengthwise rotary crush cutters last for 100's of thousands of cuts and are safe for the operator

TOUCH SCREEN DISPLAY

Intuitive set up of the cut parameters

CUTTING FLEXIBILITY


3 cutting modes: 1. automatic by crop marks; 2. sheeting; 3. manual: Miura can trim different lenghts from the same printed roll

SMART REMOTE SYSTEM

Miura can be connected to the internet network for remote assistance, for fast and efficient diagnostics







MIURA R AUTOMATIC XY CUTTER OF FLEXIBLE MATERIALS

High performing cutting machine for X and Y trimming of flexible materials from roll to roll and roll to sheets with automatic rewinding system.

- Combined horizontal and vertical cutting for the fastest finish of your rolls
- Trims and directly rewinds cut sheets on rolls (up to 3 rolls, also of different sizes). Possibility to work in addition as roll to sheet
- > 4 operating modes: automatic by crop marks (roll to rolls), automatic by crop marks (roll to sheets), by set length and manual
- Even more intuitive set up parameters thanks to the new designed user-friendly software (LCD touch screen display). New MUTING function that avoids possible misreading of hidden marks
- Long term reliability and safety combined with low maintenance costs

SUITABLE FOR:

- Paper (also laminated or encapsulated)
- **W**allpaper
- Vinyl & self adhesive vinyl
- ☑ Backlit & frontlit display
- **Solution** Reflective material
- PVC banner (up to 900 gr/m² 27 oz./ya²)
- Magnetic rubber
- Polycarbonate (film)
- Canvas & polyester (with liner)
- Many more..





Fine positioning of the cutting blades (optional)_



Advanced cutting mark reader



User-friendly software design



Aluminium 3"shaft with flanges for the right alignment of the roll



Unwinding shaft brake for adjusting the tension of the material



Front rewinding shafts with indipendent clutches





Adjustable unwinding shaft for fine positioning of the material unrolling (optional)





Single lengthwise rotary crush cutter (twin cutters optional)



Speed regulator and switch to adjust the rotation of the rewinding shafts

| Working width | 1650 mm (65 in) |
|---------------------------------|--|
| Feeding speed | 1 - 15 m/min (3 - 49 ft/min) Roll to rolls 1 - 30 m/min (3 - 98 ft./min) Roll to sheets |
| Usable lengthwise cutting units | max. 8 |
| Cross cutting speed | 5 - 120 m/min (16 -393 ft/min) |
| Max. roll diameter | Ø 300 mm (12 in) |
| Max. roll weight | 132 lb |
| Power supply | 110 V - 60 Hz - 650 W |
| Dimensions (W x L x H) | 2500 x 1200 x 1350 mm (99 x 47 x 53 in) |
| Weight | 772 lb |
| Packing Dimensions (W x L x H) | 2650 x 1350 x 1600 mm (104 x 53 x 63 in) |
| Packing Weight | 904 lb |
| | |

Manufactured in compliance with CE regulations



100% Made by FLEXA
100% Made in Italy



Advanced cutting mark reader



Optical sensor for vertical alignment



Automatic vertical alignment control panel



User-friendly software design



Fine positioning of the cutting blades (**NEW** standard)



Can be fitted with: (optional):

- 1. **Motorized Stacker** in line with the cutter: height and inclination electronically adjustable; extensible length up to 3,2 meters
- 2. Folding collecting table
- 3. **NEW Tiltable** collecting table with wheels



Clean working area thanks to the big waste basket



Fine pressure adjustment (according to the types of material)



Slimline lengthwise rotary crush cutter, single or twin, (optional)

Single lengthwise rotary crush cutter (twin cutters optional)

| Working width | 1650 mm (65 in) |
|---------------------------------|---|
| Feeding speed | 1 - 30 m/min (3 - 98 ft./min) |
| Usable lengthwise cutting units | max. 8 |
| Cross cutting speed | 5 - 120 m/min (16 -393 ft/min) |
| Max. roll diameter | Ø 300 mm (12 in) |
| Max. roll weight | 60 kg (132 lbs) |
| Suitable materials | Wallpaper, Canvas & polyester (with liner), paper, vinyl & self adhesive vinyl, backlit & frontlit display, PVC banner, magnetic rubber, polycarbonate (film), reflective material, many more |
| Power supply | 110 V - 60 Hz - 650 W |
| Dimensions (W x L x H) | 2460 x 1000 x 1330 mm (96 x 39 x 52 in) |
| Weight | 415 kg (881 lbs) |
| Packing Dimensions (W x L x H) | 2650 x 1150 x 1650 mm (104 x 45 x 65 in) |
| Packing Weight | 500 kg (1102 lbs) |

Manufactured in compliance with CE regulations



100% Made by FLEXA
100% Made in Italy