

7" Wide

Installation method

Click

Construction

Engineered Wood Surface
Cured Wood Composite Core
Birch Backing

Size

7.21" x 78.74" x 9.2 mm
(183 mm x 2000 mm x 9.2 mm)

Protective Finish

UV-Cured Acrylic

Texture

Natural Wood Grain

Bevels

Micro Bevels

Packaging

7 planks per box, 27.13 SF per box
51 lb per box
40 boxes per pallet

Warranty

80 Year "Lifetime" Residential
10 Year Commercial

Country of Origin

Sweden

Certifications

Greenguard Gold
CARB Compliant
FSC Certified





Test	Test Method	Requirement / Details	Result
Fire Resistance	EN 13501		Bfl-S1 (Hardly Flammable)
Smoke Density	ASTM E662		316 Flaming / 255 Non-Flaming
Critical Radiant Flux	ASTM E648		Class I - 0.82 W / cm ²
Thermal Resistance	EN 12664 / 12667		R 0.07 (m ² x K)/W
Thermal Conductivity	ASTM C518		1.2472 Vlu in. /h ft ² F
Formaldehyde Emission	EN 717-1		E1
Carb Phase 2 Compliant	ASTM D6007-14		Yes
Brinell Hardness	EN 1534		10 HB (Average Value)
Impact Resistance	EN 14354		EC3
Thickness Swell	EN 13329 / ISO 24336		5% Class 34 (<8%)
Taber Abrasion Resistance	ASTM D4060	CS-10 Abrasive Wheels	>5000 cycles w/out breakthrough
Sound Transmission Loss (STC)	ASTM E336/E413	8" Slab Only	55
Impact Isolation Class (IIC)	ASTM E492/E989	8" Slab Only	55
Slip Resistance (COF)	ANSI A137.1/A326.3		Wet: 0.73 (Average Value)
Surface Burning Characteristics for Building Materials	ASTM E84-19b		Class C (Type III)