

## 12W/M 24V LED RGB STRIP

## CUT & CONNECT 24V IP65

12W/M

30K LIFESPAN (HRS)

DIMMABLE

120°

BEAM ANGLE

24V

1 YEAR WARRANTY

CE & ROHS

5050 LED CHIP

CRI 80

### FEATURES & BENEFITS

• 24V • IP65

IP65

- Dimmable
- · Commercial grade high quality
- 30M Reel
- 100mm cut spacing
- · Constant voltage

- Available in RGB Multicoloured light output
- 1 year warranty
  (It is recommended to use
  Aluminium Extrusion for all LED
  Strip installs to prevent premature
  failure. Warranty will be extended
  to 2 years if installed with
  Aluminium Extrusion)

### COMPATIBLE CONTROLLERS





RF 8 ZONE LED STRIP REMOTE CONTROL

MULTI RF CONTROLLER

#### SPECIFICATIONS

| Product Code  | Power | Colour | Lumens  | Cutting Space | Dimensions |
|---------------|-------|--------|---------|---------------|------------|
| BI24-RGB-IP65 | 12W/m | RGB    | 380lm/m | 100mm         | 10 x 30000 |





RGB Double End Connector

RGB Single End Connector

# 12W 24V LED RGB STRIP ACCESSORIES

### LED STRIP CONNECTORS

#### **DRIVER REFERENCE TABLE**

It is recommended to run a maximum of 10 metres continuously to avoid any voltage drop and leave a 20% tolerance on a driver. For further information about the 24V DC LED Drivers see pages 81-83

| 15W  | 1M    |
|------|-------|
| 30W  | 2M    |
| 60W  | 4M    |
| 100W | 6.6M  |
| 150W | 10M   |
| 200W | 13.3M |
| 250W | 16.6M |
| 300W | 20M   |

| SPECIFICATIONS |                               |
|----------------|-------------------------------|
| Product Code   | Description                   |
| CD-SEND-RGB    | 10mm RGB Single End Connector |
| CD-DEND-RGB    | 10mm RGB Single End Connector |