

LAGUNA BAND SAW COMPARISON



Model	14 12	14 BX 110V	14 BX 220V	18 BX	18 CX
Motor	1.75 HP 110V	1.75 HP 110V	2.5 HP 220V	3 HP 220V	1.75 HP 110V
Dust Collection	4" Port	(2) 4" Ports	(2) 4" Ports	(2) 4" Ports	(2) 4" Ports
Blade Length	115"	115"	115"	145"	145"
Resaw Height	12"	12"	12"	16"	16"
Blade Width	1/4" to 3/4" *	1/4" to 3/4" *	1/4" to 3/4" *	1/4" to 1-1/4" *	1/4" to 1-1/4" *
Guides	Ceramic	Ceramic	Ceramic	Ceramic	Ceramic
Foot Brake	N/A	Disc Brake	Disc Brake	Disc Brake	Disc Brake
Miter Slot	3/8" x 3/4"	3/8" x 3/4"	3/8" x 3/4"	3/8" x 3/4"	3/8" x 3/4"
Fence	Hi/Low Fence 5-1/2" x 18"	Hi/Low Fence 5-1/2" x 18"	Hi/Low Fence 5-1/2" x 18"	Hi/Low Fence 5-3/4" x 22-1/2"	Hi/Low Fence 5-3/4" x 22-1/2"
Table	Cast Iron 21-1/2" x 16" Tilt: +45° Right/-7° Left	Cast Iron 21-1/2" x 16" Tilt: +45° Right/-7° Left	Cast Iron 21-1/2" x 16" Tilt: +45° Right/-7° Left	Cast Iron 20" x 26" Tilt: +45° Right/-6° Left	Cast Iron 20" x 26" Tilt: +45° Right/-6° Left
Weight	258 Lbs.	260 Lbs.	270 Lbs.	410 Lbs.	480 Lbs.
Footprint	31-1/2" x 26-7/8" 25-1/4" x 18-1/8" Base	29-3/4" x 26-7/8" 22-11/16" x 17-9/16" Base	29-3/4" x 26-7/8" 22-11/16" x 17-9/16" Base	36-3/16" x 29-7/8" 27 x 19-11/16" Base	36-3/16" x 29-7/8" 27 x 19-11/16" Base
Optional Accessories	Mobility Kit Work Lights Mini Guides	Mobility Kit Work Lights Mini Guides	Mobility Kit Work Lights Mini Guides	Mobility Kit Work Lights Mini Guides	Mobility Kit Work Lights Mini Guides
Additional Features	Tension/Tracking Windows Tension Release Lever	Tension/Tracking Windows Tension Release Lever	Tension/Tracking Windows Tension Release Lever	Tension/Tracking Windows Tension Release Lever	Mechanical Variable Speed Low Range: 100-290 SFPM High Range: 1200-3500 SFPM

* Blades smaller than 1/4" can be used with the optional Mini Guides