



# Kwik-Stik Wall Padding



## **Standard Kwik-Stik: KS600**

- Exclusive 1" thick fire-retardant foam core and hot-sprayed #457 vinyl coating.
- Meets or exceeds ASTM F2440 Wall Padding Standard.
- Kwik-Stik wall padding is a great solution for training and fitness facilities.
- Easily customized with logos, lettering, and customized graphics.
- Microban® antimicrobial product protection is available as an added option.
- Available in 27 standard Resilite vinyl-coating colors.



1.800.THE.MATS | WWW.RESILITE.COM



**RESILITE: RSP600 - Kwik-Stick**

REV: 0415

**Specification Sheet**

**Physical Properties:**

polymur	PVC/NBR
foam core color	NATURAL
weight	0.8 - 1.0 (lb/ft <sup>2</sup> )
thickness (nominal)	1.00 (in)
coating	Resilite #457 Polyvinyl Formula

**Other Specifications:**

ASTM D-1056	Compression Resistance @ 25%	5.5 - 7.5 (psi)
ASTM D-1056	Compression Set @ 50%	25 max (%)
ASTM D-1056	Density	4.0 - 7.0 (lb/ft <sup>3</sup> )
ASTM D-1056	Water Absorption %	10 max. (%)
ATSM D-412	Tensile	75 min (psi)
ATSM D-412	Elongation	100 min. (%)
ASTM D-624	C-Tear Strength	17.5 min. ( lbs/in)
FMVSS302	Flammability	Pass
ASTM E648	Flammability - Critical Radiant Flux of Floor Coverings	PASS / Class I (<) 0.45 Watts/cm <sup>3</sup>
ASTM D-1056	Temperature Use	0 (cold crack) 200 (high)
ASTM F-1081-03	Standard Specification for Competition Wrestling Mats	Meets or Exceeds
ASTM F-355-01	Test method for shock absorbing properties (Type I or Type II)	Pass G-Max (<) 100 max.
ASTM F-1292-04	Impact Attenuation for surfacing materials (Free-Fall method)	Pass HIC (<) 1000 max. Pass G-Max (<) 200 max.

Resilite provides this information as a technical service. To the extent the information is derived from sources other than Resilite, Resilite is substantially, if not wholly, relying upon other sources to provide accurate information. Each user of these products, or information should perform their own testing to determine the safety and suitability of the products. Since Resilite cannot control the end use of this product, Resilite does not guarantee that the user will obtain the same results published in this document. The data herein contained is provided as a service. The information is subject to change without notice.

**Resilite Sports Products, Inc.**

PO Box 764 • Sunbury, PA 17801-0764  
Phone: 1-800-843-6287 • www.resilite.com