

ResiTough™ Flooring Specifications



Dear Customer:

Thank you for selecting Resilite Sports Products as one of the potential suppliers for your protective flooring. Resilite's ResiTough™ Flooring interlocks to give you continuous, shock-absorbing protection for your floors. Our, outstanding service and dedication to customer satisfaction is second to none. We work directly with you to ensure we meet the needs and expectations of each and every customer.

ResiTough™ Flooring is manufactured in the USA from the highest quality, recycled rubber and EPDM rubber flecks. These raw materials are much more effective at absorbing impact, reducing noise and vibrations and will last years longer than plastics or foams.

Installation is easy with ResiTough™ Flooring's interlocking system and requires no adhesive. Edge mats and corners are available with straight edging for a professional, wall-to-wall installation.

Please feel free to use these attached specifications to help you develop your RFP, or use them when comparing products from other manufacturers.

Thank You.

ResiTough™ Flooring Specifications



- ResiTough™ Industrial Rubberized Flooring with precision-cut, interlocking joints. Polyethylene foam tiles are not acceptable.
- 23" x 23" x 3/8" (8mm) (coverage of 3.67 sq ft / tile).
- Weight: 1.95 lbs. / sq ft. (7.8 lbs / tile)
- Tensile Strength: ASTM D412 – 200 lb / in² min.
- Flexibility: ASTM F137 – Pass ¼ inch mandrel
- Coefficient of Friction: ASTM D2047 -- >0.9
- Static Load Limit: ASTM F970, 1,000 lbs. -- <0.020 in.
- Elongation at Break: ASTM D412 – 75% min.
- Noise reduction Coefficient: ASTM C423 – 0.10 sabine / ft²
- Industrial rubber flooring shall be guaranteed at least 1 year from the date of shipment.