

# Casonara LED Specifications

## GENERAL INFORMATION

### CASONARA WALL LED LIGHT ARRAY SPECS

ITEM	SYMBOL	VALUE	UNIT
Input Voltage	V	12	V
Power Dissipation	$P_D$	80	W
Operation Temperature	$T_{OPR}$	-22 to 122	°F
Storage Temperature	$T_{STG}$	-22 to 122	°F
Luminous	$I_V$	700	$L_M$
Spread	$\lambda$		um
Viewing Angle			
Color Temp	TC	11000 to 13000	K
Size		28 x 10.6 x 4.3	inch

#### POWER ADAPTOR:

Input: 110/220VAC, 50/60Hz

Output: 12VDC 33.3A 400W

### CASONARA COUNTER LED LIGHT ARRAY SPECS

ITEM	SYMBOL	VALUE	UNIT
Input Voltage	V	12	V
Power Dissipation	$P_D$	40	W
Operation Temperature	$T_{OPR}$	-22 to 122	°F
Storage Temperature	$T_{STG}$	-22 to 122	°F
Luminous	$I_V$	700	$L_M$
Spread	$\lambda$		um
Viewing Angle			
Color Temp	TC	11000 to 13000	K
Size		28 x 10.6 x 4.3	inch

#### POWER ADAPTOR:

Input: 110/220VAC, 50/60Hz

Output: 12VDC 8.3A 100W