

acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

SECTION 1: Identification

1.1 Product identifier

Trade name X10 Wheel and Tire Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Tire and wheel cleaner

Professional use Industrial use

Uses advised against Do not use for squirting or spraying. Do not use for

products which come into direct contact with the skin.

HS code 3402.41.90.

1.3 Details of the supplier of the safety data sheet

HookUp, LLC 1000 Skokie Blvd Northbrook IL 60062 United States

Telephone: 1.847.387.7000 e-mail: az@x10care.com Website: x10care.com

e-mail (competent person) az@x10care.com

1.4 Emergency telephone number

Emergency information service USA 1.847.387.7000

24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05



United States: en Page: 1 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

- Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

- Precautionary statements

P234 Keep only in original container.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P390 Absorb spillage to prevent material damage.

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

sodium hydroxide, N,N-Diethoxylated-N-coco-N-methylammonium chloride, Alcohols, C9-11 ethoxylated, sodium metasilicate, anhydrous

2.3 Other hazards

Hazards not otherwise classified

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS **Identifier** Wt% Classification acc. to GHS Name of substance **Notes** N,N-Diethoxylated-N-coco-N-CAS No 1-<5 Eye Dam. 1 / H318 61791-10-4 methylammonium chloride CAS No 1-<5 sodium metasilicate, anhyd-Acute Tox. 4 / H302 rous 6834-92-0 Acute Tox. 3 / H331 Skin Corr. 1B / H314 STOT SE 3 / H335 CAS No 2-<5 Acute Tox. 4 / H302 sodium hydroxide 1310-73-2 Skin Corr. 1A / H314 Eye Dam. 1 / H318 Met. Corr. 1 / H290

United States: en Page: 2 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Hazardous	ingredients	acc.	to	GHS
-----------	-------------	------	----	-----

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1-<5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318	
1-butoxypropan-2-ol	CAS No 5131-66-8	1-<3	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227	
methanol	CAS No 67-56-1	0.1-<0.19	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225	

For full text of abbreviations: see SECTION 16.

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 3 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Protect against external exposure, such as

frost

Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

United States: en Page: 4 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	sodium hydroxide	1310-73- 2	REL						2		NIOS H REL
US	sodium hydroxide	1310-73- 2	TLV®						2		AC- GIH® 2019
US	sodium hydroxide	1310-73- 2	PEL		2						29 CFR 1910.1 000
US	sodium hydroxide (caustic soda)	1310-73- 2	PEL (CA)						2		Cal/ OSHA PEL
US	methanol	67-56-1	TLV®	200		250				Н	AC- GIH® 2019
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOS H REL
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1 000
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/ OSHA PEL

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

absorbed through the skin short-term exposure allower which exposure should not occur and which is related to a 15-minute period (unless H STEL

otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2019

United States: en Page: 5 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Relevant DNELs of components of the mixture

CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
6834-92-0	DNEL	6.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
6834-92-0	DNEL	1.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
1310-73-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
68439-46-3	DNEL	2,080 mg/ kg	human, dermal	worker (industry)	chronic - systemic effects
68439-46-3	DNEL	294 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
5131-66-8	DNEL	147 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
5131-66-8	DNEL	52 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic ef- fects
	6834-92-0 6834-92-0 1310-73-2 68439-46-3 68439-46-3 5131-66-8 67-56-1 67-56-1 67-56-1 67-56-1	6834-92-0 DNEL 6834-92-0 DNEL 1310-73-2 DNEL 68439-46-3 DNEL 68439-46-3 DNEL 5131-66-8 DNEL 5131-66-8 DNEL 67-56-1 DNEL 67-56-1 DNEL 67-56-1 DNEL 67-56-1 DNEL	point level 6834-92-0 DNEL 6.2 mg/m³ 6834-92-0 DNEL 1.5 mg/kg bw/day 1310-73-2 DNEL 1 mg/m³ 68439-46-3 DNEL 2,080 mg/kg 68439-46-3 DNEL 294 mg/m³ 5131-66-8 DNEL 147 mg/m³ 5131-66-8 DNEL 52 mg/kg bw/day 67-56-1 DNEL 130 mg/m³ 67-56-1 DNEL 130 mg/m³ 67-56-1 DNEL 130 mg/m³ 67-56-1 DNEL 20 mg/kg bw/day 67-56-1 DNEL 20 mg/kg bw/day 67-56-1 DNEL 20 mg/kg	point level route of exposure 6834-92-0 DNEL 6.2 mg/m³ human, inhalatory 6834-92-0 DNEL 1.5 mg/kg bw/day human, dermal 1310-73-2 DNEL 1 mg/m³ human, inhalatory 68439-46-3 DNEL 2,080 mg/kg human, dermal 68439-46-3 DNEL 294 mg/m³ human, inhalatory 5131-66-8 DNEL 147 mg/m³ human, inhalatory 5131-66-8 DNEL 52 mg/kg bw/day human, dermal 67-56-1 DNEL 130 mg/m³ human, inhalatory 67-56-1 DNEL 130 mg/m³ human, inhalatory 67-56-1 DNEL 130 mg/m³ human, inhalatory 67-56-1 DNEL 20 mg/kg human, dermal 67-56-1 DNEL 20 mg/kg human, dermal	point level route of exposure 6834-92-0 DNEL 6.2 mg/m³ human, inhalatory worker (industry) 6834-92-0 DNEL 1.5 mg/kg human, dermal worker (industry) 1310-73-2 DNEL 1 mg/m³ human, inhalatory worker (industry) 68439-46-3 DNEL 2,080 mg/kg human, dermal worker (industry) 68439-46-3 DNEL 294 mg/m³ human, inhalatory worker (industry) 5131-66-8 DNEL 147 mg/m³ human, inhalatory worker (industry) 5131-66-8 DNEL 52 mg/kg human, dermal worker (industry) 67-56-1 DNEL 130 mg/m³ human, inhalatory worker (industry) 67-56-1 DNEL 20 mg/kg human, dermal worker (industry)

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.1 ^{mg} / _I	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.1 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	1.4 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	14 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	14 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	1 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.014 ^{mg} / _l	aquatic organisms	water	intermittent release

United States: en Page: 6 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Relevant PNECs of components of the mixture

TICIEVAIIT INEOS C	Ticlevant i NEGS of components of the mixture					
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
1-butoxypropan-2-ol	5131-66-8	PNEC	10 ^{mg} / _I	microorganisms	sewage treatment plant (STP)	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	2.4 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	5.3 ^{mg} / _l	aquatic organisms	water	intermittent release
1-butoxypropan-2-ol	5131-66-8	PNEC	0.24 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.53 ^{mg} / _I	aquatic organisms	freshwater	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.052 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	10 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	2.4 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.24 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.16 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
methanol	67-56-1	PNEC	100 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	1,540 ^{mg} / _l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	21 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	2.1 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
methanol	67-56-1	PNEC	100 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
methanol	67-56-1	PNEC	100 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls General ventilation.

United States: en Page: 7 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	dark green
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	14 (25 °C) (base)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 961 mbar
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	32 hPa at 25 °C
Density	1.1 ⁹ / _{cm³}
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

United States: en Page: 8 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	260 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc.	to NEC 500)	T2C (maximum permissible surface temperature on the equipment:
	,	230°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

United States: en Page: 9 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium metasilicate, anhydrous	6834-92-0	oral	1,349 ^{mg} / _{kg}
sodium metasilicate, anhydrous	6834-92-0	inhalation: vapor	>2.1 ^{mg} / _l /4h
sodium metasilicate, anhydrous	6834-92-0	inhalation: dust/mist	0.5 ^{mg} / _l /4h
sodium hydroxide	1310-73-2	oral	325 ^{mg} / _{kg}
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200 ^{mg} / _{kg}
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000 ^{mg} / _{kg}
methanol	67-56-1	oral	100 ^{mg} / _{kg}

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium metasilicate, an- hydrous	6834-92-0	LC50	310 ^{mg} / _l	fish	96 h
sodium metasilicate, an- hydrous	6834-92-0	EC50	1,700 ^{mg} / _l	aquatic invertebrates	48 h

United States: en Page: 10 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium hydroxide	1310-73-2	LC50	<180 ^{mg} / _I	fish	96 h
sodium hydroxide	1310-73-2	EC50	40 ^{mg} / _l	aquatic invertebrates	48 h
Alcohols, C9-11 eth- oxylated	68439-46-3	LC50	8.5 ^{mg} / _I	fathead minnow	96 h
Alcohols, C9-11 eth- oxylated	68439-46-3	EC50	5.3 ^{mg} / _I	daphnia magna	48 h
Alcohols, C9-11 eth- oxylated	68439-46-3	ErC50	1 – 10 ^{mg} / _l	algae	96 h
1-butoxypropan-2-ol	5131-66-8	LC50	<1,000 ^{mg} / _l	fish	96 h
1-butoxypropan-2-ol	5131-66-8	EC50	<320 ^{mg} / _I	fish	96 h
methanol	67-56-1	LC50	15,400 ^{mg} / _l	fish	96 h
methanol	67-56-1	EC50	12,700 ^{mg} / _l	fish	96 h
methanol	67-56-1	ErC50	22,000 ^{mg} / _l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium metasilicate, an- hydrous	6834-92-0	EC50	>100 ^{mg} / _I	microorganisms	3 h
sodium hydroxide	1310-73-2	EC50	22 ^{mg} / _l	microorganisms	15 min
1-butoxypropan-2-ol	5131-66-8	EC50	>1,000 ^{mg} / _l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

United States: en Page: 11 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 l	UN	num	ber
--------	----	-----	-----

DOT UN 3266
IMDG-Code UN 3266
ICAO-TI UN 3266

14.2 UN proper shipping name

DOT Corrosive liquid, basic, inorganic, n.o.s.

IMDG-Code CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

ICAO-TI Corrosive liquid, basic, inorganic, n.o.s.

Technical name (hazardous ingredients) sodium metasilicate, anhydrous, methanol

14.3 Transport hazard class(es)

DOT 8
IMDG-Code 8
ICAO-TI 8

14.4 Packing group

DOT III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous

goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

United States: en Page: 12 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Transport of dangerous goods by road or rail (49 CFR US DOT)

Particulars in the shipper's declaration UN3266, Corrosive liquid, basic, inorganic, n.o.s.,

(contains: sodium metasilicate, anhydrous, methanol),

8, III

Reportable quantity (RQ) 33,832 lbs (15,360 kg) (sodium hydroxide) (methanol)

Danger label(s) 8



Special provisions (SP) IB3, T7, TP1, TP28

ERG No 154

International Maritime Dangerous Goods Code (IMDG)

Marine pollutant Danger label(s) 8



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

EmS

F-A, S-B

Stowage category A

Segregation group 18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR)

Danger label(s) 8



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

Limited quantities (LQ)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

United States: en Page: 13 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings Name of substance **CAS No** Remarks **Effective date** 1986-12-31 methanol 67-56-1

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)
sodium hydroxide	1310-73-2		1	1000 (454)

Legend

"1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act "3" indicates that the source is section 112 of the Clean Air Act

3

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
N,N-Diethoxylated-N-coco-N-methylammoni- um chloride	61791-10-4	surfactant	
sodium metasilicate, anhydrous	6834-92-0	cleaning agent	
sodium hydroxide	1310-73-2	pH adjusting agent	OEHHA RELs
Alcohols, C9-11 ethoxylated	68439-46-3	surfactant	
acrylic polymer	75760-37-1	viscosity modifier	
1-butoxypropan-2-ol	5131-66-8	co-solvent	
disodium cocoamphodipropionate	68604-71-7	surfactant	
EDTA, anhydrous	64-02-8	chelate / se- questrant	
methanol	67-56-1	alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHHA RELs Prop 65
cocoyl hydroxyethylimidazoline	61791-38-6	non-functional con- stituent	
trisodium nitrilotriacetate, anhydrous	5064-31-3	chelate / se- questrant	

United States: en Page: 14 / 20

[&]quot;4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
methanol	67-56-1				1.0 %
sodium hydroxide	1310-73-2				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
sodium hydroxide	1310-73-2	A, N, O	

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
 Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910,

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methanol	67-56-1		TE F3
sodium hydroxide	1310-73-2		CO R1

Legend

CO Corrosive

F3 Flammable - Third Degree R1 Reactive - First Degree

TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
METHANOL	67-56-1	E
SODIUM HYDROXIDE (NA(OH))	1310-73-2	E

Legend

Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methanol	67-56-1	T, F
sodium hydroxide	1310-73-2	T, F
sodium hydroxide	1310-73-2	T, F
sodium hydroxide	1310-73-2	T, F

Legend

F Flammability (NFPA®)

United States: en Page: 15 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
methanol	67-56-1	0.12 wt%		developmental

VOC content

Regulated Volatile Organic Compounds (VOC-EPA)Regulated Volatile Organic Compounds (VOC-Cal ARB)2.1 %

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard flammability: flammability hazards Health: health hazard

Personal protection: personal protective equipment (PPE) for normal use

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

United States: en Page: 16 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

EC Substance Inventory (EINECS, ELINCS, NLP) **ECSI**

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances ISHA-ENCS

Inventory of Existing and New Chemical Substances (ISHA-ENCS) KECI Korea Existing Chemicals Inventory

NZIoC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances Taiwan Chemical Substance Inventory TCSI

TSCA Toxic Substance Control Act

15.2 **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book"). Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists

United States: en Page: 17 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

on the iions/tlv-
on the ions/tlv-
.s)
es)
50 %
protect-
rowth
tions
ustoms
b lethal-
)

United States: en Page: 18 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Abbr.	Descriptions of used abbreviations
Met. Corr.	Substance or mixture corrosive to metals
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

United States: en Page: 19 / 20



acc. to 29 CFR 1910.1200 App D

X10 Wheel and Tire Cleaner

Version number: GHS 1.0 Date of compilation: 2023-07-31

Code	Text
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H370	Causes damage to organs.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 20 / 20