


**NOTES:**

1. RECOMMENDED MINIMUM 18" CLEARANCE ALL AROUND SPA, UNLESS OTHERWISE SPECIFIED.
  2. (2) SYMBOL SHOWS 8 OPTIONAL INTERIOR PERIMETER LIGHT LOCATIONS.
  3. IF EQUIPPED, OZONATOR IS LOCATED BEHIND PANEL ON THE PUMP/PACK SIDE.
  4. DRAIN VALVE LOCATED BEHIND PANEL ON THE PUMP/PACK SIDE
  5. SEE OWNERS MANUAL FOR COMPLETE LOCATING , ELECTRICAL AND SAFETY INSTRUCTIONS.
  6. LOAD: 160 PSF
- \*COVER LIFTER AND STEP ARE PART OF SUITE PACKAGE.



120V ELECTRICAL CORD/PLUG FOR AC2-PU1, 12 FT LENGTH

RECOMMENDED ELECTRICAL PASS-THROUGH AREA FOR PERMANENT WIRING OF AC2-PU2 OR CONVERTED AC2-PU1. SEE ROUTING & ELECTRICAL SUGGESTIONS.

**PREINSTALL LAYOUT  
CROSSOVER 730L (AC2-PU1)  
CROSSOVER 740L (AC2-PU2)  
SUITE PACKAGE**