

TORCHSTAR

3000K

LED RECESSED LIGHT



2-Inch Anti-Glare Downlight **6 PACK**

- Wattage** 9W
- Luminous flux** 600lm
- Beam angle** 36°
- Material** Aluminum
- Voltage** 120V
- Lifespan** 50,000hrs
- Dimming range** 10%-100%
- Working temp** -13°F-113°F
- Dimensions** 2.4 inches (H) x 3.1 inches (D)



- Glare free thanks to optical lens and pearly luster surface, easy to install with its cylindrical junction box
- 2-inch cutting hole fits multiple installation methods
- ETL and Energy Star listed, T24 & JA8 certified, the 5-year warranty protects your interest
- CRI90+ offers high-quality lighting, aluminum light body and metal buckles are firmer and more stable
- Dimmable, 100% to 10% dimming range
- A little in, a lot out

Compatible Dimmers

LUTRON: SCL-153P, S-600-WH, DVWCL-153PH, DV-600P-WH, DVLV-600P-WH, DVCL-153P-WH, DVELV-300P-WH, MRF2-6ELV-120-WH, MRF2-600M-SW, MALV-600-WH, TTCL-100DH-WH-C, TBL03, VT-600-13-WH, VTELV-600M-W-WH, NLV-600-WH, NTLV-600-WH, NT-600, NTELV-600-WH, N-600-WH, AY-600-WH, SELV-300P

LEVITON: 6681, IPI06-1L, 6672-L, IPL06-12A, 6631-L

Caution: PLEASE turn off the power at the fuse box or circuit breaker before installing. ONLY use on 120V circuits, Damp location rated. Due to electric shocks, DO NOT use where direct water exposure occurs. DO NOT use this fixture near any source of heat. PLEASE keep this product out of the reach of children under 3 years old.

Warranty: TORCHSTAR warrants that this product is free from defects in materials and workmanship for a period of 5 years from the day of purchase. If the product has been misused, damaged by accident or in any other way of improper use, this warranty becomes void.

For further information, please go to www.torchstar.us



TORCHSTAR

3000K

LED RECESSED LIGHT



2-Inch Anti-Glare Downlight **6 PACK**

- Wattage** 9W
- Luminous flux** 600lm
- Beam angle** 36°
- Material** Aluminum
- Voltage** 120V
- Lifespan** 50,000hrs
- Dimming range** 10%-100%
- Working temp** -13°F-113°F
- Dimensions** 2.4 inches (H) x 3.1 inches (D)



- Glare free thanks to optical lens and pearly luster surface, easy to install with its cylindrical junction box
- 2-inch cutting hole fits multiple installation methods
- ETL and Energy Star listed, T24 & JA8 certified, the 5-year warranty protects your interest
- CRI90+ offers high-quality lighting, aluminum light body and metal buckles are firmer and more stable
- Dimmable, 100% to 10% dimming range
- A little in, a lot out

Compatible Dimmers

LUTRON: SCL-153P, S-600-WH, DVWCL-153PH, DV-600P-WH, DVLV-600P-WH, DVCL-153P-WH, DVELV-300P-WH, MRF2-6ELV-120-WH, MRF2-600M-SW, MALV-600-WH, TTCL-100DH-WH-C, TBL03, VT-600-13-WH, VTELV-600M-W-WH, NLV-600-WH, NTLV-600-WH, NT-600, NTELV-600-WH, N-600-WH, AY-600-WH, SELV-300P

LEVITON: 6681, IPI06-1L, 6672-L, IPL06-12A, 6631-L

Caution: PLEASE turn off the power at the fuse box or circuit breaker before installing. ONLY use on 120V circuits, Damp location rated. Due to electric shocks, DO NOT use where direct water exposure occurs. DO NOT use this fixture near any source of heat. PLEASE keep this product out of the reach of children under 3 years old.

Warranty: TORCHSTAR warrants that this product is free from defects in materials and workmanship for a period of 5 years from the day of purchase. If the product has been misused, damaged by accident or in any other way of improper use, this warranty becomes void.

For further information, please go to www.torchstar.us

