



3 STAR INDUSTRIES

ARCTIC CAT STAMPEDE

WINDSHIELD

**DO NOT REMOVE
PROTECTIVE PAPER FROM
WINDSHIELD THIS WILL BE
YOUR LAST INSTALLATION
STEP!**

STEP 1

Assemble wingnut, neoprene washer and bolt.



STEP 2

Wrap loop clamps around the roll bar, flat part of the clamp facing outward and resting on the windshield.

Part	Qty	Description
	4	1 3/4" Loop clamp
	4	Neoprene Washer
	4	1-1/2" Bolt
	4	Wingnut
	4	Small Washer
	4	Lock Nut
	2	10" Velcro Strap



STEP 3

Set windshield on the hood line, peel back protective paper enough to expose the clamp holes, line up holes in windshield with holes in clamps. Install adhesive Velcro under the loop clamps.



Insert wingnut, neoprene washer and bolt assembly through the front of the windshield, then through the clamp holes.

STEP 5

Secure with small washer and lock nut. Repeat these steps for all clamp holes. Hand tighten only at this time.



STEP 6

When your windshield is setting in the appropriate position, tighten all lock nuts! Do not over tighten! Your neoprene washer should rest against firmly against the windshield. If your neoprene washer is sunk in, you have over tightened your lock nuts. Over tightening may cause the windshield to crack near the clamp hole.

STEP 7

Peel back the film to expose the pre-cut slots. Insert strap through the front of the windshield, wrap around the bar, insert end of strap through plastic buckle and pull tight. Repeat for other strap.



STEP 8

Remove protective coating from both sides of the windshield.

Installation is complete!

Cleaning Instructions.

Lexan, which is a brand of polycarbonate, is virtually indestructible. But it is also easily scratched. Please read the cleaning recommendations to limit damage to your product.

Never wipe your polycarb back panel with any just any old cloth. We recommend using micro fleece blanket. This is super soft material you can find at Walmart. Any other cloth even micro fiber will leave scratches on the polycarbonate. If you are unsure about the fabric please give us a call at 859-488-7447 ask for Sam.

Never use any abrasive cleaning products on your polycarb. Windex for example is not ok! This will cause the polycarb to develop a haze. Some chemicals may eat through the polycarb. I do not recommend using any kind of soap but if you must please use dish soap only, like dawn. Pour on and spray off, do not wipe!

Do not try to wipe off mud period! Spray mud and debris off with water hose first! If you have access to a leaf blower or air compressor we recommend using them to dry the windshield. If not, gently use a micro fleece blanket to blot the water away and then air dry.

I recommend using a product called MuddTraxx Ceramic Detailer, to apply a coat of wax that will prevent mud and dust from clinging to your windshield. If you are having trouble finding this product online please call Sam at the number listed above.