


JOLLYFLUSH

FLUSH VALVES - CABLE OPERATED JOLLYFLUSH DUAL FLUSH



FLUSHING



Did you know?
 **WIRQUIN**
 invented the cable
 operated flush



WATER SAVING
 Dual flush button.



EASY INSTALLATION
 Suitable for both 1 1/2" & 2" pan outlet.



EXTENDABLE OVERFLOW
 Easy height adjustment even once in situ.



FITS A RANGE OF LID HOLE SIZES
 Suitable for cisterns with cover holes from ø14 mm to ø46 mm.



ADJUSTABLE
 Full flush volumes.



Description	JOLLYFLUSH 1.5"/2" DUAL FLUSH VALVE INC CLOSE COUPLING WASHER AND BOLTED CLOSE COUPLING KIT	JOLLYFLUSH 1.5"/2" SINGLE FLUSH VALVE INC CLOSE COUPLING WASHER AND BOLTED CLOSE COUPLING KIT
Reference	10120446	12050002
EAN code	5017134146400	3375537160860
Packaging	Box	Bag
Multiples / Pack	08 per outer / 160 per pallet	10 per outer / 200 per pallet
Height of cisterns (mm)	300 To 420	300 to 420
Flush rate l/sec	2.2 Wras: 1.85	1.9 Wras: 1.85 (1 1/2") 2.2 Wras: 1.85 (2")
Button diameter	14 to 46 mm	14 to 46 mm
Mechanism outlet (inches)	1.5" or 2"	1.5" or 2"
Water saving	Dual flush	Single flush
Cable length	300 mm	300 mm
Top or front mechanism	Top or front	Top or front
Main characteristics	Adjustable overflow (240 To 270mm).	Ideal for people with limited mobility. Raised button for easy flush. Adjustable overflow (240 to 270mm).