

Revision date 14-Jul-2019

Supersedes Date: 09-Nov-2017

AQUALINE CEMENT/PRIMER Red Revision Number 2

·

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name AQUALINE CEMENT/PRIMER Red

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers.

Uses advised against No information available.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand

Tel: 04-567 5119 Fax: 04-567 5412 **Manufacturer**

Bostik New Zealand Limited 19 Eastern Hutt Road Wingate, Lower Hutt, New Zealand

Tel: 04-567 5119 Fax: 04-567 5412

1.4. Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622

+64 4 917 9888

Poison Centre: 0800 764 766

E-mail address SDS.AP@Bostik.com

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2A (6.4A)
Specific target organ toxicity - Single exposure	Category 3 (f)
Flammable liquids	Category 2 (3.1B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

2.2. Label Elements



Signal word Danger

Hazard statements

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H225 - Highly flammable liquid and vapor

Prevention

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

AQUALINE CEMENT/PRIMER Red

Revision Number 2

Revision date 14-Jul-2019

Supersedes Date: 09-Nov-2017

P271 - Use only outdoors or in a well-ventilated area

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating / lighting/ .? / equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P235 - Keep cool

Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

Skin

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

Fire

P370 + P378 - In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

· May be harmful if swallowed

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical name	CAS No.	Weight-%
Methyl ethyl ketone	78-93-3	40 - <80
Acetone	67-64-1	40 - <80

^{***} Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air.

Skin contact Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician

immediately.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

entry to unnecessary and unprotected personnel

AQUALINE CEMENT/PRIMER Red

Revision Number 2 Supersedes Date: 09-Nov-2017

4.2. Most important symptoms and effects, both acute and delayed

None known. Symptoms

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

4.4. Reference to Other Sections

See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND Reference to other sections

STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

Revision date 14-Jul-2019

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Use CO2, dry chemical, or foam. Move containers from fire area if you can do it without Suitable extinguishing media

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas.

Other information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

For emergency responders Use personal protection recommended in Section 8. Isolate the hazard area and deny

entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Environmental precautions Do not empty into drains, dispose of this material and its container at hazardous or

special waste collection point.

6.3. Methods and material for containment and cleaning up

Methods for containment Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect

> spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations

(see Section 13). Protect from moisture.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of spill for later

disposal.

6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION Reference to other sections

Section 7: HANDLING AND STORAGE

AQUALINE CEMENT/PRIMER Red Revision Number 2

•

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Take precautionary measures against static charges. Use explosion-proof

Revision date 14-Jul-2019

Supersedes Date: 09-Nov-2017

electrical/ventilating/lighting/equipment.

7.2. Conditions for safe storage, including any incompatibilities

General hygiene considerations Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

Storage Conditions Keep only in the original container/package in a cool well-ventilated place. Protect from

moisture. Protect from direct contact with water or excessive moisture.

Incompatible materials Strong acids and bases

7.3. Specific end use(s)

Specific Use(s) Primers.

Other information No information available.

7.4. References to Other Sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND

STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

Chemical name	New Zealand	Australia	European Union
Methyl ethyl ketone	TWA: 150 ppm	150 ppm TWA	TWA: 200 ppm
78-93-3	TWA: 445 mg/m ³	445 mg/m³ TWA	TWA: 600 mg/m ³
	STEL: 300 ppm	300 ppm STEL	STEL: 300 ppm
	STEL: 890 mg/m ³	890 mg/m ³ STEL	STEL: 900 mg/m ³
Acetone	TWA: 500 ppm	500 ppm TWA	TWA: 500 ppm
67-64-1	TWA: 1185 mg/m ³	1185 mg/m³ TWA	TWA: 1210 mg/m ³
	STEL: 1000 ppm	1000 ppm STEL	_
	STEL: 2375 mg/m ³	2375 mg/m ³ STEL	

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL
Methyl ethyl ketone	STEL: 300 ppm	IDLH: 3000 ppm	TWA: 200 ppm
78-93-3	TWA: 200 ppm	TWA: 200 ppm	TWA: 590 mg/m ³
		TWA: 590 mg/m ³	-
		STEL: 300 ppm	
		STEL: 885 mg/m ³	
Acetone	STEL: 500 ppm	IDLH: 2500 ppm	TWA: 1000 ppm
67-64-1	TWA: 250 ppm	TWA: 250 ppm	TWA: 2400 mg/m ³
		TWA: 590 mg/m ³	_

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available

(PNEC)

OTHER INFORMATION No information available

AQUALINE CEMENT/PRIMER Red

Revision Number 2 Supersedes Date: 09-Nov-2017

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

PPE - Personal Protection Equipment

Respiratory protection

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing. No special technical protective measures are

necessary under normal conditions.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers. No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask,

Revision date 14-Jul-2019

or for short periods of work, a combination of professional filter is recommended.

General hygiene considerationsDo not eat, drink or smoke when using this product. Wash hands thoroughly after

handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and

wash before reuse.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Paste Liquid Solid

Color Red Odor Solvent

Odor threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point
No data available

Boiling point / boiling range 56 °C Flash point -17 °C

Evaporation rateFlammability (solid, gas)
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive 9.7

limits

Lower flammability or explosive 1.5

limits

Vapor pressure
Vapor density
Relative density
Water solubility
Solubility(ies)
No data available
Soluble in water
No data available
No data available
No data available
No data available

Autoignition temperature 550 °C

Decomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosityNo data availableExplosive propertiesNo information availableOxidizing propertiesNo information available

9.2. Other information

Softening PointNo information availableMolecular weightNo information availableSolvent content (%)No information available

Solid content (%) = 0

Density 0.8 g/cm³

Bulk density No information available

VOC Content (%) > 300 g/L

AQUALINE CEMENT/PRIMER Red

Revision Number 2 Supersedes Date: 09-Nov-2017

Revision date 14-Jul-2019

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and flames. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids and bases.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Acute Toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied

information.

InhalationNo data available.Eye contactNo data available.Skin contactNo data available.IngestionNo data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
78-93-3			
Acetone	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
67-64-1			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available. Serious eye damage/eye irritation No information available. Sensitization No information available. No information available. Germ cell mutagenicity Reproductive toxicity No information available. STOT - single exposure No information available. No information available. STOT - repeated exposure Target organ effects liver. Eves. retina. Skin. **Aspiration hazard** No information available. Carcinogenicity No information available.

AQUALINE CEMENT/PRIMER Red

Revision Number 2 Supersedes Date: 09-Nov-2017

Revision date 14-Jul-2019

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product Information

None known.

Component Information

Data obtained on the component(s) include

Chemical name	Algae/aquatic plants	Fish	Crustacea
Methyl ethyl ketone	EC50=1972 mg/l	LC50: 3130 - 3320mg/L (96h,	EC50 48 h > 308 mg/L (Daphnia
78-93-3	(Pseudokirchneriella subcapitata)	Pimephales promelas)	magna)
Acetone	-	LC50 96 h 4.74 - 6.33 mL/L	EC50 48 h 10294 - 17704 mg/L
67-64-1		(Oncorhynchus mykiss)	(Daphnia magna Static)

12.2. Persistence and degradability

No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready	28 days	biodegradation	98 % Readily biodegradable
Biodegradability: Closed Bottle Test	-	-	
(TG 301 D)			

12.3. Bioaccumulative potential

No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Methyl ethyl ketone	0.3	-
78-93-3		
Acetone	-0.24	0.69
67-64-1		

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Methyl ethyl ketone	The substance is not PBT / vPvB
78-93-3	
Acetone	The substance is not PBT / vPvB
67-64-1	

12.6. Other adverse effects

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

AQUALINE CEMENT/PRIMER Red

Revision Number 2 Supersedes Date: 09-Nov-2017

Revision date 14-Jul-2019

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

IMDG

UN number UN1993

Proper Shipping Name Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers))

Transport hazard class(es)

Packing group

Marine Pollutant

EmS-No.

Special Provisions

Limited Quantity (LQ)

3

Np
F-E, S-E
274

Limited Quantity (LQ)

1

Description UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers)), 3,

II, (-17°C c.c.)

IATA

UN number UN1993

Proper Shipping Name Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers))

Transport hazard class(es) 3
Packing group II
ERG Code 3H
Limited Quantity (LQ) 1 L
Special Provisions A3

Description UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers)), 3,

Ш

ADR

UN Number UN1993

Proper Shipping Name Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers))

Transport hazard class(es) 3 Labels 3 Packing Group ||

Description UN1993, Flammable liquid, n.o.s. (Methyl ethyl ketone, Xylenes (o-, m-, p- isomers)), 3,

II, (D/E)

Limited Quantity (LQ) 1 L

Special Provisions 274, 601, 640C

Classification Code F1
Tunnel Restriction Code (D/E)

Section 15: REGULATORY INFORMATION

National Regulations

ERMA Group HSR002662

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 14-Jul-2019
Revision note Not applicable.

Page 8/9

AQUALINE CEMENT/PRIMER Red Revision Number 2

Training Advice

Provide adequate information, instruction, and training for operator

Revision date 14-Jul-2019 **Supersedes Date:** 09-Nov-2017

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet