

仕 様 書

(Specifications)

項目 (Items)	内容 (Specification)
名称 (Type)	気相用張力式高圧ホース (逆流・過流防止弁付き) A high-pressure hose having a gas discharge protection valve (tension triggered type) (with excess flow / non return valve)
型式 (Model)	T I H - 6 - 8 W
使用圧力 (Working Pressure Range)	1. 5 6 MP a 以下 (or less)
作動荷重 (Working load)	2 0 ~ 1 5 0 N (1.0MPa 加圧時) (Add 1.0MPa Pressure)
気密 (Gas Tight Pressure Test)	1. 8 0 MP a
耐圧 (Pressure Test)	2. 7 0 MP a
入口接続 (Inlet Connection)	POL継手 (手締め) (POL Joint (hand Start))
出口接続 (Outlet Connection)	R 1 / 4
使用温度範囲 (Temperature Capabilities)	- 2 5 ~ 6 0 °C
口径(Bore)	φ 6
全長 (Overall Length)	約(Approx) 8 1 7 mm
質量 (Product Weight)	約(Approx) 0. 3 5 kg
備考 (Note)	逆流・過流防止弁付き (with excess flow / non return valve)

Date : 3 March, 2015

I·T·O株式会社
[**I·T·O Corporation**]

東大阪市箱殿町 1 0 番 4 号
(10-4 Hakodono-cho, Higashi-Osaka City, Japan)
TEL:072-981-3781 FAX:072-987-6590