



BRONZE

Technical Data Sheet

ThermaSmart[®]PRO Tube

Thermal Insulation by Thermaflex[®]

ThermaSmart[®]PRO, a fully recyclable thermal sheet insulation product made of direct extruded, closed-cell high quality polyolefine foam.

Benefit from:

- Condensation free system for life-time installed by qualified insulator
- Consistent performance - Damage free, robust insulation material
- Safety - Excellent fire and smoke behavior
- Fast fabrication of fitting insulation – Welding technique up to ID42mm
- Gain point for Green building program - Cradle to Cradle Certified[™] Bronze, EPD, RoHS



Applications

- All HVAC-R systems: Heating, Cooling, Air conditioning and Refrigeration

Technical Properties

Properties	Units SI	Values	Testing method
Physical properties			
Dimensional tolerances	-	Coherent	EN 14313
Density	kg/m ³	18 - 40	-
Structure	-	Fine, closed-cells	-
Color	-	Anthracite	-
Thermal properties			
Service temperature range	°C	-80 to +95	-
Maximum service temperature	°C	+95	EN 14707
Thermal conductivity (λ)	W/m.K	0.035 @ 10°C 0.038 @ 40°C	EN ISO 8497
Fire properties			
SBI classification	-	BL, s1, d0	EN 13501-1
British standard	-	Class 1	BS 476 Part 7
British standard	-	Class 0	BS 476 Part 6
Flammability standard	-	HF-1	UL94
Smoke & Toxicity	-	Pass	IMO Resolution MSC 307(88) annex 1 part 5
Water resistance properties			
Water vapor diffusion	μ	≥ 10,000	EN 13469
Water absorption	kg/m ²	0.01	EN 13472

Availability

- Standard product length is 2m in carton boxes
- In coils up to Ø28 mm and wall thickness 6-13 mm
- Product versions: non-slit, pre-slit, Self-Adhesive
- Pre-fabricated parts

Carrier Pipe Ø max. [mm]	Tube Insulation Ø [mm]	Carrier Pipe Ø max. [mm]	Tube Insulation Ø [mm]
6	7.0-8.5	40	42.0-43.5
8	9.0-10.5	42	44.0-46.0
10	11.0-12.5	48	50.0-52.0
12	13.0-14.5	50	52.0-54.0
15	16.0-17.5	54	56.0-58.0
18	19.0-20.5	60	62.0-64.0
20	21.0-22.5	63	65.0 - 67.5
22	23.0-24.5	76	77.0 - 79.5
25	26.0-27.5	89	91.5 - 94.5
28	29.0-30.5	102	105.0 - 108.0
32	33.0-35.0	108	111.5 - 114.0
35	36.0-38.0	114	117.0 - 120.0

Insulation Wall thickness [mm]
6
9
13
19
25
30

V1.0, 2018-03-22



Thermaflex International Holding b.v.
Veerweg 1, 5154 NS Waalwijk The Netherlands
www.thermaflex.com

Disclaimer

All recommendations and information provided on this data sheet are based on our knowledge and experience. Product specifications are intended as guidelines. Since conditions of service are beyond our control, users must satisfy themselves that products are suitable for the intended use. No guarantee or warranty is given or implied or that any use of products will not infringe rights belonging to other parties. We reserve the right to change product design and properties without notification.