## CABLE MANAGEMENT SYSTEMS



www.cablecovers.co.nz

| Product Specifications:                                | Style<br>No.  | Power cables                              | Applications/Cable type  |
|--|---------------|---|--|
| 70mm   | CP2           | 1-2<br>Power<br>Cables                    | Extruded rubber design     Ideal for offices, boardrooms and computer rooms     Available cut to length, minimum order 2 metres.   |
| 17mm 10mm 20mm   | CP2/Y         | 1-2<br>Power<br>Cables                    | Tough PVC design in yellow Ideal for offices, boardrooms and computer rooms Available cut to length, minimum order 2 metres.   |
| 19mm 32mm x 13mm 19mm 98mm                             | CP2BY         | 4-5<br>Power<br>Cables                    | Economy extruded rubber design     Ribbed surface and yellow stripe down either side     Two useable channels     Ideal for temporary and permanent applications   |
| 90mm 20mm  | CP3           | 3-4<br>Power<br>Cables                    | Extruded rubber design     Ideal for offices, boardrooms and computer rooms     Available cut to length, minimum order 2 metres.   |
| — 23mm——————————————————————————————————               | CP4           | 4-5<br>Power<br>Cables<br>and/or<br>Hoses | Extruded rubber design     Ideal for offices, warehouses and factories     Comfortably protects power cables, 3 phase cables, compressed airlines and water hoses     Available cut to length, minimum order 2 metres. |
| -20mm- 30mm  | CP5           | 4-8 Power Cables and/or Hoses             | Extruded rubber design     Ideal for warehouse, factory and external applications     Comfortably fits two 3-phase power cables or two compressed airlines     Available cut to length, minimum order 2 metres.        |
| 12mm 20mm 130mm  | CP14          | 4-5<br>Power<br>Cables                    | Flexible PVC dropover cable protector - ribbed profile     Available in yellow or black, 1 metre inter-locking lengths     Heavier product for good grip     Ideal for office and pedestrian applications              |
| 13mm 20mm 13mm   | CP12          | 4-5<br>Power<br>Cables                    | Polyurethane dropover cable protector Anti-slip checker tread plate surface Ideal for office and pedestrian applications Available in Yellow or Black, 1 metre inter-locking lengths, minimum order 2 lengths.         |
| 27mm 27mm 35mm   | CP13          | 8-10<br>Power<br>Cables                   | Polyurethane dropover cable protector Anti-slip checker tread plate surface Ideal for office and pedestrian applications Available in Yellow or Black, 1 metre inter-locking lengths, minimum order 2 lengths.         |
| 35mm 35mm 50mm 300mm                                   | CP<br>DROP2   | Power<br>Cables<br>and/or<br>Hoses        | Two Channel Heavy Duty Dropover cable protector Ideal for warehouse and industrial applications Simply dropover top of cables Available in 1 metre inter-locking lengths   |
| 16mm 6.4mm 11mm  | CPS/SM        | 2<br>Power<br>Cables                      | <ul> <li>Aailable per metre or a discounted 9 metre roll</li> <li>Standard flexible extruded rubber design</li> <li>Ribbed surface with two useable channels</li> </ul>  |
| 19mm 9.5mm 16mm  | CPS/MD        | 3<br>Power<br>Cables                      | Aailable per metre or a discounted 9 metre roll     Standard flexible extruded rubber design     Ribbed surface with two useable channels     Ideal for permanent applications   |
| Industrial grade velcrose securing system  60mm  105mm | SAF/1.8       | 3<br>Power<br>Cables                      | Available in 1.8 metre or 9 metre lengths in various colours.     Secures cables to looped carpet     Quality Industrial grade nylon fabric     Can be cut to any length without unravelling.                          |
| Nylon fabric Velcrose securing system 55mm 97mm        | Quick<br>Fit™ | 3<br>Power<br>Cables                      | Economy fabric cable covers in 1.0 metre lengths in Black, Yellow or Light Grey     Easy to set and remove to carpet without damage to carpet Ideal for temporary or permanent applications                            |
| Channel Height 10mm 22mm 19m                           | CPDuct        | 2<br>Power<br>Cables                      | Comes in 1.9 metre lengths. Supplied with double sided tape on the base Suitable for indoor use Remove the top cover, lay your cables in the channel and click the cover back into place.                              |

## CABLE MANAGEMENT SYSTEMS



www.cablecovers.co.nz

| Product Specifications:                      | Style<br>No.  | Power                                       | Applications/Cable type  |
|--|---------------|---|--|
| 19mm 9.5mm 19mm 76mm                         | CPSIDESM      | 1-2<br>Power<br>Cables                      | Available in yellow/black or black 1 metre inter-locking lengths     Sections clip together to create desired length     Flexible design allows cable protector to go around corner     14 tonne loading capacity per axle.  |
| 35mm 19mm 76mm 248mm                         | CPSIDEMD      | 18 Power Cables and/or Hoses                | Available in 840mm lengths which include end caps (Without the end caps the length is 750mm)     Colours are black/yellow or black     Sections clip together to create desired length     Flexible design allows cable protector to go around corner     6 tonne loading capacity per axle. |
| 54mm 38mm 76mm 346mm                         | CPSIDELG      | 38 Power Cables and/or Hoses                | Available in black/yellow 860mm lengths which include end caps (Without the end caps the length is 750mm)     Sections clip together to create desired length     Flexible design allows cable protector to go around corner     6 tonne loading capacity per axle.                          |
| 15mm (W) x<br>10mm (H)<br>80mm               | PYTHON<br>/SM | 2<br>Power<br>Cables                        | Flexible, yellow and black cable cover     900mm length can be customised to suit your application     Can be bent to approx. 2 metre circumference circle     Round grips on underside that prevent slipping  |
| 27mm (W) x<br>20mm (H)<br>150mm              | PYTHON<br>/LG | 4<br>Power<br>Cables                        | Flexible, durable yellow and black cable cover     900mm length can be customised to suit your application     Can be bent to approx. 2 metre circumference circle     Round grips on underside that prevent slipping  |
| 320mm  | CP1CH         | Multiple<br>Power<br>Cables<br>and<br>Hoses | Suitable for indoor and outdoor use Ideal for temporary and permanent applications Suitable for high volume pedestrian traffic, light to medium weight vehicle applications Available in 1 metre inter-locking lengths.  |
| 30mm 30mm Channel Height 35mm 245mm          | CP2CH         | Multiple<br>Power<br>Cables<br>and<br>Hoses | Suitable for indoor and outdoor use     Ideal for temporary and permanent applications     Suitable for high volume pedestrian traffic, light to medium weight vehicle applications     Available in 900mm inter-locking lengths.  |
| Channel Width 60mm Channel Height 55mm 75mm  | СРЗСН         | Multiple<br>Power<br>Cables<br>and<br>Hoses | Large channels to suit a variety of cable and hose sizes Suitable for indoor and outdoor use Ideal for temporary and permanent applications Suitable for low to medium volume, light to medium weight vehicle applications Available in 900mm metre inter-locking lengths.                   |
| Channel Width 38mm Channel Height 30mm 500mm | CP5CH         | Multiple<br>Power<br>Cables<br>and<br>Hoses | Modular rubber design with plastic lid     Large channels to suit a variety of cable and hose sizes     Suitable for low to medium volume, light to medium weight vehicle applications     Available in 900mm metre inter-locking lengths.   |
| 22mm   | ESH300        | 8-10 Power cables and Hoses                 | Speed hump style cable protector, reduces vehicle speed in low traffic environments and offers a cable protection     Two channels to protect cables and hoses     Available in 1.83 metre lengths, fast and easy to install.  |
| 95mm 70mm 85mm                               | CR850         | Multiple<br>Hoses<br>and<br>Cables          | 850mm long in direction of travel and 300mm wide per module. Pack of 4 modules will total 1.2 metres wide     Weight rating = 10 tonne per axle     Provide safe passage for pedestrians and vehicles     2 large channels to suit a variety of cable and hose sizes                         |
| Channel Height 130mm 150mm 136mm             | CR1010        | Multiple<br>Hoses<br>and<br>Cables          | 1010mm long in direction of travel and 300mm wide per module. Pack of 4 modules will total 1.2 metres wide     Weight rating = 20 tonne per axle     Provide safe passage for pedestrians and vehicles     2 large channels to suit a variety of cable and hose sizes                        |

