

QUICK STARTUP GUIDE

DOMOTING CUSTOMS - GARAGE DOOR ALERT KIT

INTRODUCTION

This product is designed for customers using the *Insteon Hub* with *Insteon I/O Linc Garage Door Kit* that would like to get an alert if the garage door has been left open for a configurable amount of time.

ITEMS REQUIRED (NOT INCLUDED)


A second Insteon IO Linc 2450.

HOW IT WORKS

The Insteon Hub has the ability to send instant alerts if the garage door is opened or closed. However, there is no alert to let you know if you left your garage door open for an extended period of time. The *Domotinc Customs - Garage Door Alert Kit* is designed to alert you if your garage door has been left open by



getting the "open" signal from your current *Insteon I/O Linc Garage Door Control and Status Kit,* then wait a configurable amount of time and send that same "open" signal to a second Insteon 2450, which will then alert you through the Insteon app. This makes it a very simple and transparent integration with your Insteon setup.



TIMER CONFIGURATION

The timer can be set from 5 minutes to 75 minutes, in 5 minutes increments. An addition will be performed if multiple DIP switches are set to the ON position. For instance, if you set the 10 minutes and 20 minutes switches to ON, the delay before you get an alert for the garage door been left open will be 30 minutes (10+20). If all switches are OFF, this enable the demo/test mode which has a delay of 30 seconds. If all the switches are ON like on the picture, that would equal 75 minutes (5+10+20+40).



CONNECTIONS

Connecting the *Domotinc Customs - Garage Door Alert Kit* is very simple.

This device is designed to be totally transparent to Insteon. It does not require to be connected to your WiFi nor to be added as an Insteon device. It also does not require external power as it draws power from both Insteon 2450.

Connection are already made from factory, info provided as reference Ground (coper wire) -5volt (both white wires) -Alert sensor (yellow wire of the 90 degrees audio connector) Sensor from Insteon Garage Door Kit (yellow wire of straight audio connector) Set alert delay (minutes) using DIP switches. Connect the 90 degrees audio jack in a new Insteon 2450. Connect the straight audio jack in your actual Insteon I/O Linc Garage Door Control and Status Kit. CONFIGURATION IN INSTEON HUB Please refer to Insteon documentation to add your Insteon 2450 to your Insteon Hub. Give it a friendly name like "garage alert". Set "Monitor and Display Sensor Status" to ON.

Go into Alerts.

Enable "Off Alert" and click "Message & recipients".

Set "off when close" under sensor mode

- Enable "Push Notification" to receive alert on your mobile when the garage door has been left open.
- Enter your email address, a subject and a message in the line of "you forgot the garage door".

DISCLAMER

It is your responsibility to ensure you closed your garage door. You should not solely rely on this device to ensure your garage door is closed. Domotinc and Domotinc-Customs cannot be held responsible in the event an alert is not sent as different circumstances may prevent you from receiving the alert, including, but not limited to, power outrage, your home internet service provider failure, instead network interferences, bad cell phone coverage... Always ensure you closed your garage door before leaving your house.