





Conforms to OSHA HCS 2012 (29 CFR 1910.1200) SAFETY DATA SHEET

PETRON PLUSTM THE ENGINE CONDITIONER

Part No. 12121-12oz, 12121-1g, 12121-5g, 12121-54g, 12121-275g, 12121-330-g

SECTION 1. PREPARATION INFORMATION

Date : March 18, 2015

GHS Product identifier: Petron Plus The Engine Conditioner

ID #: 12121-12oz, 12121-1g, 12121-5g, 12121-54g, 12121-275g

12121-330g

Code : Lubricant and Supplement.

CAS Number : Not Applicable for mixtures.

Synonyms : None.

Generic Chemical

Name : Mixture.

Applications include

the Following : Gasoline Engines and Propane Engines Oil Supplement, 12oz. to 4 to

6 quarts of engine oil.

Do Not use in diesel engines.

Manufactured by : PETRON PLUS GLOBAL, INC.

P. O. BOX 1906 208 East 2nd

HUTCHINSON, KS. 67504-1906 USA

Contact Information: 620/663-1800 - Phone

info@petronplus7.com

Emergency Health and Safety Number: CHEMTREC: 800.424.9300 (24 Hours)

International: +1-703-527-3887



Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 2 of 17

SECTION 2. HAZARDOUS IDENTIFICATION

Hazard Classification

Unknown toxicity

Acute toxicity, oral : 0.03 %
Acute toxicity, dermal : 0.03 %
Acute toxicity, inhalation, vapor : 7.84 %
Acute toxicity, Inhalation, dust : 7.84 %

Health hazards : Aspiration hazard Category 1

Reproductive toxicity Effects on or via lactation

Acute toxicity (Oral) Category 4
Specific Target Organ Toxicity Category 2

Repeated Exposure

Environmental hazards : Hazardous to the aquatic Category 3

environment, acute hazard

Hazardous to the aquatic Category 1

environment, long-term hazard

OSHA Defined hazards : Not classified.

Classification of the : Not Classified. substance or mixture

Label elements :





Signal Word : Danger.

Hazard statement : May be fatal if swallowed and enter airways.

May cause harm to breast-fed children.

Harmful to aquatic life.

Very toxic to aquatic life with long lasting effects.

Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention Do not breathe dust/fume/gas/mist/vapors/spray.

Do no handle until all safety precautions have been read and understood.

Avoid contact during pregnancy/while nursing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid contact with eyes.

Avoid release to the environment.

Observe good industrial hygiene practices.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 3 of 17

SECTION 2. HAZARDOUS IDENTIFICATION, Cont.

Precautionary statements, Cont.

Response : IF SWALLOWED: Call a POISON CENTER or doctor/physician. Do NOT induce

vomiting. If exposed or concerned: Get medical advice/attention.

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rising.

Storage Store in well-ventilated place. Keep container tightly closed.

Disposal : Disposal of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazards not otherwise

classified : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture : Mixture

Other means of : Not applicable.

identification

CAS Number/other identifiers

CAS number : Not applicable.

CHEMICAL NAME	CAS # or		% RANGE
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		20 - 50 %
Proprietary Ingredients	Mixture		10 - 40%
Mineral Oil Alkaryl amine Zinc alkyldithiophosphate Mixture	Not determined Confidential Confidential	}	3 - 20 % 0.7 - 2 % } 0.7 - 2 % } 5 - 20 %
Zinc alkyldithiophosphate Diphenylamine	84605-29-8 122-39-4	}	}
Highly refined mineral oil (C15-C50 01154100-5165P	Mixture Trade secret	} }	1 - 10 %Mixture 0.1 - 1 %
Highly refined mineral oil (C15-C50 Calcium branched chain Alkylated phenol sulfide	Mixture Trade secret	}	1 - 10 % 1 - 5% Mixture
Fatty Acid, Tall-Oil, Esters with Neopentyl Glycol	68002-76-6		1 - 5 %
Alkaryl amine Diphenylamine	Confidential 122-39-4		0.3 - 0.8 Mixture 0.005 - 0.05%
Mineral Oil	64742-53-6		0.04 - 0.06

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 4 of 17

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS, Cont.

The mineral oil contained in this material may be described by one or more of the following CAS Nos.: 64742-54-7, 64742-65-0, 64742-55-8, and 64742-56-9.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4. FIRST AID MEASURES

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water (for 30 minutes), occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Get medical

attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Launder contaminated clothing before reuse. Get medical attention if

symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do NOT INDUCE VOMITING unless directed to do so by medical personnel. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye Contact : Direct contact with eyes may cause temporary irritation.

Inhalation : May cause respiratory irritation or other pulmonary effects following prolonged or

repeated inhalation of mist at airborne levels above recommended mineral oil

exposure limit.

Skin contact : If material is heated, thermal burns may result from skin contact.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye Contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Note to physician : Acute aspirations of large amounts of oil-laden material may produce a serious

aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current

workplace exposure limits is unlikely to cause pulmonary abnormalities.

Special treatment : No special treatment.

Protection of first-aiders: No special protection is needed.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 5 of 17

SECTION 5. FIRE-FIGHTING MEASURES

NFPA 704 Hazard Class

Health: 1 Flammability: 1 **Instability: 0**



0 (Minimal)

1 (Slight)

2 (Moderate)

3 (Serious)

4 (Severe)

Extinguishing media

Suitable extinguishing Water fog, Foam, Dry chemical, Carbon dioxide (CO2).

media

Unsuitable extinguishing: Do not use water jet as an extinguisher, as this will spread the fire.

media

Extinguishing media, Cont.

Specific hazards arising: During fire, gases hazardous to health may be formed.

from the chemical

Hazardous thermal Decomposition products may include the following materials: carbon dioxide,

decomposition products carbon monoxide, nitrogen oxides, sulfur oxides, and other products of incomplete

combustion.

Special protective

Self-contained breathing apparatus and full protective clothing must be worn in actions for fire-fighters

case of fire.

Special protective

equipment for fire-fighters apparatus (SCBA) with full face-piece operated in positive pressure mode. Move

Fire-fighters should wear appropriate equipment and self-contained breathing

containers from fire area if you can do so without risk.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

responders

Put on appropriate personal protective equipment.

For emergency

If specialized clothing is required to deal with the spillage, take note of any

information in Section 8 on the suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 6 of 17

SECTION 6. ACCIDENTAL RELEASE MEASURES, Cont.

Personal precautions, protective equipment and emergency procedures, Cont.

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform the relevant authorities if the product has caused

environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

SPILL PROCEDURES: For Small Spills: ventilate area, wear chemical splash goggles. Wear rubber

boots. Prevent entry into sewers, waterways. Pick up free liquid for recycle or

disposal. Absorb small amount on inert material for disposal.

SPILL PROCEDURES: For Large Spills: Personal Protective Equipment must be worn. Avoid skin

> contact. Use skin protection. See Personal Protection Section for additional PPE recommendations. Take precautions to avoid release to the environment. Ventilate area if spilled in confined space or other poorly ventilated area. Prevent entry into sewer and waterway, dispose of in accordance with all federal, state and local environmental regulations. Pick-up free liquid for recycle and/or disposal.

Residual liquid can be absorbed on inert material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section *). Avoid contact

with used product. Do not reuse container.

Advice on general Eating, drinking and smoking should be prohibited in area where this material is

handled, stored and processed. Workers should wash hands and face before eating,

drinking and smoking. See also Section 8 for additional information on hygiene

Store in accordance with local regulations. Store in original container protected

measures.

Conditions for safe storage,:

occupational hygiene

including any

from direct sunlight in dry, cool and well-ventilated area, away from incompatible incompatibilities materials (see Section 10) and food and drink. Keep container tightly closed and

sealed until ready for use. Containers that have been opened must be carefully resealed and keep upright to prevent leaking. Do not store in unlabeled containers.

Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits

Under conditions which may generate mists, the following additional exposure limits are recommended: ACGIH TLV TWA: 5 mg/m^3 ; STEL: 10 mg/m^3 .

Appropriate engineering

controls

Good general ventilation should be sufficient to control worker exposure to

airborne contaminants.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 7 of 17

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION, Cont.

Control parameters, Cont.

Environmental exposure Emissions from ventilation or work process equipment should be checked to ensure

they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working period.

Ensure that eyewash stations and safety showers are close to the workstation

location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk

> assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless

the assessment indicates a higher degree of protection: safety glasses with

side-shields.

Skin protection

controls

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a skin risk assent indicates

this is necessary.

Body protection Personal protective equipment for the body should selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection Use a properly fitted, air-purifying or supplied air respirator complying with an

> approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the

product and the safe working limits of the selected respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Brown.

Appearance

Physical state Liquid. Color

Odor Mild hydrocarbon.

Odor threshold Not available.

pH Not available.

Pour point <-10°F (-23.3°C).

Boiling point Not available.

Flash point >310°F (154°C). [Cleveland]

Evaporation rate Not available.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 8 of 17

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES, Cont.

Appearance, Cont.

Flammability (Solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure

Vapor density

Relative density

Solubility

Partition coefficient: n
Not available.

Not available.

Not available.

octanol/water

Auto-ignition temperature:

Decomposition temperature:

Viscosity

Not available.

Not available.

Specific Gravity: 1.026 @ 60 degrees F.

Density : 8.545 (lbs/gal).

SECTION 10. STABILITY AND REACTIVITY

ReactivityNo specific test data related to reactivity available for this product or its

ingredients.

Chemical stability : This product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

Conditions to avoid : No specific data.

Incompatible material: Reactive or incompatible with the following materials: Oxidizing materials.

Thermal Decomposition : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye : Weak to moderate eye irritant. Based on data from components or similar

materials.

Skin : Cause mild skin irritation. Based on data from components or similar materials

Inhalation : Not expected to be a problem as long as exposure limits are not exceeded.

Ingestion : Expected to be a low ingestion hazard. Based on data from components or similar

materials.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 9 of 17

SECTION 11. TOXICOLOGICAL INFORMATION, Cont.

Information on toxicological effects

Acute toxicity

Oral

Component : ATEmix > 10,000 mg/kg

Dermal

Component : Not classified for acute toxicity based on available data.

Inhalation

Component : Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation

Component Prolonged or repeated skin contact as from clothing wet with material may cause

dermatitis. Symptoms may include redness, edema, drying, and cracking of the

skin.

Remarks: Causes mild skin irritation.

Serious Eye Damage/Eye Irritation

Component : Direct contact with eyes may cause temporary irritation.

Respiratory sensitization

Component : No data available.

Skin sensitization

Components

Mineral oil : Classification: Not a skin sensitizer. (Read across) Not a skin sensitizer.

Zinc alkyldithiophosphate: Classification: Not a skin sensitizer. (Literature) Not a skin sensitizer.

Zinc alkyldithiophosphate: Classification: Not a skin sensitizer. (Literature).

Diphenylamine: Classification: Not a skin sensitizer. (Literature).

Specific Target Organ Toxicity - Single Exposure

Components

Mineral oil : If material is misted or if vapors are generated from heating, exposure may cause

irritation of mucous membranes and the upper respiratory tract.

Diphenylamine Exposure to a high concentration of vapors or mist may be irritating.

Aspiration Hazard

Components

Mineral oil : Material can be aspirated into the lungs during the act of swallowing or vomiting.

This could result in severe injury to the lungs and death.

Other effects

Components

Diphenylamine : Kidney Blood Liver.

Part No. 12121-12oz, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 10 of 17

SECTION 11. TOXICOLOGICAL INFORMATION, Cont.

Chronic Effects

Carcinogenicity

Components : Not expected to cause cancer. This product contains mineral oils which are severely

refined and not considered carcinogenic. All the oils in this product have been

demonstrated to contain less than 3 % extractables by IP-346 test.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified.

US. National Toxicology Program (NTP) Report on Carcinogenic:

No carcinogenic components identified.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified.

Germ Cell Mutagenicity:

Alkaryl amine : This material has not exhibited mutagenic or genotoxic potential in laboratory

tests.

Diphenylamine : The Ames Salmonella test for mutagenicity was negative for this product. The

mouse micronucleus and the ray hepatocyte UDS tests for genotoxicity were

negative for diphenylamine.

Reproductive Toxicity

Diphenylamine : There are conflicting reports in the literature concerning the teratogenicity of

diphenylamine. However, because the predominant route of exposure was oral (via gavage or diet) and relatively high dose levels were administered in the studies where positive effects were observed, it would not seem to present a workplace

hazard.

Specific Target Organ Toxicity - Repeated Exposure

Diphenylamine : A two year feeding study in rats and dogs of diphenylamine demonstrated liver,

kidney and blood cell damage. The effect was observed at levels as low as 100 ppm. A five month feeding study in rats of 1% diphenylamine produced renal cystic disease. A dose-dependent increase in Heinz body formation was evident during a

12 week study of 5 to 1000 ppm. The no effect level was at 10 ppm.

Dermal: Target Organ(s): Liver, Kidney
Inhalation: Target Organ(s): Kidney, Liver

Oral Target Organ(s): Liver, Kidney

PETRON PLUSTM THE ENGINE CONDITIONER SDS

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 P. 11 of 17

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Fish

Mineral Oil LC 50 (Fathead Minnow, 4 d): > 100 mg/l

Alkaryl amine LC 50 (Zebra Fish, 4 d): > 100 mg/l

Zinc alkyldithiophosphate : LC 50 (Rainbow Trout, 4 Days): 4.5 mg/l

LC 50 (Rainbow Trout, 4 Days): 1.8 mg/l

LC 50 (Sheepshead Minnow, 4 Days): 46 mg/l

Zinc alkyldithiophosphate : LC 50 (Rainbow Trout, 4 Days): 4.5 mg/l

> LC 50 (Sheepshead Minnow, 4 Days): 46 mg/l LC 50 (Rainbow Trout, 4 Days): 1.8 mg/l

Diphenylamine LC 50 (Not reported, 2 d): 2.2 mg/l

Proprietary Ingredients

Mixture LC50 Rainbow trout, donaldson trout: 0.06 - 0.08 mg/l, 96 hours

(Oncorhynchus mykiss)

LC50 Bleak (Alburnus alburmus): > 10000 mg/l, 96 hours

> 5000 mg/l, 96 hours

Bluegill (Lepomis macrochirus): > 300 mg/l, 24 hours

> 300 mg/l, 96 hours > 10.7 mg/l, 24 hours> 10.7 mg/l, 96 hours > 10 mg/l, 24 hours > 10 mg/l, 96 hours

> 0.1 mg/l, 24 hours> 0.1 mg/l, 96 hours

Channel catfish (Ictalurus punctatus

> 300 mg/l, 24 hours > 300 mg/l, 96 hours> 10 mg/l, 24 hours

> 10 mg/l, 96 hours > 0.1 mg/l, 24 hours

> 0.1 mg/l, 96 hours

Fathead minnow (Pimephales promelas

> 100 mg/l, 24 hours

> 100 mg/l, 96 hours

Rainbow trout, donaldson trout > 300 mg/l, 24 hours

(Oncorhynchus mykiss) > 300 mg/l, 96 hours

94.5 - 271 mg/l, 24 h

> 10 mg/l, 24 hours> 0.1 mg/l, 24 hours > 0.1 mg/l, 96 hours

0.06 - 0.08 mg/l, 96 h 0.06 - 0.08 mg/l, 96 h > 0.0109 mg/l, 24 hours

> 0.0109 mg/l, 96 hours

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 12 of 17

SECTION 12.

ECOLOGICAL INFORMATION, Cont.

Ecotoxicity, Cont. Fish, Cont.

Yellow perch (Perca flavescens) > 10.7 mg/l, 24 hours

> 10.7 mg/l, 96 hours

> 10 mg/l, 24 hours

> 10 mg/l, 96 hours

Aquatic Invertebrates

Mineral Oil : LC 50 (Water Flea (Daphnia magna), 2 d): > 10,000 mg/l

LC 50 (Water Flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water Flea (Daphnia magna), 21 d): > 10 mg/l

Alkaryl amine LC 50 (Water Flea (Daphnia magna), 2 d): > 100 mg/l

Zinc alkyldithiophosphate : LC 50 (Water Flea (Daphnia magna), 2 d): > 23 mg/l

NOEC (Water Flea (Daphnia magna), 2 d): > 10 mg/l LC 50 (Water Flea (Daphnia magna), 21 d): > 0.4 mg/l

Zinc alkyldithiophosphate : LC 50 (Water Flea (Daphnia magna), 2 d): > 23 mg/l

NOEC (Water Flea (Daphnia magna), 2 d): > 10 mg/l LC 50 (Water Flea (Daphnia magna), 21 d): > 0.8 mg/l NOEC (Water Flea (Daphnia magna), 21 d): > 0.4 mg/l

Diphenylamine LC 50 (Water Flea (Daphnia magna), 2 d): > 0.31 mg/l

Toxicity to Aquatic Plants

Mineral Oil : LC 50 (Green algae (Scenedesmus quadricauda), 3 d): > 100 mg/l

Alkaryl amine LC 50 (Green algae (Scenedesmus quadricauda), 3 d): > 600 mg/l

Zinc alkyldithiophosphate : LC 50 (Green algae (Scenedesmus quadricauda), 3 d): > 21 mg/l

Zinc alkyldithiophosphate : LC 50 (Green algae (Scenedesmus quadricauda), 3 d): > 21 mg/l

NOEC (Green algae (Scenedesmus quadricauda), 3 d): > 10 mg/l

Diphenylamine LC 50 (Green algae (Scenedesmus quadricauda), 3 d): > 1.51 mg/l

Toxicity to soil dwelling organisms

No data available.

Sediment Toxicity

No data available.

Toxicity to Terrestrial Plants

No data available.

Toxicity to Above-Ground Organisms

No data available.

^{*}Estimates for product may be based on additional component data not shown.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 13 of 17

SECTION 12. ECOLOGICAL INFORMATION, Cont.

Toxicity to Microorganisms

Zinc alkyldithiophosphate : LC 50 (Sludge, 0.1 d): > 10,000 mg/l

Persistence and Degradability

Biodegradation

Mineral Oil : OECD TG 301 B, 31 %, 28 d, Not readily degradable.

Alkaryl amine CECD TG 301 B, 0 %, 28 d, Not readily degradable.

Zinc alkyldithiophosphate : OECD TG 301 B, 1.5 %, 28 d, Not readily degradable.

Zinc alkyldithiophosphate : OECD TG 301 B, 1.5 %, 28 d, Not readily degradable.

Diphenylamine : OECD TG 301 D, 26 %, 26 d, Not readily degradable.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Alkaryl amine Bioconcentration Factor (BCF): 1,584.89 (Measured).

Partition Coefficient n-octanol / water (log Kow)

Zinc alkyldithiophosphate Log Kow: 2.21 20°C, 68°F (Measured).

Zinc alkyldithiophosphate : Log Kow: 0.56 (Measured).

Mobility : No data available.

Other Adverse Effects : No data available.

SECTION 13. DISPOSAL CONSIDERATION

WASTE DISPOSAL

This material, if discarded, is not a hazardous waste under RCRA Regulation 40CFR 261. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION for additional handling information and protection of employees.

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 14 of 17

SECTION 14. TRANSPORTATION INFORMATION

U.S. DOT : Not regulated as dangerous goods.

IMDG Not regulated as dangerous goods.

IATA Not regulated as dangerous goods.

Special Precautions for :

User

No special precautions.

Shipping description may vary based on mode of transport, quantities, temperatures of the material, package size, percent of each component, and/or origin and destination it is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. For transportation, steps must be taken to prevent load shifting or materials falling, and all relating legal statutes should be obeyed. Review classification requirements before shipping materials at elevated temperatures.

SECTION 15. REGULATORY INFORMATION

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable Quantity

Alkylated phenol De minimis concentration: 0.1% Diphenylamine De minimis concentration: 0.1%

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard: No

Delayed Hazard: No Fire Hazard: No Pressure Hazard: No Reactivity Hazard: No

SARA 302 Extremely Hazardous Substance

SARA 304 Emergency Release Notification

SARA 311/312 Hazardous Chemical

SARA 313 (TRI Reporting)

This product may contain chemical(s) regulated under the Superfund Amendments and Reauthorization Act (SARA). For additional information please contact Petron Plus Global, Inc. Customer Assistance: info@petronplus7.com

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 15 of 17

SECTION 15. REGULATORY INFORMATION, Cont.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or cause birth defects or other reproductive harm.

Ethyl benzene 8.00 PPB
Naphthalene 8.00 PPB
Benzene 778.00 PPT
Toluene 777.00 PPT

US. Massachusetts RTK:
US. New Jersey RTK:
US. Pennsylvania RTK:
US. Rhode Island RTK:
Not regulated.
Not regulated.
Not regulated.

International Inventories Status:

Inventory Status

Australia (AICS) : All components are in compliance with chemical notification requirements in

Australia.

Canada (DSL/NDSL) : All components are in compliance with Canadian Environmental Protection Act

and are present on the Domestic Substances List.

China (IECSC)All components of this product are listed on the Inventory of Existing Chemical

Substances in China.

European Union : All components of this product are listed on the Inventory of Existing Commercial

Chemical Substances (EINECS).

Japan (ENCS)All components are in compliance with the Chemical Substances Control Law of

Japan.

New Zealand (NZIoC) : All components are in compliance with chemical notification requirements in New

Zealand.

Philippines (PICCS) : All components are in compliance with the Philippines Toxic Substances and

Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

Taiwan (TCSCA)All components of this product are listed on the Taiwan inventory.

United States (TSCA) : All components of this material are on the US TSCA Inventory or are exempt.

The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.

Part No. 12121-12oz, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g -

Revision Date: 18-March-2015 - P. 16 of 17

SECTION 16.

OTHER INFORMATION

Key literature references and sources for data:

Internal company data, suppliers and other publicly available resources.

HMIS Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible.

Revision Date:

18-March-2015

Updated to Format.

Kev to Abbreviations:

ACGIH = American Conference of Government Industrial Hygienists; API = American Petroleum Institute; ATE = Acute Toxicity Estimate; BCF = Bioconcentration Factor; CAS/CASRN = Chemical Abstracts Service Registry Number, CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; DOT = Department of Transportation (USA); EPA = Environmental Protection Agency; GHS = Globally Harmonization System; IARC = International Agency for Research for Cancer; IATA = International Air Transport Association; IBC = Intermediate Bulk Container; IMO/IMDG = International Maritime Dangerous Goods Code; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; LogPow = Logarithm of the octanol/water partition coefficient; MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships; 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution); NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SDS = Safety Data Sheet; SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weight Average (8 hours); UEL = Upper Explosive Limit; UN = United Nations; WHMIS = Worker Hazardous Materials Information System (Canada).

Part No. 12121-120z, 12121-1g, 12121-5g, 12121-54g, 12121-275g 12121-330g

Revision Date: 18-March-2015 - P. 17 of 17

SECTION 16. OTHER INFORMATION, Cont.

Notice to reader:

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSION DRAWN HEREIN ARE FORM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABLE OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MANY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESS DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.

No responsibility is assumed for any damage or injury resulting from abnormal use from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.