





Conforms to OSHA HCS 2012 (29 CFR 1910.1200) SAFETY DATA SHEET

PETRON PLUSTM HI-TEMP, EXTREME-PRESSURE, MULTI-PURPOSE POLYUREA GREASE

Part No. 00950-14 oz, 00950-35-lbs, 00950-120 lbs, & 00950-400 lbs

SECTION 1. PREPARATION INFORMATION

Date : March 18, 2015

1.1 **Product Identifier**

Material Name : Petron Plus Hi-Temp, Extreme-Pressure, Multi-Purpose Polyurea

Grease

Product Code : 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use : Automotive and Industrial Grease.

Uses advised against : This product must not be used in applications other than

recommended in Section 1 without taking the advice from

supplier/manufacturer.

1.3 Details of supplier of safety data sheet.

Manufacturers/Supplier: PETRON PLUS GLOBAL, INC.

P. O. BOX 1906 208 East 2nd

HUTCHINSON, KS. 67504-1906 USA

Telephone Number : 620/663-1800 **Emergency Telephone** : 620/200-3338

Number

Email Address : info@petronplus7.com



Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - **P. 2 of 13**

SECTION 2. HAZARDOUS IDENTIFICATION

2.1 Classification of the substance or mixture

OSHA Hazard Communication Standard

This material is not considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200). This SDS contains valuable

information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees

and other users of this product.

Label elements

Hazardous pictogram : Not Applicable.

OSHA HCS 2012: No significant hazard as per GHS.

Sign word : Not Applicable.

Hazardous statement : Not Applicable.

2.3 Other hazards

Health hazards : This product once produced as completely reacted resultant product

on its ingredients is not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning may clog the skin pores resulting in disorders like acne/folliculitis. However, the one or more ingredients (CAS # 101-68-8, 112-90-3) used to make this grease which is expected to completely react in final stage to form grease, may/do have health hazard which are explained in Section 8. Used grease may contain

harmful impurities/ harmful extraneous substances.

Safety hazard : Not classified as flammable but will burn.

Environment hazard : Not classified as environmental hazard under GHS criteria.

Precautionary statements:

Prevention : Wear protective gloves while handling. Wear eye and face protection.

Wash hands thoroughly after handling.

Response : If on skin; wash with plenty of soap and water. Remove contaminated

clothing and shoes. Launder contaminated clothing before reuse. If in eyes, wash with water for several minutes, in case of contact lenses,

remove and wash with plenty of water. In case of irritating, get

medical attention. In case of high-pressure injection skin may cause

serious damage, get medical attention.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 3 of 13

SECTION 2. HAZARDOUS IDENTIFICATION, Cont.

Precautionary statements, Cont.:

Storage : Store the product in well-ventilated area. Keep the container upright.

Do not lay down, upside down, or do not keep container horizontally. This product has natural tendency to squeeze oil if not kept properly.

Disposal : Take expert advise of local regulatory agency for disposing of this

product.

Hazards not otherwise

classified (HNOC) : None as classified under 29 CFR 1900.1200

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture : This material is defined as a mixture.

CHEMICAL NAME	CAS#	EC/	%	Classification as	Comment
	Number	REACH	by Weight	per to regulation/	
				directive	

Hydrotreated Heavy naphthenic distillates	64742-52-5 REACH Reg	> 75%	OSHA HCS 2012:	Contains < 3%
	# 01-2119467170-		None	DMSO extract-
	45-001			carcinogen
				classification not
				applicable.

Polyurea thickener and additive	Proprietary /	 < 20%	None	
	mixture			

Additional information:

As per 29 CFR 1910.1200 paragraph (i), formulation is considered as trade secret and therefore specific chemical names and exact percentages of components have been withheld. Specific chemical identity and exact percentages composition may be provided on request to health professionals, authorized representatives of regulatory authority, employees concerned in accordance with applicable provisions of paragraph (i). However, this product contains the reaction product of isocynate compound CAS # 101-68-8) and amine compound (CAS # 112-90-3) which in unreacted form may/do have health hazard whereas the resultant completely reacted product in final form is not reported to possess any serious health / environmental hazards.

SECTION 4. FIRST AID MEASURES

4.1 <u>Description of first aid measures</u>

General information : Not expected to be a health hazard if used under normal conditions.

Inhalation : Under normal conditions of intended use, this material is not expected

to be a inhalation hazard. If some symptom exist, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

BALANCE OF PAGE INTENTIONALLY LEFT BLANK

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 4 of 13

SECTION 4. FIRST AID MEASURES, Cont.

Description of first aid measures, Cont. 4.1

Skin contact Remove contaminated clothing and shoes. Launder contaminated

> clothing before reuse. Flush contaminated skin with plenty of water followed by washing by soap. If persistent irritation occurs, obtain medical attention. If product is injection into or under the skin due to any reason, the victim, regardless of size or appearance of wound, victim should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal / absent, early surgical treatment

may significantly reduce the extent of injury.

Eye contact Immediately flush eyes with plenty of water (for 30 minutes),

> occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Ingestion In general no treatment is necessary unless large quantities are

> swallowed, however, it's advisable to take medical attention. Do Not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

Self-protection for

first aider

When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the incident,

injury and surroundings.

SECTION 5. FIRE-FIGHTING MEASURES

5.1 **Extinguishing media:**

Suitable extinguishing Halon, Dry chemicals, Foam, Carbon dioxide (CO2), Water spray or media

fog. Do not use water jet as an extinguisher, as this will spread the

fire.

Unsuitable extinguishing: Do not use water jet as an extinguisher, as this will spread the fire.

media

5.2 Specific hazards arising from the substance or mixture:

Hazardous combustion product may include a complex mixture of airborne solid liquid particulates and gases (smoke), carbon monoxide, unidentified inorganic and organic compounds.

5.3 Advice for firefighters:

Proper protective equipment include chemical resistant gloves to be worn, chemical resistant suit is recommended when large contact with spill product is expected. Self-contained breathing apparatus (SCBA) must be worn when approaching a fire in confined area. Select the fire fighters clothing approved by relevant standards.

Revision Date: 18-March-2015 - P. 5 of 13

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch and walk through spill area. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing/equipment. Ventilate the closed areas.

Emergency procedures

Isolate the spill / leak area in all directions for about 150 feet (50 meters) for liquids and about 75 feet (25 meters) for solids and semi-solids. Eliminate all sources of ignition or flammable (no smoking, sparks, flames, etc.) that may come into contact with a spill of this material, if this can be done without risk. Keep unauthorized person away and ventilate closed spaces before entering. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Contain the discharge material.

Environmental procedures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.4 Methods and materials for containment and cleaning up

<u>For Small Spills</u>: Ventilate area, wear chemical splash goggles. Wear rubber boots. Prevent entry into sewers, waterways. Pick up free liquid for recycle or disposal. Absorb small amount on inert material for disposal, or shovel into suitable properly marked container for disposal or reclamation in accordance with local regulations.

For Large Spills: Personal Protective Equipment must be worn. Avoid skin contact. Use skin protection. See Personal Protection Section for additional PPE recommendations. Take precautions to avoid release to the environment. Ventilate area if spilled in confined space or other poorly ventilated area. Prevent entry into sewer and waterway. Pick-up free solids, semi-solids, liquid for recycle and/or disposal. Residual solids, slime-solids, liquid can be absorbed on inert material, or shovel into suitable properly marked container for disposal or reclamation in accordance with local regulations.

6.5 Reference to other sections

Refer to Section 8 - exposure control / personal protection and Section 13 - disposal considerations

SECTION 7. HANDLING AND STORAGE

7.1 General Precautions

Store in well-ventilated area, if risk of vapor inhalation is there. Use the information in this safety data sheet as input for risk management arising due to local conditions which help to manage safe handling of this product.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 6 of 13

SECTION 7. HANDLING AND STORAGE, Cont.

7.2 Precautions for safe handling

Avoid prolonged and repeated contact with skin. Avoid inhaling the vapors/mist. When handling the drums, kegs, pails, etc., proper safety shoes, and other protective clothes, safety glasses, etc. should be worn. Dispose appropriately any contaminated rags/material as per prevailing local allowable practices. Keep containers in closely tight and, cool and well ventilated areas.

7.3 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in dry, cool and well-ventilated area, preferably < 120°F (< 50°C) and away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and keep upright to prevent leaking. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.4 Specific End Use(s):

This material should not be used for any other purpose that the intended use per Section 1 without expert advice.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 <u>Control parameters</u>

Material	Source	Type	ppm	mg/m3	Notation
Mineral oil mist	ACGIH	TWA (inhalable fraction)		5 mg/m3	
MDI (CAS # 101-68-8)	ACGIH	TWA	0.005		

Additional information:

Due to semi-solid nature of the product, generation of mist and dust is unlikely to occur.

Biological exposure index (BEI):

No biological limit allocated.

PNEC related information:

Data not available.

Monitoring methods:

Monitoring of the concentration of substances in the breathing zone of workers or in general workplace may be required to confirm the compliance with local governing authority.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 7 of 13

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.2 Engineering measures/controls

Adequate ventilation systems may be needed to control concentration of airborne contaminants above permissible threshold applicable limits.

8.3 Personal protective equipment pictograms









Respiratory:

In case of insufficient ventilation, use suitable respiratory equipment.

Eye/face protection:

Wear safety goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety goggles.

Skin / Body:

Wear safety shoes and protective gloves.

8.4 Environmental Exposure Controls:

Minimize release to the environment. Follow best practices for site management and disposal of waste as per local regulations.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on physical and chemical properties

Physical state : Semi Solid Grease

Color : Blue.

Odor : Slight hydrocarbon.

Odor threshold : Not available.
pH : Not applicable.
Pour point : Not applicable.
Boiling point : Not available.

BALANCE OF PAGE INTENTIONALLY LEFT BLANK

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - **P. 8 of 13**

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES, Cont.

Information on physical and chemical properties, Cont.

Flash point : > 400°F (204°C).

Evaporation rate : Not available.

Flammability (Solid, gas) : Not available.

Lower and upper explosive: Not available.

(flammable) limits

Vapor pressure @ ambient: < 0.13 kPa (< 1 mm Hg)

temperature

Vapor density (Air = 1) : <1

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available. **Decomposition** : Not available.

temperature

Specific Gravity: : 0.87

Density : 7.506 (lbs/gal).

Electrical conductivity : Though no data is available, this material is not expected to be a static

accumulator.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity : No specific test data related to reactivity available for this product or

its ingredients. However, under high temperatures of adverse

operating conditions thermal / chemical decomposition of the product

may be possible.

10.2 Chemical stability

No hazardous reaction is expected under normal conditions of

temperatures and pressure.

10.3 Possibility of hazardous

reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

10.4 Conditions to avoid

Extreme temperatures and direct sunlight / heat, flames and sources

of ignition.

10.5 Incompatible material

Reactive or incompatible with the following materials:

Strong oxidizing agents.

10.6 Hazardous Polymerization

Hazardous decomposition is not expected to form under normal

conditions of storage.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 9 of 13

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological information

Basis of assessment	:	Information given hereby is based on the components and the toxicology of similar products and the data indicated here are representative of mainly base oil which is present in majority.
Acute oral toxicity	:	This product does not have to be classified. Test data not available. Ingestion of large quantities may cause discomfort.
Acute dermal toxicity	:	This product does not have to be classified. Test data not available.
Acute inhalation toxicity	7 :	This product does not have to be classified. Test data not available.
Skin corrosion / irritatio	n:	This product does not have to be classified. Test data not available. Degrease the skin, long term exposure may cause irritation and possible infection.
Serious eye damage / irr	itation :	This product does not have to be classified. Test data not available. Temporary irritation possible.
Respiratory / skin sensit	ization	
	:	Not determined. May cause sensitization by skin contact. Symptoms may include redness, swelling, blistering, ulceration though often develops slowly.
Aspiration hazard	:	Not expected to be aspiration hazard, based on physical-chemical properties of the material.
Germ cell mutagenicity	:	Based on assessment of components, not classifiable to be germ cell mutagen. Test data not available.
Carcinogenicity	:	Based on assessment of components, not classifiable carcinogen. Test data not available.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 10 of 13

SECTION 11. TOXICOLOGICAL INFORMATION, Cont.

11.2 Material

Carcinogenicity Classification

Highly refined base oil blend (IP 346 < 3 %)

ACGIH group A4; not classified as human carcinogen.

IARC 3; not classified as to carcinogen to humans.

GHS / CLP, no carcinogenicity classification.

Based on our raw material suppliers information/SDS, this material is not known to contain any chemical listed as a carcinogen or suspected carcinogen by OSHA Hazard Communication Standard 29CFR 1910.1200, IARC, or the National Toxicology Program (NTP).

SECTION 12. ECOLOGICAL INFORMATION

Basis of assessment

Eco-toxicological data has not been determined specifically on this product. The information given herewith are based on the information given on eco-toxicity of components and/or on similar products. The information given here are representative of the product as whole and not as individual components.

12.1 Toxicity

Sparingly soluble mixture in aqueous media. Not toxic to fish but may coat gill structure and cause suffocation if spilled. This may cause gastrointestinal distress in birds and mammals through ingestion.

12.2 Persistence and degradability

Expected to be not readily biodegradable. This major oil component expected to biodegrade over period of 100-120 days in aerobic environment at temperatures above 70°F (21°C), however finished product contains components that may persist in the environment.

12.3 Bioaccumulative potential

May contain components that bioaccumulate.

12.4 Mobility in soil

Product is semi-solid in nature in most conditions and may absorb to soil and may not be mobile. It floats on water.

12.5 Other Adverse Effects

Product contains the component that have been classified non-volatile

in nature and therefore not expected to release to environment in

significant quantities.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 11 of 13

SECTION 13. DISPOSAL CONSIDERATION

Disposal recommendation is based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material at the time of disposal which may vary at the time of disposal.

13.1 Waste treatment methods

:

Product disposal

Try to minimize the product waste by using best applicable practices. It is the responsibility of the waste generator to evaluate the waste classification and appropriate disposal methodology in accordance with the applicable regulation. Do not dispose in to environment, in drain or in river / ponds / water reservoirs.

Regulatory Disposal information

To the best of Petron Plus Global, Inc. knowledge, this product is not listed by EPA as a hazardous waste (40 CFR, Part 261 D) and also not formulated specifically to contain reactant materials which listed as hazardous waste. However used product may be regulated.

Empty Container Warning

Do not attempt to refill or clean containers since residue is difficult to remove. Empty drums should be completely drained, properly bunged and returned to a drum re-conditioner. All containers should be disposed of in an environmentally safe manner and in accordance with government regulations.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 14.	TRANSPORTATION INFORMATION						
	Bulk Shipping	Non-bulk Shipping	Identification Number	Hazardous Class			
US DOT	Not required	Not required	Not required	Not required			
Canada TDG	Not required	Not required	Not required	Not required			
European	Not required	Not required	Not required	Not required			
ADR, IMDG, IATA-DGR	Not classified as	hazardous product for la	and, sea and air transport				

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 12 of 13

SECTION 15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This material is considered hazardous in accordance with OSHA

HazCom 2012, 29 CFR 1910.1200

US Inventory List : All components are listed or exempted.

(TSCA 8b)

SARA 302/304 : No products were found.

SARA 311/312 : None.

Classification : Immediate (acute) health hazard, delayed (chronic) health hazard.

SARA 313 : This product contain no chemical subject to the supplier notification

requirements of the SARA 313 Toxic Release Program.

Listed or exempt from listing / notification on the following chemical inventories: AICS, IECSC, TSCA

Inventory	Status
KECI	Restrictions apply
NDSL	Restrictions apply

SECTION 16. OTHER INFORMATION

NFPA 704



HMIS



0 (Minimal)

1 (Slight)

2 (Moderate)

3 (Serious)

4 (Severe)

Reprinted with permission from NFPA 704-2001, identification of the Hazards of Materials for Emergency Response Copyright 1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright 2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Part No. 00950-14 oz, 00950-35 lbs, 00950-120 lbs & 00950-400 lbs

Revision Date: 18-March-2015 - P. 13 of 13

SECTION 16. OTHER INFORMATION, Cont.

Revision Date: 18-March-2015

Updated to Format.

Key to Abbreviations:

ACGIH = American Conference of Government Industrial Hygienists; API = American Petroleum Institute; ATE = Acute Toxicity Estimate; BCF = Bioconcentration Factor; CAS/CASRN = Chemical Abstracts Service Registry Number, CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; DOT = Department of Transportation (USA); EPA = Environmental Protection Agency; GHS = Globally Harmonization System; IARC = International Agency for Research for Cancer; IATA = International Air Transport Association; IBC = Internediate Bulk Container; IMO/IMDG = International Maritime Dangerous Goods Code; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; LogPow = Logarithm of the octanol/water partition coefficient; MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships; 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution); NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SDS = Safety Data Sheet; SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weight Average (8 hours); UEL = Upper Explosive Limit; UN = United Nations; WHMIS = Worker Hazardous Materials Information System (Canada).

Notice to reader:

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSION DRAWN HEREIN ARE FORM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABLE OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MANY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESS DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.

No responsibility is assumed for any damage or injury resulting from abnormal use from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.